

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : SikaPower®-751 (H 9951-1) Part B

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive, Product is not intended for consumer use

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited  
Watchmead Welwyn Garden City  
Hertfordshire. AL7 1BQ  
Telephone : +44 (0)1707 394444  
Telefax : +44 (0)1707 329129  
E-mail address of person : EHS@uk.sika.com  
responsible for the SDS

#### 1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC)  
24 Hour Emergency Telephone Number +44 870 190 6777

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

|                                                                        |                                                                                       |
|------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Acute toxicity, Category 4                                             | H302: Harmful if swallowed.                                                           |
| Skin corrosion, Category 1                                             | H314: Causes severe skin burns and eye damage.                                        |
| Serious eye damage, Category 1                                         | H318: Causes serious eye damage.                                                      |
| Skin sensitisation, Category 1                                         | H317: May cause an allergic skin reaction.                                            |
| Reproductive toxicity, Category 2                                      | H361d: Suspected of damaging the unborn child.                                        |
| Specific target organ toxicity - repeated exposure, Category 2, Kidney | H373: May cause damage to organs through prolonged or repeated exposure if swallowed. |
| Long-term (chronic) aquatic hazard, Category 3                         | H412: Harmful to aquatic life with long lasting effects.                              |

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

|                          |   |                           |                                                                                                                                                                            |
|--------------------------|---|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hazard statements        | : | H302                      | Harmful if swallowed.                                                                                                                                                      |
|                          | : | H314                      | Causes severe skin burns and eye damage.                                                                                                                                   |
|                          | : | H317                      | May cause an allergic skin reaction.                                                                                                                                       |
|                          | : | H361d                     | Suspected of damaging the unborn child.                                                                                                                                    |
|                          | : | H373                      | May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.                                                                                   |
|                          | : | H412                      | Harmful to aquatic life with long lasting effects.                                                                                                                         |
| Precautionary statements | : | <b>Prevention:</b>        |                                                                                                                                                                            |
|                          | : | P201                      | Obtain special instructions before use.                                                                                                                                    |
|                          | : | P260                      | Do not breathe mist or vapours.                                                                                                                                            |
|                          | : | P280                      | Wear protective gloves/ protective clothing/ eye protection/ face protection.                                                                                              |
|                          | : | <b>Response:</b>          |                                                                                                                                                                            |
|                          | : | P303 + P361 + P353        | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.                                                                               |
|                          | : | P304 + P340 + P310        | IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.                                                       |
|                          | : | P305 + P351 + P338 + P310 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. |

### Hazardous components which must be listed on the label:

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine  
benzyl alcohol  
Methyleneoxide, polymer with benzenamine, hydrogenated  
3,6-diazaoctanethylenediamin  
salicylic acid  
3-aminomethyl-3,5,5-trimethylcyclohexylamine  
4,4'-methylenebis(cyclohexylamine)  
N-(3-(trimethoxysilyl)propyl)ethylenediamine  
Phenol, styrenated

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

| Chemical name                                                                                                      | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number          | Classification                                                                                                                                                                                                     | Concentration<br>(% w/w) |
|--------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylene-tetramine | 68082-29-1<br>500-191-5<br>01-2119972320-44-XXXX               | Skin Irrit. 2; H315<br>Eye Dam. 1; H318<br>Skin Sens. 1A; H317<br>Aquatic Chronic 2; H411                                                                                                                          | >= 20 - < 25             |
| benzyl alcohol                                                                                                     | 100-51-6<br>202-859-9<br>603-057-00-5<br>01-2119492630-38-XXXX | Acute Tox. 4; H302<br>Eye Irrit. 2; H319<br>Skin Sens. 1B; H317<br><br>Acute toxicity estimate<br><br>Acute oral toxicity:<br>1.200 mg/kg                                                                          | >= 10 - < 20             |
| Methyleneoxide, polymer with benzenamine, hydrogenated                                                             | 135108-88-2<br>603-894-6<br>01-2119983522-33-XXXX              | Acute Tox. 3; H301<br>Skin Corr. 1C; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1; H317<br>STOT RE 2; H373 (Kidney)<br>Aquatic Chronic 3; H412<br><br>Acute toxicity estimate<br><br>Acute oral toxicity:<br>300 mg/kg | >= 10 - < 20             |
| Glyceryl poly(oxypropylene)triamine                                                                                | 64852-22-8<br>Not Assigned                                     | Skin Irrit. 2; H315<br>Eye Dam. 1; H318<br>Aquatic Chronic 3; H412                                                                                                                                                 | >= 5 - < 10              |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025

Version 3.0

Print Date 02.09.2025

Revision Date: 02.09.2025

|                                                                                                   |                                                                                            |                                                                                                                                                                                                                                                                |              |
|---------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| 3,6-diazaoctanethylenediamin                                                                      | 112-24-3<br>203-950-6<br>612-059-00-5<br>01-2119487919-13-XXXX (covered by CAS 90640-67-8) | Acute Tox. 4; H302<br>Acute Tox. 4; H312<br>Skin Corr. 1B; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1; H317<br>Aquatic Chronic 3; H412<br><br>Acute toxicity estimate<br><br>Acute oral toxicity: 1.716 mg/kg<br>Acute dermal toxicity: 1.465 mg/kg              | >= 5 - < 10  |
| salicylic acid                                                                                    | 69-72-7<br>200-712-3<br>607-732-00-5<br>01-2119486984-17-XXXX                              | Acute Tox. 4; H302<br>Eye Dam. 1; H318<br>Repr. 2; H361d<br><br>Acute toxicity estimate<br><br>Acute oral toxicity: 891 mg/kg                                                                                                                                  | >= 3 - < 5   |
| 2-methylpentane-1,5-diamine                                                                       | 15520-10-2<br>239-556-6<br>01-2119976310-41-XXXX                                           | Acute Tox. 4; H302<br>Acute Tox. 4; H332<br>Acute Tox. 4; H312<br>Skin Corr. 1A; H314<br>Eye Dam. 1; H318<br>STOT SE 3; H335 (Respiratory system)<br><br>Acute toxicity estimate<br><br>Acute oral toxicity: 1.170 mg/kg<br>Acute dermal toxicity: 1.870 mg/kg | >= 2,5 - < 3 |
| 2,4,6-tris(dimethylaminomethyl)phenol<br>Contains:<br>bis[(dimethylamino)methyl]phenol<br><= 15 % | 90-72-2<br>202-013-9<br>603-069-00-0<br>01-2119560597-27-XXXX                              | Acute Tox. 4; H302<br>Skin Irrit. 2; H315<br>Eye Irrit. 2; H319<br><br>Acute toxicity estimate<br><br>Acute oral toxicity: 1.999 mg/kg                                                                                                                         | >= 1 - < 2,5 |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

|                                                                                                                                                                                        |                                                                           |                                                                                                                                                                                                                                                       |             |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| 3-aminomethyl-3,5,5-trimethylcyclohexylamine                                                                                                                                           | 2855-13-2<br>220-666-8<br>612-067-00-9<br>01-2119514687-32-XXXX           | Acute Tox. 4; H302<br>Skin Corr. 1B; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1A; H317<br><br>specific concentration limit<br>Skin Sens. 1A; H317<br>≥ 0,001 %<br><br>Acute toxicity estimate<br><br>Acute oral toxicity:<br>1.030 mg/kg<br>1.030 mg/kg | ≥ 1 - < 2,5 |
| 4,4'-methylenebis(cyclohexylamine)                                                                                                                                                     | 1761-71-3<br>217-168-8<br>01-2119541673-38-XXXX                           | Acute Tox. 4; H302<br>Skin Corr. 1B; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1B; H317<br>STOT RE 2; H373<br><br>Acute toxicity estimate<br><br>Acute oral toxicity:<br>380 mg/kg                                                                       | ≥ 1 - < 2,5 |
| N-(3-(trimethoxysilyl)propyl)ethylenediamine<br>Contains:<br>N,N'-bis[3-(trimethoxysilyl)propyl]ethylenediamine ≤ 3 %<br>1-(2-Aminoethyl)-2,2-dimethoxy-1-aza-2-silacyclopentane ≤ 3 % | 1760-24-3<br>217-164-6<br>01-2119970215-39-XXXX                           | Eye Dam. 1; H318<br>Skin Sens. 1B; H317<br>STOT SE 3; H335<br>(Respiratory system)                                                                                                                                                                    | ≥ 1 - < 2,5 |
| Phenol, styrenated                                                                                                                                                                     | Not Assigned<br>701-443-9<br>01-2119980970-27-XXXX, 01-2119979575-18-XXXX | Skin Irrit. 2; H315<br>Skin Sens. 1A; H317<br>Aquatic Chronic 2; H411                                                                                                                                                                                 | ≥ 0,5 - < 1 |

For explanation of abbreviations see section 16.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- |                         |   |                                                                                                                                                                                                                                                                                                                 |
|-------------------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General advice          | : | Move out of dangerous area.<br>Consult a physician.<br>Show this safety data sheet to the doctor in attendance.                                                                                                                                                                                                 |
| If inhaled              | : | Move to fresh air.<br>Consult a physician after significant exposure.                                                                                                                                                                                                                                           |
| In case of skin contact | : | Take off contaminated clothing and shoes immediately.<br>Wash off with soap and plenty of water.<br>Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.                                                                                    |
| In case of eye contact  | : | Small amounts splashed into eyes can cause irreversible tissue damage and blindness.<br>In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.<br>Continue rinsing eyes during transport to hospital.<br>Remove contact lenses.<br>Keep eye wide open while rinsing. |
| If swallowed            | : | Do not induce vomiting without medical advice.<br>Rinse mouth with water.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person.                                                                                                                                 |

#### 4.2 Most important symptoms and effects, both acute and delayed

- |          |   |                                                                                                                                                                                                                                                                                                                                      |
|----------|---|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms | : | Gastrointestinal discomfort<br>Allergic reactions<br>Dermatitis<br>See Section 11 for more detailed information on health effects and symptoms.                                                                                                                                                                                      |
| Risks    | : | Health injuries may be delayed.<br>corrosive effects<br>sensitising effects<br><br>Harmful if swallowed.<br>May cause an allergic skin reaction.<br>Causes serious eye damage.<br>Suspected of damaging the unborn child.<br>May cause damage to organs through prolonged or repeated exposure if swallowed.<br>Causes severe burns. |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

---

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Store in accordance with local regulations.
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : Consult most current local Product Data Sheet prior to any use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Contains no substances with occupational exposure limit values.

#### Occupational exposure limits of decomposition products

| Components | CAS-No.                                                                                                                    | Value type (Form of exposure) | Control parameters *             | Basis *    |
|------------|----------------------------------------------------------------------------------------------------------------------------|-------------------------------|----------------------------------|------------|
| methanol   | 67-56-1                                                                                                                    | TWA                           | 200 ppm<br>260 mg/m <sup>3</sup> | 2006/15/EC |
|            | Further information: Indicative, Identifies the possibility of significant uptake through the skin                         |                               |                                  |            |
|            |                                                                                                                            | TWA                           | 200 ppm<br>266 mg/m <sup>3</sup> | GB EH40    |
|            | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that |                               |                                  |            |



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

|  |                                                   |      |                      |         |
|--|---------------------------------------------------|------|----------------------|---------|
|  | dermal absorption will lead to systemic toxicity. |      |                      |         |
|  |                                                   | STEL | 250 ppm<br>333 mg/m3 | GB EH40 |

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166  
Wear eye/face protection.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.  
Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

#### Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance : liquid  
Colour : red  
Odour : amine-like

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

#### Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 101 °C  
Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : 9 - 12  
Concentration: 100 %

#### Viscosity

Viscosity, kinematic : No data available

#### Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 0,07 hPa

Density : ca. 1,00 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : No data available

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

Hazardous decomposition products : methanol

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Harmful if swallowed.

#### Components:

##### benzyl alcohol:

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008  
  
LD50 Oral (Rat): 1.200 mg/kg  
  
Acute inhalation toxicity : LC50 (Rat): > 4,178 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### Methyleneoxide, polymer with benzenamine, hydrogenated:

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

Acute oral toxicity : LD50 Oral (Rat): 300 mg/kg

Acute toxicity estimate: 300 mg/kg  
Method: Calculation method

### Glyceryl poly(oxypropylene)triamine:

Acute oral toxicity : LD50 Oral (Rat): 2.690 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 12.500 mg/kg

### 3,6-diazaoctanethylenediamin:

Acute oral toxicity : LD50 Oral (Rat): 1.716 mg/kg

Acute toxicity estimate: 1.716 mg/kg  
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rabbit): 1.465 mg/kg

Acute toxicity estimate: 1.465 mg/kg  
Method: Calculation method

### salicylic acid:

Acute oral toxicity : LD50 Oral (Rat): 891 mg/kg

Acute toxicity estimate: 891 mg/kg  
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg

### 2-methylpentane-1,5-diamine:

Acute oral toxicity : LD50 Oral (Rat): 1.170 mg/kg

Acute toxicity estimate: 1.170 mg/kg  
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rabbit): 1.870 mg/kg

Acute toxicity estimate: 1.870 mg/kg  
Method: Calculation method

### 2,4,6-tris(dimethylaminomethyl)phenol:

Acute oral toxicity : LD50 (Rat): > 1.999 mg/kg  
Remarks: Harmful if swallowed.  
Annex VI - Harmonised  
REGULATION (EC) No 1272/2008

### 3-aminomethyl-3,5,5-trimethylcyclohexylamine:

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

Acute oral toxicity : Acute toxicity estimate: 1.030 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

Acute toxicity estimate: 1.030 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

LD50 Oral (Rat): 1.030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg  
LD50 (Rabbit): > 2.000 - 5.000 mg/kg

### **4,4'-methylenebis(cyclohexylamine):**

Acute oral toxicity : LD50 Oral (Rat): 380 mg/kg

Acute toxicity estimate: 380 mg/kg  
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rabbit): 2.110 mg/kg

### **N-(3-(trimethoxysilyl)propyl)ethylenediamine:**

Acute oral toxicity : LD50 Oral (Rat): 2.995 mg/kg

### **Phenol, styrenated:**

Acute oral toxicity : LD50 Oral (Rat): 2.500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): > 5.000 mg/kg

### **Skin corrosion/irritation**

Causes severe burns.

### **Components:**

#### **2,4,6-tris(dimethylaminomethyl)phenol:**

Species : Rabbit  
Assessment : Corrosive  
Method : OECD Test Guideline 404

Assessment : irritating  
Remarks : Annex VI - Harmonised  
REGULATION (EC) No 1272/2008

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

### Serious eye damage/eye irritation

Causes serious eye damage.

#### Components:

##### **2,4,6-tris(dimethylaminomethyl)phenol:**

|            |   |                                                       |
|------------|---|-------------------------------------------------------|
| Species    | : | Rabbit                                                |
| Assessment | : | Causes serious eye damage.                            |
| Assessment | : | irritating                                            |
| Remarks    | : | Annex VI - Harmonised<br>REGULATION (EC) No 1272/2008 |

### Respiratory or skin sensitisation

#### **Skin sensitisation**

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

Not classified due to lack of data.

#### Components:

##### **4,4'-methylenebis(cyclohexylamine):**

|            |   |                                                    |
|------------|---|----------------------------------------------------|
| Test Type  | : | Buehler Test                                       |
| Assessment | : | The product is a skin sensitiser, sub-category 1B. |
| Result     | : | The product is a skin sensitiser, sub-category 1B. |

### Germ cell mutagenicity

Not classified due to lack of data.

### Carcinogenicity

Not classified due to lack of data.

### Reproductive toxicity

Suspected of damaging the unborn child.

### STOT - single exposure

Not classified due to lack of data.

### STOT - repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.

### Aspiration toxicity

Not classified due to lack of data.

## 11.2 Information on other hazards

### Endocrine disrupting properties

Not classified due to lack of data.

#### Product:

|            |   |                                                           |
|------------|---|-----------------------------------------------------------|
| Assessment | : | The substance/mixture does not contain components consid- |
|------------|---|-----------------------------------------------------------|

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

##### **Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and tri-ethylenetetramine:**

|                                                                        |   |                                                                                                                                                                                     |
|------------------------------------------------------------------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Toxicity to fish                                                       | : | LC50 (Brachydanio rerio (zebrafish)): 7,07 mg/l<br>Exposure time: 96 h                                                                                                              |
| Toxicity to algae/aquatic plants                                       | : | EC50 (Pseudokirchneriella subcapitata (green algae)): 4,34 mg/l<br>Exposure time: 72 h<br><br>NOEC (Pseudokirchneriella subcapitata (green algae)): 0,5 mg/l<br>Exposure time: 72 h |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | EC50: 7,07 mg/l<br>Exposure time: 48 d<br>Species: Daphnia sp. (water flea)                                                                                                         |

##### **benzyl alcohol:**

|                                                     |   |                                                                      |
|-----------------------------------------------------|---|----------------------------------------------------------------------|
| Toxicity to fish                                    | : | LC50 (Fish): > 100 mg/l<br>Exposure time: 96 h                       |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): > 100 mg/l<br>Exposure time: 48 h |

##### **Glyceryl poly(oxypropylene)triamine:**

|                  |   |                                             |
|------------------|---|---------------------------------------------|
| Toxicity to fish | : | LC50 (Fish): 68 mg/l<br>Exposure time: 96 h |
|------------------|---|---------------------------------------------|

##### **3,6-diazaoctanethylenediamin:**

|                                                     |   |                                                                                |
|-----------------------------------------------------|---|--------------------------------------------------------------------------------|
| Toxicity to fish                                    | : | LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l<br>Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia (water flea)): 10 - 100 mg/l<br>Exposure time: 48 h              |
| Toxicity to algae/aquatic                           | : | EC50 (Pseudokirchneriella subcapitata (green algae)): 10 -                     |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

plants 100 mg/l  
Exposure time: 72 h

### 3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l  
Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 1,5 mg/l  
Exposure time: 72 h

### 4,4'-methylenebis(cyclohexylamine):

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50: 6,84 mg/l  
Exposure time: 48 h  
Species: Daphnia magna (Water flea)

## 12.2 Persistence and degradability

No data available

## 12.3 Bioaccumulative potential

No data available

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

## 12.6 Endocrine disrupting properties

### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## 12.7 Other adverse effects

### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- European Waste Catalogue : 20 01 27\* paint, inks, adhesives and resins containing dangerous substances
- Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

### SECTION 14: Transport information

#### 14.1 UN number or ID number

- ADR : UN 2735
- IMDG : UN 2735
- IATA : UN 2735

#### 14.2 UN proper shipping name

- ADR : POLYAMINES, LIQUID, CORROSIVE, N.O.S.  
(3,6-diazaoctanethylenediamin, Methyleneoxide, polymer with benzenamine, hydrogenated)
- IMDG : POLYAMINES, LIQUID, CORROSIVE, N.O.S.  
(3,6-diazaoctanethylenediamin, Methyleneoxide, polymer with benzenamine, hydrogenated)
- IATA : Polyamines, liquid, corrosive, n.o.s.  
(3,6-diazaoctanethylenediamin, Methyleneoxide, polymer with benzenamine, hydrogenated)

#### 14.3 Transport hazard class(es)

- |     | Class | Subsidiary risks |
|-----|-------|------------------|
| ADR | : 8   |                  |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

**IMDG** : 8

**IATA** : 8

### 14.4 Packing group

#### ADR

Packing group : III  
Classification Code : C7  
Hazard Identification Number : 80  
Labels : 8  
Tunnel restriction code : (E)

#### IMDG

Packing group : III  
Labels : 8  
EmS Code : F-A, S-B

#### IATA (Cargo)

Packing instruction (cargo aircraft) : 856  
Packing instruction (LQ) : Y841  
Packing group : III  
Labels : Corrosive

#### IATA (Passenger)

Packing instruction (passenger aircraft) : 852  
Packing instruction (LQ) : Y841  
Packing group : III  
Labels : Corrosive

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

#### IATA (Passenger)

Environmentally hazardous : no

#### IATA (Cargo)

Environmentally hazardous : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH) : Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 12,8% w/w

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 15,4% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations  
Health and Safety at Work Act 1974 & Subsidiary Regulations  
Control of Substances Hazardous to Health Regulations (COSHH)  
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Full text of H-Statements

|       |                                                                                   |
|-------|-----------------------------------------------------------------------------------|
| H301  | : Toxic if swallowed.                                                             |
| H302  | : Harmful if swallowed.                                                           |
| H312  | : Harmful in contact with skin.                                                   |
| H314  | : Causes severe skin burns and eye damage.                                        |
| H315  | : Causes skin irritation.                                                         |
| H317  | : May cause an allergic skin reaction.                                            |
| H318  | : Causes serious eye damage.                                                      |
| H319  | : Causes serious eye irritation.                                                  |
| H332  | : Harmful if inhaled.                                                             |
| H335  | : May cause respiratory irritation.                                               |
| H361d | : Suspected of damaging the unborn child.                                         |
| H373  | : May cause damage to organs through prolonged or repeated exposure if swallowed. |
| H411  | : Toxic to aquatic life with long lasting effects.                                |
| H412  | : Harmful to aquatic life with long lasting effects.                              |

### Full text of other abbreviations

|                  |                                                                                                                                         |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Acute Tox.       | : Acute toxicity                                                                                                                        |
| Aquatic Chronic  | : Long-term (chronic) aquatic hazard                                                                                                    |
| Eye Dam.         | : Serious eye damage                                                                                                                    |
| Eye Irrit.       | : Eye irritation                                                                                                                        |
| Repr.            | : Reproductive toxicity                                                                                                                 |
| Skin Corr.       | : Skin corrosion                                                                                                                        |
| Skin Irrit.      | : Skin irritation                                                                                                                       |
| Skin Sens.       | : Skin sensitisation                                                                                                                    |
| STOT RE          | : Specific target organ toxicity - repeated exposure                                                                                    |
| STOT SE          | : Specific target organ toxicity - single exposure                                                                                      |
| 2006/15/EC       | : Europe. Indicative occupational exposure limit values                                                                                 |
| GB EH40          | : UK. EH40 WEL - Workplace Exposure Limits                                                                                              |
| 2006/15/EC / TWA | : Limit Value - eight hours                                                                                                             |
| GB EH40 / TWA    | : Long-term exposure limit (8-hour TWA reference period)                                                                                |
| GB EH40 / STEL   | : Short-term exposure limit (15-minute reference period)                                                                                |
| ADR              | : European Agreement concerning the International Carriage of Dangerous Goods by Road                                                   |
| CAS              | : Chemical Abstracts Service                                                                                                            |
| DNEL             | : Derived no-effect level                                                                                                               |
| EC50             | : Half maximal effective concentration                                                                                                  |
| GHS              | : Globally Harmonized System                                                                                                            |
| IATA             | : International Air Transport Association                                                                                               |
| IMDG             | : International Maritime Code for Dangerous Goods                                                                                       |
| LD50             | : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaPower®-751 (H 9951-1) Part B

Date of last issue: 09.07.2025  
Revision Date: 02.09.2025

Version 3.0

Print Date 02.09.2025

|        |   |                                                                                                                                                                                                                                      |
|--------|---|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LC50   | : | Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)                                                                                                 |
| MARPOL | : | International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978                                                                                                                        |
| OEL    | : | Occupational Exposure Limit                                                                                                                                                                                                          |
| PBT    | : | Persistent, bioaccumulative and toxic                                                                                                                                                                                                |
| PNEC   | : | Predicted no effect concentration                                                                                                                                                                                                    |
| REACH  | : | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC   | : | Substances of Very High Concern                                                                                                                                                                                                      |
| vPvB   | : | Very persistent and very bioaccumulative                                                                                                                                                                                             |

### Further information

#### Classification of the mixture:

|                   |       |
|-------------------|-------|
| Acute Tox. 4      | H302  |
| Skin Corr. 1      | H314  |
| Eye Dam. 1        | H318  |
| Skin Sens. 1      | H317  |
| Repr. 2           | H361d |
| STOT RE 2         | H373  |
| Aquatic Chronic 3 | H412  |

#### Classification procedure:

|                                     |
|-------------------------------------|
| Calculation method                  |
| Based on product data or assessment |
| Based on product data or assessment |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN