Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE® 243™ THREADLOCKER

Other means of identification: LOCTITE 243 THREADLOCKER 10ML
Product code: IDH1329837
Recommended use of the chemical and restrictions on use

Intended use: Threadlocker
Manufacturer/Importer/Distributor Representative Company

Henkel Adhesive Tech. Vietnam Co., Ltd,
No. 7, Road 9A Bien Hoa II Industrial Zone,
Bien Hoa City,
810000 Dong Nai Province

Vietnam

Phone: +84 (28) 7100 6301
Fax-no.: +84 (28) 7100 6300

E-mail address of person responsible for Safety Data Sheet: ap-ua-psra.sea@henkel.com

Emergency Telephone for Chemical Accidents: FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +84 28 71006388

Section 2. Hazards identification

GHS Classification:

Hazard Class	Hazard Category
Skin sensitizer	Category 1
Chronic hazards to the aquatic environment	Category 3

GHS label elements:

Hazard pictogram:



Signal word: Warning

Hazard statement:	H317 May cause an allergic skin reaction. H412 Harmful to aquatic life with long lasting effects.

Precaution:

Prevention:	P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves.
Response:	P302+P352 IF ON SKIN: Wash with plenty of water. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Tetramethylene dimethacrylate 2082-81-7	10- 30 %	Skin Sensitization 1B H317 Acute hazards to the aquatic environment 2 H401
Poly (4EO) ethylene glycol dimethacrylate 25852-47-5	10- 30 %	Acute hazards to the aquatic environment 3 H402
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	1- 10 %	Acute toxicity 4; Ingestion H302 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 2 H411
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	1- 10 %	Skin Sensitization 1B H317 Acute hazards to the aquatic environment 3 H402
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	1- 10 %	
Ethene, homopolymer 9002-88-4	1- 10 %	
Polyethylene glycol monomethacrylate 25736-86-1	1- 10 %	Acute hazards to the aquatic environment 3 H402
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen maleate 51978-15-5	0.1- 1 %	Skin corrosion/irritation 1B H314 Serious eye damage/eye irritation 1 H318 Skin Sensitization 1 H317
maleic anhydride 108-31-6	< 0.01 %	Acute toxicity 4; Oral H302 Acute toxicity 5; Dermal H313 Skin corrosion/irritation 1B H314 Serious eye damage/eye irritation 1 H318 Respiratory Sensitization 1 H334 Skin Sensitization 1A H317 Specific target organ toxicity - repeated exposure 1; Inhalation H372 Acute hazards to the aquatic environment 3 H402

Section 4. First aid measures

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact: Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion: Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

Section 5. Fire fighting measures

Suitable extinguishing media: water, carbon dioxide, foam, powder

Improper extinguishing media: High pressure waterjet

Specific hazards arising from the chemical: In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

Special protection equipment and precautions for firefighters: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Hazardous combustion products: Toxic and irritating vapors.

Additional fire fighting advice: In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions: Avoid contact with skin and eyes.
Wear protective equipment.
Ensure adequate ventilation.
Keep away from sources of ignition.
See advice in section 8

Environmental precautions: Do not empty into drains / surface water / ground water.

Clean-up methods: Dispose of contaminated material as waste according to Section 13.
For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Section 7. Handling and storage

Handling: Avoid skin and eye contact.
See advice in section 8

Storage: Storage at 8 to 28°C is recommended.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

Particles (insoluble or poorly soluble) not otherwise specified, respirable particles 68611-44-9	**Value type**	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	ACGIH
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles 68611-44-9	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	ACGIH
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles 9002-88-4	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	ACGIH
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles 9002-88-4	**Value type**	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	ACGIH
METHACRYLIC ACID 79-41-4	**Value type**	Time Weighted Average (TWA):
	ppm	20
	Remarks	ACGIH
Methacrylic acid 79-41-4	**Value type**	Time Weighted Average (TWA):
	mg/m³	70
	Remarks	VN OEL
MALEIC ANHYDRIDE, INHALABLE FRACTION AND VAPOR 108-31-6	**Value type**	Time Weighted Average (TWA):
	mg/m³	0.01
	Remarks	ACGIH

Respiratory protection:

Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.
Protective eye equipment should conform to EN166.

Body protection:

Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls:	Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.
General protection and hygiene measures:	The workplace should be equipped with an emergency shower and eye-rinsing facility.
Hygienic measures:	Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working. Take off contaminated clothing and wash before reuse.

Section 9. Physical and chemical properties

Appearance:	Blue liquid
Odor:	Acrylic, Mild
Odor threshold (CA):	No data available.
pH:	Not applicable, Product is non-polar/aprotic.
Melting point / freezing point:	Not applicable, Product is a liquid
Specific gravity:	1.09
Boiling point:	> 150 °C (> 302 °F)
Flash point: (None)	> 100 °C (> 212 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	non flammable
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure: (; 27 °C (80.6 °F))	< 0.1 mm hg
Vapor density:	1
Density:	1.08 g/cm3
Solubility:	Slightly soluble (20 °C)
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	1,300.0 - 3,000.0 mPa.s (Brookfield; Instrument: RVT; speed of rotation: 20 min-1; Spindle No: 3; Method: ;; LCT STM 10; Viscosity Brookfield)
VOC content: (2010/75/EC)	< 3 %

Section 10. Stability and reactivity

Reactivity/Incompatible materials:	Reacts with strong oxidants. Acids. Reducing agents. Strong bases.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions:	Rapid polymerization may generate excessive heat and pressure.
Conditions to avoid:	Stable under normal conditions of storage and use.
Hazardous decomposition products:	carbon oxides. Hydrocarbons nitrogen oxides

Section 11. Toxicological information

Oral toxicity:	Acute toxicity estimate (ATE) : > 2,000 mg/kg Method: Calculation method

Dermal toxicity: Acute toxicity estimate (ATE) : > 2,000 mg/kg
Method: Calculation method

Symptoms of Overexposure**:** None known.

Acute oral toxicity:

Tetramethylene dimethacrylate 2082-81-7	Value type	LD50
	Value	10,066 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Poly (4EO) ethylene glycol dimethacrylate 25852-47-5	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	not specified
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	Value type	LD50
	Value	753 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Value type	LD50
	Value	10,837 mg/kg
	Species	rat
	Method	not specified
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
Ethene, homopolymer 9002-88-4	Value type	Acute toxicity estimate (ATE)
	Value	> 5,000 mg/kg
	Species	
	Method	Expert judgement
Polyethylene glycol monomethacrylate 25736-86-1	Value type	Acute toxicity estimate (ATE)
	Value	> 5,000 mg/kg
	Species	
	Method	Expert judgement
maleic anhydride 108-31-6	Value type	LD50
	Value	1,090 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)

Acute inhalative toxicity:

Poly (4EO) ethylene glycol dimethacrylate 25852-47-5	Value type	Acute toxicity estimate (ATE)
	Value	> 5 mg/l
	Exposure time	
	Species	
	Method	Expert judgement
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Value type	Acute toxicity estimate (ATE)
	Value	28.17 mg/l
	Exposure time	
	Species	
	Method	Expert judgement
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	Value type	LC50
	Value	> 5.01 mg/l
	Exposure time	4 h
	Species	rat
	Method	OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class (ATC) Method)
Ethene, homopolymer 9002-88-4	Value type	Acute toxicity estimate (ATE)
	Value	> 5 mg/l
	Exposure time	4 h
	Species	
	Method	Expert judgement
Polyethylene glycol monomethacrylate 25736-86-1	Value type	Acute toxicity estimate (ATE)
	Value	> 5 mg/l
	Exposure time	
	Species	
	Method	Expert judgement

Acute dermal toxicity:

Tetramethylene dimethacrylate 2082-81-7	Value type	LD50
	Value	> 3,000 mg/kg
	Species	rabbit
	Method	not specified
Tetramethylene dimethacrylate 2082-81-7	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rabbit
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
Poly (4EO) ethylene glycol dimethacrylate 25852-47-5	Value type	Acute toxicity estimate (ATE)
	Value	> 5,000 mg/kg
	Species	
	Method	Expert judgement
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rabbit
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Value type	Acute toxicity estimate (ATE)
	Value	> 5,000 mg/kg
	Species	
	Method	Expert judgement
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
Ethene, homopolymer 9002-88-4	Value type	Acute toxicity estimate (ATE)
	Value	> 5,000 mg/kg
	Species	
	Method	Expert judgement
Polyethylene glycol monomethacrylate 25736-86-1	Value type	Acute toxicity estimate (ATE)
	Value	> 5,000 mg/kg
	Species	
	Method	Expert judgement
maleic anhydride 108-31-6	Value type	LD50
	Value	2,620 mg/kg
	Species	rabbit
	Method	not specified

Skin corrosion/irritation:

Tetramethylene dimethacrylate 2082-81-7	Result	not irritating
	Exposure time	24 h
	Species	rabbit
	Method	FDA Guideline
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Result	not irritating
	Exposure time	24 h
	Species	rabbit
	Method	Draize Test
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	not specified
maleic anhydride 108-31-6	Result	highly irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Tetramethylene dimethacrylate 2082-81-7	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	not specified
maleic anhydride 108-31-6	Result	corrosive
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Tetramethylene dimethacrylate 2082-81-7	Result	sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Poly (4EO) ethylene glycol dimethacrylate 25852-47-5	Result	not sensitising
	Test type	
	Species	
	Method	OECD Guideline 406 (Skin Sensitisation)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Result	sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	Result	not sensitising
	Test type	Patch-Test
	Species	human
	Method	human repeat insult patch test
maleic anhydride 108-31-6	Result	sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Tetramethylene dimethacrylate 2082-81-7	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Tetramethylene dimethacrylate 2082-81-7	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Tetramethylene dimethacrylate 2082-81-7	Result	positive without metabolic activation
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Tetramethylene dimethacrylate 2082-81-7	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Tetramethylene dimethacrylate 2082-81-7	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Result	negative
	Type of study / Route of administration	in vitro mammalian cell micronucleus test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	Ames Test
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	Chromosome Aberration Test
maleic anhydride 108-31-6	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
maleic anhydride 108-31-6	Result	negative
	Type of study / Route of administration	inhalation
	Metabolic activation / Exposure time	
	Species	rat
	Method	OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)

Repeated dose toxicity:

2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Result	NOAEL=1,000 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	daily
	Species	rat
	Method	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	Result	NOAEL=500 mg/kg
	Route of application	oral: feed
	Exposure time / Frequency of treatment	5-8 wdaily
	Species	rat
	Method	not specified
maleic anhydride 108-31-6	Result	NOAEL=40 mg/kg
	Route of application	oral: feed
	Exposure time / Frequency of treatment	90 ddaily
	Species	rat
	Method	not specified

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: H412 Harmful to aquatic life with long lasting effects.

Toxicity:

Tetramethylene dimethacrylate 2082-81-7	Value type	LC50
	Value	32.5 mg/l
	Acute Toxicity Study	Fish
	Exposure time	48 h
	Species	
	Method	DIN 38412-15
Tetramethylene dimethacrylate 2082-81-7	Value type	EC50
	Value	9.79 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	2.11 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Tetramethylene dimethacrylate 2082-81-7	Value type	NOEC
	Value	20 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	28 d
	Species	activated sludge, domestic
	Method	not specified
Poly (4EO) ethylene glycol dimethacrylate 25852-47-5	Value type	LC50
	Value	19.02 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oryzias latipes
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Poly (4EO) ethylene glycol dimethacrylate 25852-47-5	Value type	EC50
	Value	> 100 mg/l
	Acute Toxicity Study	Daphnia

	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Poly (4EO) ethylene glycol dimethacrylate 25852-47-5	Value type	EC50
	Value	> 100 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EC10
	Value	61 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Poly (4EO) ethylene glycol dimethacrylate 25852-47-5	Value type	EC50
	Value	130 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	
	Species	not specified
	Method	other guideline:
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	Value type	LC50
	Value	4.36 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	Value type	EC50
	Value	19.4 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	Value type	EC0
	Value	5 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Value type	LC50
	Value	16.4 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Danio rerio
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Value type	EC50
	Value	> 100 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	18.6 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	Value type	LC50
	Value	> 10,000 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Brachydanio rerio (new name: Danio rerio)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	Value type	EL50
	Value	> 10,000 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	24 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	Value type	EC50
	Value	> 173 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	Value type	EC50
	Value	> 2,500 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge of a predominantly domestic sewage
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Ethene, homopolymer 9002-88-4	Value type	LC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	
	Method	Weight of evidence
Ethene, homopolymer 9002-88-4	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	
	Method	Weight of evidence
Ethene, homopolymer 9002-88-4	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	
	Method	Weight of evidence
Polyethylene glycol monomethacrylate 25736-86-1	Value type	LC50
	Value	> 10 - 100 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	not specified
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
maleic anhydride 108-31-6	Value type	LC50
	Value	75 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Lepomis macrochirus
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
maleic anhydride 108-31-6	Value type	EC50
	Value	77 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
maleic anhydride 108-31-6	Value type	EC50
	Value	29 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EC10
	Value	23 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
maleic anhydride 108-31-6	Value type	EC10
	Value	44.6 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	
	Species	Pseudomonas putida
	Method	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)

Persistence and degradability:

Tetramethylene dimethacrylate 2082-81-7	Result	readily biodegradable
	Route of application	aerobic
	Degradability	84 %
	Method	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)
Poly (4EO) ethylene glycol dimethacrylate 25852-47-5	Result	readily biodegradable
	Route of application	aerobic
	Degradability	85 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	Result	
	Route of application	aerobic
	Degradability	> 7 - 9 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Result	readily biodegradable
	Route of application	aerobic
	Degradability	85 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Polyethylene glycol monomethacrylate 25736-86-1	Result	readily biodegradable
	Route of application	
	Degradability	> 60 %
	Method	OECD 301 A - F
maleic anhydride 108-31-6	Result	readily biodegradable
	Route of application	aerobic
	Degradability	98 %
	Method	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)

Bioaccumulative potential / Mobility in soil:

Tetramethylene dimethacrylate 2082-81-7	LogPow	3.1
	Temperature	
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Poly (4EO) ethylene glycol dimethacrylate 25852-47-5	LogPow	-2.07
	Temperature	
	Method	QSAR (Quantitative Structure Activity Relationship)
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	LogPow	2.8
	Temperature	20 °C
	Method	not specified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	LogPow	2.3
	Temperature	
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
maleic anhydride 108-31-6	LogPow	-2.61
	Temperature	19.8 °C
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

Section 13. Disposal considerations

Product

Method of disposal: Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages: Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:
Not dangerous goods

Railroad transport RID:
Not dangerous goods

Inland water transport ADN:
Not dangerous goods

Marine transport IMDG:
Not dangerous goods

Air transport IATA:
Not dangerous goods

Section 15. Regulatory information

Regulatory Information: This Safety Data Sheet has been generated based on

LAW ON CHEMICALS No. 69/2025/QH15, issued on June 14, 2025;

Decree No. 24/2026/NĐ-CP, issued on January 17, 2026, ON THE LISTS OF CHEMICALS GOVERNED BY THE LAW ON CHEMICALS;

Decree No. 25/2026/NĐ-CP, issued on January 17, 2026, DETAILED REGULATIONS AND MEASURES FOR ORGANIZING AND GUIDING THE IMPLEMENTATION OF CERTAIN ARTICLES OF THE LAW ON CHEMICALS CONCERNING THE DEVELOPMENT OF THE CHEMICAL INDUSTRY AND CHEMICAL SAFETY AND SECURITY;

Decree No. 26/2026/NĐ-CP, issued on January 17, 2026, DETAILED REGULATIONS AND GUIDELINES FOR IMPLEMENTING CERTAIN ARTICLES OF THE LAW ON CHEMICALS REGARDING THE MANAGEMENT OF CHEMICAL ACTIVITIES AND HAZARDOUS CHEMICALS IN PRODUCTS AND GOODS;

Circular No. 01/2026/TT-BCT, issued on January 17, 2026, DETAILED REGULATIONS AND GUIDELINES FOR IMPLEMENTING CERTAIN ARTICLES OF THE LAW ON CHEMICALS AND GOVERNMENT DECREE NO. 26/2026/ND-CP DETAILING AND GUIDING THE IMPLEMENTATION OF CERTAIN ARTICLES OF THE LAW ON CHEMICALS REGARDING THE MANAGEMENT OF CHEMICAL ACTIVITIES AND HAZARDOUS CHEMICALS IN PRODUCTS AND GOODS;

Circular No. 02/2026/TT-BCT, issued on January 17, 2026, REGULATIONS ON SOME IMPLEMENTATION MEASURES OF THE LAW ON CHEMICALS AND GOVERNMENT DECREE NO. 25/2026/ND-CP DETAILING AND PROVIDING MEASURES FOR ORGANIZING AND GUIDING THE IMPLEMENTATION OF SOME ARTICLES OF THE LAW ON CHEMICALS CONCERNING THE DEVELOPMENT OF THE CHEMICAL INDUSTRY AND CHEMICAL SAFETY AND SECURITY;

Decree No. 161/2024/ND-CP, issued on December 18, 2024, ON LIST OF DANGEROUS GOODS, TRANSPORT OF DANGEROUS GOODS AND PROCEDURES FOR ISSUANCE OF LICENSES OR CERTIFICATES OF COMPLETION OF TRAINING PROGRAMS FOR DRIVERS OR ESCORTS TRANSPORTING DANGEROUS GOODS BY ROAD;

Decree No. 34/2024/NĐ-CP, issued on March 31, 2024, ON LIST OF DANGEROUS GOODS, TRANSPORT OF DANGEROUS GOODS BY INLAND WATERCRAFT;

Decree No. 33/2024/NĐ-CP, issued on March 27, 2024, IMPLEMENTING THE CONVENTION ON THE PROHIBITION OF THE DEVELOPMENT, PRODUCTION, STOCKPILING AND USE OF CHEMICAL WEAPONS AND ON THEIR;

Decree No. 37/2026/NĐ-CP, issued on January 23, 2026, ELABORATING CERTAIN ARTICLES AND MEASURES FOR ORGANIZING AND GUIDING THE IMPLEMENTATION OF THE LAW ON PRODUCT AND GOODS QUALITY.

If other regulatory information applies that is not already provided or updated elsewhere in this Safety Data Sheet, then it is described in this subsection.

Global inventory status:

Regulatory list	Notification
TCSI	yes
IECSC	yes

Section 16. Other information

Disclaimer:

This Safety Data Sheet has been generated based on Law On Chemicals No. 69/2025/QH15; Decree No. 24/2026/NĐ-CP; Decree No. 25/2026/NĐ-CP; Decree No. 26/2026/NĐ-CP; Circular No. 01/2026/TT-BCT; Circular No. 02/2026/TT-BCT; Decree No. 161/2024/ND-CP; Decree No. 34/2024/NĐ-CP; Decree No. 33/2024/NĐ-CP, and Decree No. 37/2026/NĐ-CP.
No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.
This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.
Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).