Safety Data Sheet according to Singapore Standard SS 586.

LOCTITE ABLESTIK 2332-17 known as 2332-17/500G PULSE

SDS No. : 590061
V001.3
Revision: 10.01.2025
printing date: 25.03.2026

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE ABLESTIK 2332-17 known as 2332-17/500G PULSE

Other means of identification: LOCTITE ABLESTIK 2332-17
Product code: IDH1375081
Recommended use of the chemical and restrictions on use

Intended use: 1-c- epoxide adhesive
Manufacturer/Importer/Distributor Representative Company

Henkel Singapore Pte Ltd
Science Park Drive 1B
Units 09-31 to 09-35
119315 Singapore

Singapore

Phone: +65 (6266) 0100
Fax-no.: +65 (6266) 1161

E-mail address of person responsible for Safety Data Sheet: ap-ua-psra.sea@henkel.com

Emergency Telephone for Chemical Accidents: FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +65 6424 7016

Section 2. Hazards identification

GHS Classification:

Hazard Class	Hazard Category
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitizer	Category 1
Germ cell mutagenicity	Category 2
Carcinogenicity	Category 2
Toxic to reproduction	Category 1B
Acute hazards to the aquatic environment	Category 1
Chronic hazards to the aquatic environment	Category 1

GHS label elements:

Hazard pictogram:



Signal word: Danger

Hazard statement:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H341 Suspected of causing genetic defects.
H351 Suspected of causing cancer.
H360 May damage fertility or the unborn child.
H410 Very toxic to aquatic life with long lasting effects.

Precaution:

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P391 Collect spillage.

Disposal:

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	30- 60 %	Skin irritation 2 H315 Serious eye irritation 2 H319 Skin Sensitization 1 H317 Chronic hazards to the aquatic environment 2 H411
Bisphenol A reaction product with epichlorohydrin polymer with polyoxypropyleneamine 68318-44-5	10- 30 %	Skin irritation 2 H315 Serious eye irritation 2 H319 Skin Sensitization 1 H317
diuron 330-54-1	1- 10 %	Acute toxicity 4; Oral H302 Carcinogenicity 2 H351 Target Organ Systemic Toxicant - Repeated exposure 2 H373 Acute hazards to the aquatic environment 1 H400 Chronic hazards to the aquatic environment 1 H410
Trimethylolpropane triglycidyl ether 30499-70-8	1- 10 %	Skin irritation 2 H315 Serious eye damage/eye irritation 1 H318 Skin Sensitization 1 H317 Germ cell mutagenicity 2 H341 Reproductive toxicant. 1B H360 Chronic hazards to the aquatic environment 2 H411
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	1- 10 %	Skin irritation 2 H315 Skin Sensitization 1A H317 Chronic hazards to the aquatic environment 2 H411
Carbon black 1333-86-4	0.1- 1 %	

Section 4. First aid measures

Inhalation: Should not be a problem as product is of low volatility. However, if feeling unwell remove patient to fresh air.

Skin contact: Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact: Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:	Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.
Indication of immediate medical attention and special treatment needed:	See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media:	water, carbon dioxide, foam, powder
Improper extinguishing media:	High pressure waterjet
Specific hazards arising from the chemical:	In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released. In case of fire, keep containers cool with water spray.
Special protection equipment and precautions for firefighters:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Section 6. Accidental release measures

Personal precautions:	Avoid contact with skin and eyes. Wear protective equipment.
Environmental precautions:	Do not empty into drains / surface water / ground water.
Clean-up methods:	For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal. Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling:	Avoid skin and eye contact. See advice in section 8
Storage:	Ensure good ventilation/extraction.Keep container tightly sealed. Refer to Technical Data Sheet.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

DIURON 330-54-1	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	ACGIH
DIURON 330-54-1	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	SG OEL
CARBON BLACK, INHALABLE FRACTION 1333-86-4	**Value type**	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	ACGIH
CARBON BLACK 1333-86-4	**Value type**	Time Weighted Average (TWA):
	mg/m³	3.5
	Remarks	SG OEL

Respiratory protection:
Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:
Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.
Protective eye equipment should conform to EN166.

Body protection:
Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls:
Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

General protection and hygiene measures:
The workplace should be equipped with an emergency shower and eye-rinsing facility.

Hygienic measures:
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Take off contaminated clothing and wash before reuse.

Section 9. Physical and chemical properties

Appearance:	Black liquid
Odor:	Slight
Odor threshold (CA):	No data available.
pH:	Not applicable, Product is non-soluble (in water).
Melting point / freezing point:	Not applicable, Product is a liquid
Specific gravity:	1.2
Boiling point:	No data available.
Flash point:	> 100 °C (> 212 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure: (; 20 °C (68 °F))	< 1 hPa
Vapor density:	> 1
Density:	1.0952 g/cm3
Solubility:	Insoluble
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
VOC content: (2010/75/EC)	< 3 %

Section 10. Stability and reactivity

Reactivity/Incompatible materials:	Reacts with alcohols and amines. Reacts with oxidants, acids and lyes Reaction with some curing agents may produce an exothermic reaction which in large masses could cause runaway polymerization.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions:	Rapid polymerization may generate excessive heat and pressure.
Conditions to avoid:	No decomposition if stored and applied as directed.
Hazardous decomposition products:	Hydrocarbons carbon oxides. nitrogen oxides

Section 11. Toxicological information

Oral toxicity:	Acute toxicity estimate (ATE) : > 2,000 mg/kg Method: Calculation method

Symptoms of Overexposure**:** After eye contact: Corrosive, may cause permanent damage to eyes (impairment of vision).

Acute oral toxicity:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 420 (Acute Oral Toxicity)
diuron 330-54-1	Value type	LD50
	Value	1,000 - 1,017 mg/kg
	Species	rat
	Method	not specified
diuron 330-54-1	Value type	Acute toxicity estimate (ATE)
	Value	1,000 mg/kg
	Species	
	Method	Expert judgement
Trimethylolpropane triglycidyl ether 30499-70-8	Value type	LD50
	Value	3,398 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Carbon black 1333-86-4	Value type	LD50
	Value	> 8,000 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)

Acute inhalative toxicity:

diuron 330-54-1	Value type	LC50
	Value	> 5.05 mg/l
	Exposure time	4 h
	Species	rat
	Method	OECD Guideline 403 (Acute Inhalation Toxicity)
diuron 330-54-1	Value type	Acute toxicity estimate (ATE)
	Value	5.051 mg/l
	Exposure time	
	Species	
	Method	Expert judgement

Acute dermal toxicity:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
diuron 330-54-1	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
Trimethylolpropane triglycidyl ether 30499-70-8	Value type	LD50
	Value	> 3,170 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Carbon black 1333-86-4	Value type	LD50
	Value	> 15,400 mg/kg
	Species	rabbit
	Method	not specified

Skin corrosion/irritation:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	irritating
	Exposure time	
	Species	
	Method	Weight of evidence
diuron 330-54-1	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Trimethylolpropane triglycidyl ether 30499-70-8	Result	not corrosive
	Exposure time	
	Species	Human, EpiDermTM SIT (EPI-200), Reconstructed Human Epidermis (RHE)
	Method	OECD Guideline 431 (In Vitro Skin Corrosion: Reconstructed Human Epidermis (RHE) Test Method)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Result	irritating
	Exposure time	4 h
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Carbon black 1333-86-4	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	irritating
	Exposure time	
	Species	
	Method	Weight of evidence
diuron 330-54-1	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Trimethylolpropane triglycidyl ether 30499-70-8	Result	corrosive
	Exposure time	
	Species	rabbit
	Method	other guideline:
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Carbon black 1333-86-4	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
diuron 330-54-1	Result	not sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)
Trimethylolpropane triglycidyl ether 30499-70-8	Result	sensitising
	Test type	Maurer optimisation test
	Species	guinea pig
	Method	Maurer Optimisation Test
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Result	Sub-Category 1A (sensitising)
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Carbon black 1333-86-4	Result	not sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	not specified
diuron 330-54-1	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
diuron 330-54-1	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
diuron 330-54-1	Result	
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Trimethylolpropane triglycidyl ether 30499-70-8	Result	positive
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Trimethylolpropane triglycidyl ether 30499-70-8	Result	positive
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Trimethylolpropane triglycidyl ether 30499-70-8	Result	positive
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Trimethylolpropane triglycidyl ether 30499-70-8	Result	positive
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	rat
	Method	OECD Guideline 489 (In Vivo Mammalian Alkaline Comet Assay)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Result	positive
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	rat
	Method	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Carbon black 1333-86-4	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Carbon black	Result	negative

1333-86-4	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Carbon black 1333-86-4	Result	negative
	Type of study / Route of administration	sister chromatid exchange assay in mammalian cells
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells)
Carbon black 1333-86-4	Result	negative
	Type of study / Route of administration	in vitro mammalian cell micronucleus test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
Carbon black 1333-86-4	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 490 (In Vitro Mammalian Cell Gene Mutation Tests Using the Thymidine Kinase Gene)
Carbon black 1333-86-4	Result	negative
	Type of study / Route of administration	inhalation
	Metabolic activation / Exposure time	
	Species	rat
	Method	OECD Guideline 489 (In Vivo Mammalian Alkaline Comet Assay)

Repeated dose toxicity:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	NOAEL=50 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	14 wdaily
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Trimethylolpropane triglycidyl ether 30499-70-8	Result	NOAEL=270 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	90 ddaily
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Result	NOAEL=250 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	13 wdaily
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Carbon black 1333-86-4	Result	NOAEL=> 1,000 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	90 ddaily
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Carbon black 1333-86-4	Result	NOAEL=1 mg/m3
	Route of application	inhalation
	Exposure time / Frequency of treatment	13 w6 h/d, 5 d/w
	Species	rat
	Method	not specified

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: H410 Very toxic to aquatic life with long lasting effects.

Toxicity:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	LC50
	Value	1.75 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	EC50
	Value	1.7 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	EC50
	Value	> 11 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus capricornutum
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	4.2 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus capricornutum
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	IC50
	Value	> 100 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge, industrial
	Method	other guideline:
diuron 330-54-1	Value type	NOEC
	Value	4.2 mg/l
	Acute Toxicity Study	Fish
	Exposure time	7 d
	Species	Pimephales promelas
	Method	OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study)
	Value type	LC50
	Value	6.6 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Leuciscus idus melanotus
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
diuron 330-54-1	Value type	EC50
	Value	1.4 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
diuron 330-54-1	Value type	NOEC
	Value	0.0032 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EC50
	Value	0.022 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
diuron 330-54-1	Value type	EC 50
	Value	> 10,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	

	Species	
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Trimethylolpropane triglycidyl ether 30499-70-8	Value type	LC50
	Value	75 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Cyprinus carpio
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Trimethylolpropane triglycidyl ether 30499-70-8	Value type	EC50
	Value	3.7 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Trimethylolpropane triglycidyl ether 30499-70-8	Value type	EC50
	Value	9 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	2.5 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Value type	LC50
	Value	5.7 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Leuciscus idus
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Value type	EC50
	Value	2.55 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Value type	EC50
	Value	1.8 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Value type	IC50
	Value	> 100 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge, industrial
	Method	other guideline:
Carbon black 1333-86-4	Value type	LC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Brachydanio rerio (new name: Danio rerio)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Carbon black 1333-86-4	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Daphnia
	Exposure time	24 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Carbon black 1333-86-4	Value type	NOEC
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)

	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Carbon black 1333-86-4	Value type	EC0
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge, domestic
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

Persistence and degradability:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	5 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
diuron 330-54-1	Result	
	Route of application	aerobic
	Degradability	0 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Trimethylolpropane triglycidyl ether 30499-70-8	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	8 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
	Result	not inherently biodegradable
	Route of application	aerobic
	Degradability	25 %
	Method	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	0 %
	Method	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

Bioaccumulative potential / Mobility in soil:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	LogPow	3.242
	Temperature	25 °C
	Method	EU Method A.8 (Partition Coefficient)
diuron 330-54-1	LogPow	2.84
	Temperature	20 °C
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Trimethylolpropane triglycidyl ether 30499-70-8	LogPow	< 3
	Temperature	
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	LogPow	2.7 - 3.6
	Temperature	
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

Section 13. Disposal considerations

Product

Method of disposal: Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages: Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:

Class:	4.1
Packing group:	III
Classification code:	PM1
Hazard ident. number:	
UN no.:	3532
Label:	4.1
Technical name:	POLYMERIZING SUBSTANCE, LIQUID, STABILIZED, N.O.S. (Epoxy resin,Dicyandiamide)
Additional Information ADR:	Up to 500 g max per inner/primary package when shipped as originally packaged only

Railroad transport RID:

Class:	4.1
Packing group:	III
Classification code:	PM1
Hazard ident. number:	
UN no.:	3532
Label:	4.1
Technical name:	POLYMERIZING SUBSTANCE, LIQUID, STABILIZED, N.O.S. (Epoxy resin,Dicyandiamide)
Additional Information RID:	Up to 500 g max per inner/primary package when shipped as originally packaged only

Inland water transport ADN:

Class:	4.1
Packing group:	III
Classification code:	PM1
Hazard ident. number:	
UN no.:	3532
Label:	4.1
Technical name:	POLYMERIZING SUBSTANCE, LIQUID, STABILIZED, N.O.S. (Epoxy resin,Dicyandiamide)

Marine transport IMDG:

Class:	4.1
Packing group:	III
UN no.:	3532
Label:	4.1

EmS:	F-J ,S-G
Seawater pollutant:	Marine pollutant
Proper shipping name:	POLYMERIZING SUBSTANCE, LIQUID, STABILIZED, N.O.S. (Epoxy resin,Dicyandiamide)
Additional Information IMDG:	Up to 500 g max per inner/primary package when shipped as originally packaged only

Air transport IATA:

Class:	4.1
Packing group:	III
Packaging instructions (passenger):	459
Packaging instructions (cargo):	459
UN no.:	3532
Label:	4.1
Proper shipping name:	Polymerizing substance, liquid, stabilized, n.o.s. (Epoxy resin,Dicyandiamide)
Additional Information IATA:	Up to 500 g max per inner/primary package when shipped as originally packaged only

Section 15. Regulatory information

Regulatory Information: Workplace Safety And Health Act (Chapter 354A, Section 40B) Workplace Safety And Health (Approved Codes of Practice) Notification 2020.
Workplace Safety And Health Act (Chapter 354A, Section 65) Workplace Safety And Health (General Provisions) (Amendment No.2) Regulations 2024

Global inventory status:

Regulatory list	Notification
TSCA	yes
DSL	yes
ENCS (JP)	yes
ISHL (JP)	yes
IECSC	yes
AIIC	yes
TCSI	yes

Section 16. Other information

Disclaimer: This Safety Data Sheet has been generated based on Workplace Safety And Health Act (Chapter 354A, Section 40B) Workplace Safety And Health (Approved Codes of Practice) Notification 2020 and Workplace Safety And Health Act (Chapter 354A, Section 65) Workplace Safety And Health (General Provisions) (Amendment No.2) Regulations 2024 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.
Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).