Safety Data Sheet

LOCTITE ABLESTIK CE 8500-S39

SDS No. : 373861
V002.2
Revision: 27.11.2017
printing date: 25.03.2026

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE ABLESTIK CE 8500-S39

Other means of identification: LOCTITE ABLESTIK CE 8500-S39
Product code: IDH1189580
Recommended use of the chemical and restrictions on use

Intended use: Epoxy adhesive

Identification of manufacturer, importer or distributor
Importer: Henkel Singapore Pte Ltd 401 Commonwealth Drive, #03-01/02, Haw Par Technocentre, Singapore. 149598
Phone : +65 62660100 Fax : +65 62661161

E-mail address of person responsible for Safety Data Sheet: ap-ua-psra.sea@henkel.com

Emergency information: FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call CHEMTREC: +1 703-741-5970

Section 2. Hazards identification

GHS Classification:

Hazard Class	Hazard Category
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitizer	Category 1
Acute hazards to the aquatic environment	Category 1
Chronic hazards to the aquatic environment	Category 1

GHS label elements:

Hazard pictogram:



Signal word: Danger

Hazard statement:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H410 Very toxic to aquatic life with long lasting effects.

Precaution:

Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P391 Collect spillage.

Disposal:

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	60- 100 %	Acute hazards to the aquatic environment 1 H400 Chronic hazards to the aquatic environment 1 H410
Siloxanes and Silicones, di-Me, 10-carboxydecyl group-terminated, polymers with bisphenol A diglycidyl ether 217448-17-4	10- 30 %	Skin irritation 2 H315 Serious eye damage/eye irritation 2 H319 Skin Sensitization 1 H317
Dihydro-3-(tetrapropenyl)furan-2,5-dione 26544-38-7	1- 10 %	Serious eye damage/eye irritation 2 H319 Skin Sensitization 1 H317
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	1- 10 %	Acute toxicity 4; Oral H302 Acute toxicity 4; Inhalation H332 Acute toxicity 4; Dermal H312 Skin irritation 2 H315 Serious eye damage/eye irritation 1 H318 Skin Sensitization 1 H317
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	1- 10 %	Skin irritation 2 H315 Serious eye damage/eye irritation 2 H319 Skin Sensitization 1 H317 Chronic hazards to the aquatic environment 2 H411
Formaldehyde polymer with phenol 9003-35-4	0.1- 1 %	Serious eye damage/eye irritation 2 H319 Skin Sensitization 1 H317 Target Organ Systemic Toxicant - Single exposure 3 H335

Section 4. First aid measures

Inhalation: Should not be a problem as product is of low volatility. However, if feeling unwell remove patient to fresh air.

Skin contact: Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact: Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:	Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.
Indication of immediate medical attention and special treatment needed:	See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media:	water, carbon dioxide, foam, powder
Improper extinguishing media:	High pressure waterjet
Specific hazards arising from the chemical:	In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.
Special protection equipment and precautions for firefighters:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Additional fire fighting advice:	In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions:	Avoid contact with skin and eyes. Wear protective equipment.
Environmental precautions:	Do not empty into drains / surface water / ground water.
Clean-up methods:	For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Section 7. Handling and storage

Handling:	Avoid skin and eye contact. See advice in section 8
Storage:	Ensure good ventilation/extraction.Keep container tightly sealed. Keep frozen.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

SILVER, METAL, DUST AND FUME 7440-22-4	**Value type**	Time Weighted Average (TWA):
	mg/m³	0.1
	Remarks	ACGIH
SILVER, METAL 7440-22-4	**Value type**	Time Weighted Average (TWA):
	mg/m³	0.1
	Remarks	SG PEL

Respiratory protection:
Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:
Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.
Protective eye equipment should conform to EN166.

Body protection:
Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls:
Ensure good ventilation/extraction.

General protection and hygiene measures:
Eyewash fountains and emergency showers are required.

Hygienic measures:
Good industrial hygiene practices should be observed. Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working.

Section 9. Physical and chemical properties

Appearance: silver
paste
Odor: mild
Odor threshold (CA): No data available.
pH: No data available.
Melting point / freezing point: No data available.
Specific gravity: 3.12
Boiling point: No data available.

Flash point:	> 93 °C (> 199.4 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure:	Not applicable
Vapor density:	No data available.
Density:	3.12 g/cm3
Solubility:	No data available.
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	Not available.
Decomposition temperature:	
Viscosity:	No data available.
VOC content: (2010/75/EC)	< 3 %

Section 10. Stability and reactivity

Reactivity/Incompatible materials:	Reacts with alcohols and amines. Reacts with oxidants, acids and lyes Reaction with some curing agents may produce an exothermic reaction which in large masses could cause runaway polymerization.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions:	Rapid polymerization may generate excessive heat and pressure.
Conditions to avoid:	No decomposition if stored and applied as directed.
Hazardous decomposition products:	Hydrocarbons carbon oxides. nitrogen oxides

Section 11. Toxicological information

Oral toxicity:	Acute toxicity estimate (ATE) : > 2,000 mg/kg Method: Calculation method
Inhalative toxicity:	Acute toxicity estimate (ATE) : > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Dermal toxicity:	Acute toxicity estimate (ATE) : > 2,000 mg/kg Method: Calculation method

Health Effects:

Ingestion: May cause gastrointestinal tract irritation if swallowed.

Skin: Causes skin irritation.
May cause an allergic skin reaction.

Eyes: Causes serious eye damage.

Symptoms of Overexposure**:** Prolonged or repeated skin contact with silver and its salts may cause a blue-gray discoloration of the skin and mucous membranes that is irreversible (Argyria).

Acute oral toxicity:

Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
Dihydro-3-(tetrapropenyl)furan-2,5-dione 26544-38-7	Value type	LD50
	Value	2,900 mg/kg
	Species	rat
	Method	OECD Guideline 423 (Acute Oral toxicity)
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	Value type	LD50
	Value	1,118 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 420 (Acute Oral Toxicity)
Formaldehyde polymer with phenol 9003-35-4	Value type	LD50
	Value	4,100 mg/kg
	Species	rat
	Method	

Acute dermal toxicity:

Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
Dihydro-3-(tetrapropenyl)furan-2,5-dione 26544-38-7	Value type	LD50
	Value	6,200 mg/kg
	Species	rabbit
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	not specified

Skin corrosion/irritation:

Dihydro-3-(tetrapropenyl)furan-2,5-dione 26544-38-7	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	other guideline:
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Result	moderately irritating
	Exposure time	24 h
	Species	rabbit
	Method	Draize Test

Serious eye damage/irritation:

Dihydro-3-(tetrapropenyl)furan-2,5-dione 26544-38-7	Result	irritating
	Exposure time	
	Species	rabbit
	Method	Evaluated according F.H.S.A.= Federal Hazardous Substance Act.
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	Result	Category 1 (irreversible effects on the eye)
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Dihydro-3-(tetrapropenyl)furan-2,5-dione 26544-38-7	Result	sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	Result	sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Result	sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	Result	negative
	Type of study / Route of administration	in vitro mammalian cell micronucleus test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
Dihydro-3-(tetrapropenyl)furan-2,5-dione 26544-38-7	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Dihydro-3-(tetrapropenyl)furan-2,5-dione 26544-38-7	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Dihydro-3-(tetrapropenyl)furan-2,5-dione 26544-38-7	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	Result	positive
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	Result	positive
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	Result	positive
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	not specified

Repeated dose toxicity:

Dihydro-3-(tetrapropenyl)furan-2,5-dione 26544-38-7	Result	NOAEL=50 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	28 days
	Species	rat
	Method	EPA Guideline
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	Result	NOAEL=200 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	28 ddaily
	Species	rat
	Method	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Result	NOAEL=50 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	14 wdaily
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: Very toxic to aquatic life with long lasting effects.

Toxicity:

Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	Value type	LC50
	Value	0.0012 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Pimephales promelas
	Method	other guideline:
	Value type	EC10
	Value	0.00019 mg/l
	Acute Toxicity Study	Fish
	Exposure time	217 d
	Species	Salmo trutta
	Method	OECD Guideline 210 (fish early lite stage toxicity test)
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	Value type	EC50
	Value	0.00022 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	other guideline:
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	Value type	EC10
	Value	0.00016 mg/l
	Acute Toxicity Study	Algae
	Exposure time	15 d
	Species	other:
	Method	other guideline:
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	Value type	LC50
	Value	24 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Brachydanio rerio (new name: Danio rerio)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	Value type	EC50
	Value	75 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	24 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	Value type	EC 50
	Value	> 100 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	

	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Value type	LC50
	Value	1.75 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Value type	EC50
	Value	1.7 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Value type	EC50
	Value	> 11 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus capricornutum
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	4.2 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus capricornutum
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Value type	IC50
	Value	> 100 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge, industrial
	Method	other guideline:

Persistence and degradability:

Dihydro-3-(tetrapropenyl)furan-2,5-dione 26544-38-7	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	9.9 %
	Method	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	Result	
	Route of application	aerobic
	Degradability	38 %
	Method	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Result	
	Route of application	aerobic
	Degradability	5 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

Bioaccumulative potential / Mobility in soil:

Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	Bioconcentration factor (BCF)	70
	Exposure time	42 d
	Species	Cyprinus carpio
	Temperature	20 °C
	Method	other guideline:
Dihydro-3-(tetrapropenyl)furan-2,5-dione 26544-38-7	LogPow	>= 4.39
	Temperature	22 °C
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
1,4-Bis(2,3-epoxypropoxy)butane 2425-79-8	LogPow	-0.269
	Temperature	25 °C
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	LogPow	3.242
	Temperature	25 °C
	Method	EU Method A.8 (Partition Coefficient)

Section 13. Disposal considerations

Product

Method of disposal: Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages: After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Section 14. Transport information

Road transport ADR:

Class:	9
Packing group:	III
Classification code:	M7
Hazard ident. number:	90
UN no.:	3077
Label:	9
Technical name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Silver)

Railroad transport RID:

Class:	9
Packing group:	III
Classification code:	M7
Hazard ident. number:	90
UN no.:	3077
Label:	9
Technical name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Silver)

Inland water transport ADN:

Class:	9
Packing group:	III
Classification code:	M7
Hazard ident. number:	
UN no.:	3077
Label:	9
Technical name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Silver)

Marine transport IMDG:

Class:	9
Packing group:	III
UN no.:	3077
Label:	9
EmS:	F-A ,S-F
Seawater pollutant:	Marine pollutant
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Silver)

Air transport IATA:

Class:	9
Packing group:	III
Packaging instructions (passenger):	956
Packaging instructions (cargo):	956
UN no.:	3077
Label:	9
Proper shipping name:	Environmentally hazardous substance, solid, n.o.s. (Silver)

Further information for transport:
The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), 197 (IATA), 969 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

Section 15. Regulatory information

Regulatory Information: Workplace Safety And Health Act (Chapter 354A) Workplace Safety And Health (Approved Codes of Practice) Notification 2013 SS586 Specification for Hazard Communication for hazardous chemicals and dangerous good Part 1,2,3

Global inventory status:

Regulatory list	Notification
TSCA	yes
IECSC	yes

Section 16. Other information

Disclaimer: This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.