LOCTITE EA E-05CL known as Hysol E-05CL Epoxy ADH - Ultra

SDS No. : 157199
V001.7
Revision: 08.04.2026
printing date: 09.04.2026

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE EA E-05CL known as Hysol E-05CL Epoxy ADH - Ultra

Other means of identification: LOCTITE EA E-05CL
Product code: IDH701962
Recommended use of the chemical and restrictions on use

Intended use: 2-Component epoxy adhesive
Manufacturer/Importer/Distributor Representative Company

Henkel Adhesive Tech. Vietnam Co., Ltd,
No. 7, Road 9A Bien Hoa II Industrial Zone,
Bien Hoa City,
810000 Dong Nai Province

Vietnam

Phone: +84 (28) 7100 6301
Fax-no.: +84 (28) 7100 6300

E-mail address of person responsible for Safety Data Sheet: ap-ua-psra.sea@henkel.com

Emergency Telephone for Chemical Accidents: FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +84 28 71006388

Section 2. Hazards identification

GHS Classification:

Hazard Class	Hazard Category
Skin corrosion/irritation	Category 1B
Serious eye damage/eye irritation	Category 1
Skin sensitizer	Category 1
Chronic hazards to the aquatic environment	Category 3

GHS label elements:

Hazard pictogram:



Signal word: Danger

Hazard statement:	H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H412 Harmful to aquatic life with long lasting effects.
Precaution:	
Prevention:	P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash hands thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection.
Response:	P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P304+P340+P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P363 Wash contaminated clothing before reuse.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	60- 100 %	Acute toxicity 5; Oral H303 Skin Sensitization 1B H317 Acute hazards to the aquatic environment 3 H402 Chronic hazards to the aquatic environment 3 H412
Benzyldimethylamine 103-83-3	1- 10 %	Flammable liquids 3 H226 Acute toxicity 4; Ingestion H302 Acute toxicity 3; Inhalation H331 Acute toxicity 4; Dermal H312 Skin corrosion/irritation 1B H314 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 2 H411
2-Aminoethanol 141-43-5	1- 10 %	Flammable liquids 4 H227 Acute toxicity 4; Oral H302 Acute toxicity 4; Inhalation H332 Acute toxicity 4; Dermal H312 Skin corrosion/irritation 1B H314 Serious eye damage/eye irritation 1 H318 Target Organ Systemic Toxicant - Single exposure 3 H335 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 3 H412
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	0.1- 1 %	Corrosive to metals 1 H290 Acute toxicity 3; Oral H301 Skin corrosion/irritation 1B H314 Serious eye damage/eye irritation 1 H318 Acute hazards to the aquatic environment 3 H402

Section 4. First aid measures

Inhalation: Move to fresh air, consult doctor if complaint persists.

Skin contact: Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing. If necessary, see a dermatologist.

Eye contact: Wash with plenty of water immediately and continue for several minutes, holding eyelid open. Consult a doctor.

Ingestion: Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.
Immediate medical treatment necessary.

Section 5. Fire fighting measures

Suitable extinguishing media: Foam, extinguishing powder, carbon dioxide.
Water spray jet

Improper extinguishing media: High pressure waterjet

Specific hazards arising from the chemical: Danger of decomposition if exposed to heat.

Special protection equipment and precautions for firefighters: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Hazardous combustion products: Sulphur oxides
See section 10.

Section 6. Accidental release measures

Personal precautions: Avoid skin and eye contact.
Ensure adequate ventilation.
Wear protective equipment.
See advice in section 8

Environmental precautions: Do not empty into drains / surface water / ground water.

Clean-up methods: Remove mechanically.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling: See advice in section 8
Extract when the product is heated.
Ensure good ventilation/suction at the workplace.
Do not spray onto flames or red-hot objects.
Keep away from sources of ignition - no smoking.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

ETHANOLAMINE 141-43-5	**Value type**	Short Term Exposure Limit (STEL):
	ppm	6
	Remarks	ACGIH
ETHANOLAMINE 141-43-5	**Value type**	Time Weighted Average (TWA):
	mg/m³	8
	Remarks	VN OEL
ETHANOLAMINE 141-43-5	**Value type**	Time Weighted Average (TWA):
	ppm	3
	Remarks	ACGIH
ETHANOLAMINE 141-43-5	**Value type**	Short-term exposure limit (STEL):
	mg/m³	15
	Remarks	VN OEL

Respiratory protection: Suitable breathing mask when there is inadequate ventilation.
Suitable respiratory protection:
Filter type: A (EN 14387)

Hand protection: Use of Butyl or Nitrile Rubber gloves is recommended.
Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection: Goggles which can be tightly sealed.
and/or
facial protection
Protective eye equipment should conform to EN166.

Body protection: Wear protective equipment.
Suitable protective clothing
apron
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls: Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

General protection and hygiene measures: The workplace should be equipped with an emergency shower and eye-rinsing facility.

Hygienic measures: Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Take off contaminated clothing and wash before reuse.

Section 9. Physical and chemical properties

Appearance: No data available.
Odor: No data available.
Odor threshold (CA): No data available.
pH: No data available.
Melting point / freezing point: No data available.
Specific gravity: 1.12
Boiling point: > 78 °C (> 172.4 °F)
Flash point: 78 °C (172.4 °F)

(Pensky Martens closed cup)

Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure:	No data available.
Vapor density:	No data available.
Density:	1.12 g/cm3
Solubility:	Not miscible or difficult to mix (20 °C)
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
VOC content:	< 1 % < 10 g/l

Section 10. Stability and reactivity

Reactivity/Incompatible materials:
Reaction with strong oxidants.
Reaction with strong bases
Reaction with strong acids.
Reaction with some curing agents may produce an exothermic reaction which in large masses could cause runaway polymerization.

Conditions to avoid:
Stable under normal conditions of storage and use.
Danger of decomposition if exposed to heat.

Hazardous decomposition products:
Irritating vapors.
Hydrocarbons
Sulphur oxides
nitrogen oxides
At higher temperature ammonia or amine derivatives may be generated.
May produce fumes when heated to decomposition. Fumes may contain carbon monoxide and other toxic fumes.
See section 5.

Section 11. Toxicological information

Oral toxicity:
Acute toxicity estimate (ATE) : > 2,000 mg/kg
Method: Calculation method

Inhalative toxicity:
Acute toxicity estimate (ATE) : > 20 mg/l
Exposure time: 4 h
Test atmosphere: Vapor
Method: Calculation method

Dermal toxicity:
Acute toxicity estimate (ATE) : > 2,000 mg/kg
Method: Calculation method

Symptoms of Overexposure**:** None known.

Acute oral toxicity:

Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	Value type	LD50
	Value	2,600 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Benzyldimethylamine 103-83-3	Value type	LD50
	Value	353 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
2-Aminoethanol 141-43-5	Value type	LD50
	Value	1,089 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Value type	Acute toxicity estimate (ATE)
	Value	215 mg/kg
	Species	
	Method	Expert judgement

Acute inhalative toxicity:

Benzyldimethylamine 103-83-3	Value type	LC50
	Value	2.052 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified
2-Aminoethanol 141-43-5	Value type	Acute toxicity estimate (ATE)
	Value	1.5 mg/l
	Exposure time	
	Species	
	Method	Expert judgement
2-Aminoethanol 141-43-5	Value type	LC50
	Value	1 - 5 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified

Acute dermal toxicity:

Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	Value type	LD50
	Value	> 10,200 mg/kg
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Benzyldimethylamine 103-83-3	Value type	LD50
	Value	1,477 mg/kg
	Species	rabbit
	Method	not specified
2-Aminoethanol 141-43-5	Value type	LD50
	Value	1,025 mg/kg
	Species	rabbit
	Method	not specified

Skin corrosion/irritation:

Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-Aminoethanol 141-43-5	Result	corrosive
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-Aminoethanol 141-43-5	Result	corrosive
	Exposure time	4 h
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-Aminoethanol 141-43-5	Result	corrosive
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
2-Aminoethanol 141-43-5	Result	Category 1 (irreversible effects on the eye)
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	Result	Sub-Category 1B (sensitising)
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2-Aminoethanol 141-43-5	Result	not sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	not specified

Germ cell mutagenicity:

2-Aminoethanol 141-43-5	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2-Aminoethanol 141-43-5	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	without
	Method	equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2-Aminoethanol 141-43-5	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
2-Aminoethanol 141-43-5	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Repeated dose toxicity:

2-Aminoethanol 141-43-5	Result	NOAEL=300 mg/kg
	Route of application	oral: feed
	Exposure time / Frequency of treatment	> 75 ddaily
	Species	rat
	Method	other guideline:

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: H412 Harmful to aquatic life with long lasting effects.

Toxicity:

Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	Value type	LC50
	Value	87 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Danio rerio
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	Value type	EC50
	Value	12 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	Value type	EC50
	Value	> 733 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	338 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	Value type	EC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge of a predominantly domestic sewage
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Benzyldimethylamine 103-83-3	Value type	LC50
	Value	37.8 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Pimephales promelas
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Benzyldimethylamine 103-83-3	Value type	EC50
	Value	> 100 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	EU Method C.2 (Acute Toxicity for Daphnia)
Benzyldimethylamine 103-83-3	Value type	EC50
	Value	1.34 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)
	Method	EU Method C.3 (Algal Inhibition test)
	Value type	NOEC
	Value	0.24 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)
	Method	EU Method C.3 (Algal Inhibition test)
Benzyldimethylamine 103-83-3	Value type	EC10
	Value	534 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	17 h
	Species	Pseudomonas putida
	Method	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)

2-Aminoethanol 141-43-5	Value type	LC50
	Value	349 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Cyprinus carpio
	Method	EU Method C.1 (Acute Toxicity for Fish)
	Value type	NOEC
	Value	1.24 mg/l
	Acute Toxicity Study	Fish
	Exposure time	41 d
	Species	Oryzias latipes
	Method	OECD Guideline 210 (fish early life stage toxicity test)
2-Aminoethanol 141-43-5	Value type	EC50
	Value	27.04 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-Aminoethanol 141-43-5	Value type	EC50
	Value	2.8 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EC10
	Value	0.7 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Aminoethanol 141-43-5	Value type	EC10
	Value	> 1,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge, domestic
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Value type	LC50
	Value	> 100 - 220 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Leuciscus idus
	Method	DIN 38412-15
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Value type	EC50
	Value	50 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Value type	EC50
	Value	> 100 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)
	Method	EU Method C.3 (Algal Inhibition test)
	Value type	NOEC
	Value	> 100 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)
	Method	EU Method C.3 (Algal Inhibition test)
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Value type	EC50
	Value	330 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	17 h
	Species	
	Method	not specified

Persistence and degradability:

Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	5 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Benzyldimethylamine 103-83-3	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	0 - 2 %
	Method	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
2-Aminoethanol 141-43-5	Result	readily biodegradable
	Route of application	aerobic
	Degradability	> 80 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Result	not inherently biodegradable
	Route of application	aerobic
	Degradability	< 20 %
	Method	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	< 20 %
	Method	OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)

Bioaccumulative potential / Mobility in soil:

Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	LogPow	1.2
	Temperature	20 °C
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Benzyldimethylamine 103-83-3	Bioconcentration factor (BCF)	> 2.1 - 22
	Exposure time	42 d
	Species	Cyprinus carpio
	Temperature	
	Method	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)
Benzyldimethylamine 103-83-3	LogPow	1.98
	Temperature	
	Method	EU Method A.8 (Partition Coefficient)
2-Aminoethanol 141-43-5	LogPow	-1.91
	Temperature	25 °C
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Bioconcentration factor (BCF)	< 0.4
	Exposure time	42 day
	Species	Cyprinus carpio
	Temperature	
	Method	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)

Section 13. Disposal considerations

Product

Method of disposal: Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages: Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:

Class:	8
Packing group:	III
Classification code:	C7
Hazard ident. number:	80
UN no.:	2735
Label:	8
Technical name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Aliphatic amines)

Railroad transport RID:

Class:	8
Packing group:	III
Classification code:	C7
Hazard ident. number:	80
UN no.:	2735
Label:	8
Technical name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Aliphatic amines)

Inland water transport ADN:

Class:	8
Packing group:	III
Classification code:	C7
Hazard ident. number:	80
UN no.:	2735
Label:	8
Technical name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Aliphatic amines)

Marine transport IMDG:

Class:	8
Packing group:	III
UN no.:	2735
Label:	8
EmS:	F-A ,S-B
Seawater pollutant:	-
Proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Aliphatic amines)

Air transport IATA:

Class:	8
Packing group:	III
Packaging instructions (passenger):	852
Packaging instructions (cargo):	856
UN no.:	2735
Label:	8
Proper shipping name:	Amines, liquid, corrosive, n.o.s. (Aliphatic amines)

Section 15. Regulatory information

Regulatory Information: This Safety Data Sheet has been generated based on

LAW ON CHEMICALS No. 69/2025/QH15, issued on June 14, 2025;

Decree No. 24/2026/NĐ-CP, issued on January 17, 2026, ON THE LISTS OF CHEMICALS GOVERNED BY THE LAW ON CHEMICALS;

Decree No. 25/2026/NĐ-CP, issued on January 17, 2026, DETAILED REGULATIONS AND MEASURES FOR ORGANIZING AND GUIDING THE IMPLEMENTATION OF CERTAIN ARTICLES OF THE LAW ON CHEMICALS CONCERNING THE DEVELOPMENT OF THE CHEMICAL INDUSTRY AND CHEMICAL SAFETY AND SECURITY;

Decree No. 26/2026/NĐ-CP, issued on January 17, 2026, DETAILED REGULATIONS AND GUIDELINES FOR IMPLEMENTING CERTAIN ARTICLES OF THE LAW ON CHEMICALS REGARDING THE MANAGEMENT OF CHEMICAL ACTIVITIES AND HAZARDOUS CHEMICALS IN PRODUCTS AND GOODS;

Circular No. 01/2026/TT-BCT, issued on January 17, 2026, DETAILED REGULATIONS AND GUIDELINES FOR IMPLEMENTING CERTAIN ARTICLES OF THE LAW ON CHEMICALS AND GOVERNMENT DECREE NO. 26/2026/ND-CP DETAILING AND GUIDING THE IMPLEMENTATION OF CERTAIN ARTICLES OF THE LAW ON CHEMICALS REGARDING THE MANAGEMENT OF CHEMICAL ACTIVITIES AND HAZARDOUS CHEMICALS IN PRODUCTS AND GOODS;

Circular No. 02/2026/TT-BCT, issued on January 17, 2026, REGULATIONS ON SOME IMPLEMENTATION MEASURES OF THE LAW ON CHEMICALS AND GOVERNMENT DECREE NO. 25/2026/ND-CP DETAILING AND PROVIDING MEASURES FOR ORGANIZING AND GUIDING THE IMPLEMENTATION OF SOME ARTICLES OF THE LAW ON CHEMICALS CONCERNING THE DEVELOPMENT OF THE CHEMICAL INDUSTRY AND CHEMICAL SAFETY AND SECURITY;

Decree No. 161/2024/ND-CP, issued on December 18, 2024, ON LIST OF DANGEROUS GOODS, TRANSPORT OF DANGEROUS GOODS AND PROCEDURES FOR ISSUANCE OF LICENSES OR CERTIFICATES OF COMPLETION OF TRAINING PROGRAMS FOR DRIVERS OR ESCORTS TRANSPORTING DANGEROUS GOODS BY ROAD;

Decree No. 34/2024/NĐ-CP, issued on March 31, 2024, ON LIST OF DANGEROUS GOODS, TRANSPORT OF DANGEROUS GOODS BY INLAND WATERCRAFT;

Decree No. 33/2024/NĐ-CP, issued on March 27, 2024, IMPLEMENTING THE CONVENTION ON THE PROHIBITION OF THE DEVELOPMENT, PRODUCTION, STOCKPILING AND USE OF CHEMICAL WEAPONS AND ON THEIR;

Decree No. 37/2026/NĐ-CP, issued on January 23, 2026, ELABORATING CERTAIN ARTICLES AND MEASURES FOR ORGANIZING AND GUIDING THE IMPLEMENTATION OF THE LAW ON PRODUCT AND GOODS QUALITY.

If other regulatory information applies that is not already provided or updated elsewhere in this Safety Data Sheet, then it is described in this subsection.

Global inventory status:

Regulatory list	Notification
TSCA	yes
AIIC	yes
DSL	yes
KECI (KR)	yes
IECSC	yes

Section 16. Other information

Disclaimer:

This Safety Data Sheet has been generated based on Law On Chemicals No. 69/2025/QH15; Decree No. 24/2026/NĐ-CP; Decree No. 25/2026/NĐ-CP; Decree No. 26/2026/NĐ-CP; Circular No. 01/2026/TT-BCT; Circular No. 02/2026/TT-BCT; Decree No. 161/2024/ND-CP; Decree No. 34/2024/NĐ-CP; Decree No. 33/2024/NĐ-CP, and Decree No. 37/2026/NĐ-CP.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).