LOCTITE EA E-05MR B known as HYSOL E-05MR 50ML PART B

SDS No. : 283109
V001.6
Revision: 08.04.2026
printing date: 09.04.2026

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE EA E-05MR B known as HYSOL E-05MR 50ML PART B

Other means of identification: LOCTITE EA E-05MR B
Product code: IDH1086593
Recommended use of the chemical and restrictions on use

Intended use: Epoxy Hardener
Manufacturer/Importer/Distributor Representative Company

Henkel Adhesive Tech. Vietnam Co., Ltd,
No. 7, Road 9A Bien Hoa II Industrial Zone,
Bien Hoa City,
810000 Dong Nai Province

Vietnam

Phone: +84 (28) 7100 6301
Fax-no.: +84 (28) 7100 6300

E-mail address of person responsible for Safety Data Sheet: ap-ua-psra.sea@henkel.com

Emergency Telephone for Chemical Accidents: FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +84 28 71006388

Section 2. Hazards identification

GHS Classification:

Hazard Class	Hazard Category	Route of Exposure
Acute toxicity	Category 4	Oral
Skin corrosion/irritation	Category 1A	
Serious eye damage/eye irritation	Category 1	
Skin sensitizer	Category 1	
Chronic hazards to the aquatic environment	Category 2	

GHS label elements:

Hazard pictogram:



Signal word: Danger

Hazard statement:	H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects.

Precaution:

Prevention:	P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash hands thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection.
Response:	P301+P310+P330 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Rinse mouth. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P304+P340+P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P363 Wash contaminated clothing before reuse. P391 Collect spillage.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	10- 30 %	Acute toxicity 3; Oral H301 Acute toxicity 4; Inhalation H332 Acute hazards to the aquatic environment 1 H400 Chronic hazards to the aquatic environment 1 H410
Phenol, 4,4′-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, reaction products with 3,3′-[oxybis(2,1-ethanediyloxy)] 68585-28-4	1- 10 %	Acute toxicity 4; Oral H302 Skin corrosion/irritation 1B H314 Serious eye damage/eye irritation 1 H318 Skin Sensitization 1 H317
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	1- 10 %	Acute toxicity 4; Oral H302 Acute toxicity 4; Dermal H312 Skin corrosion/irritation 1A H314 Serious eye damage/eye irritation 1 H318 Skin Sensitization 1B H317 Acute hazards to the aquatic environment 2 H401
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	1- 10 %	Acute toxicity 5; Oral H303 Acute toxicity 5; Dermal H313 Skin corrosion/irritation 1B H314 Serious eye damage/eye irritation 1 H318 Skin Sensitization 1 H317
Benzyldimethylamine 103-83-3	0.1- 1 %	Flammable liquids 3 H226 Acute toxicity 4; Ingestion H302 Acute toxicity 3; Inhalation H331 Acute toxicity 4; Dermal H312 Skin corrosion/irritation 1B H314 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 2 H411

Section 4. First aid measures

Inhalation: Move to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention.

Skin contact:	Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Rinse the mouth. Drink 1-2 glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

Section 5. Fire fighting measures

Suitable extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Specific hazards arising from the chemical:	In case of fire, keep containers cool with water spray. Burning produces obnoxious and toxic fumes. Personnel in vicinity and downwind should be evacuated. Do not allow run-off from fire fighting to enter drains or water courses.
Special protection equipment and precautions for firefighters:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Ammonia. Phenolics. Hydrogen sulfide. Nitric acid. Toxic fumes. Irritating vapors.
Additional fire fighting advice:	Do not store or use near heat, spark, open flame or other sources of ignition.

Section 6. Accidental release measures

Personal precautions:	Avoid skin and eye contact. Wear protective equipment. Ensure adequate ventilation. See advice in section 8
Environmental precautions:	Do not empty into drains / surface water / ground water.
Clean-up methods:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal. Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling.
Use only with adequate ventilation.
Keep container closed.

Storage: Store in tightly closed containers. In a cool/well-ventilated area.
Isolate from incompatible substances.
Keep away from heat and direct sunlight.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

Respiratory protection: Use a NIOSH approved respirator if ventilation is inadequate.

Eye protection: Safety goggles or safety glasses with side shields.
Full face protection should be used if the potential for splashing or spraying of product exists.
Protective eye equipment should conform to EN166.

Body protection: Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls: Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

General protection and hygiene measures: The workplace should be equipped with an emergency shower and eye-rinsing facility.

Hygienic measures: Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Take off contaminated clothing and wash before reuse.

Section 9. Physical and chemical properties

Appearance:	Clear Liquid
Odor:	Mild
Odor threshold (CA):	No data available.
pH:	Not available.
Melting point / freezing point:	No data available.
Specific gravity:	1.12
Boiling point:	No data available.
Flash point: (Pensky Martens closed cup)	> 93.94 °C (> 201.09 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure:	No data available.
Vapor density:	No data available.
Density:	No data available.
Solubility:	No data available.
Partition coefficient: n-octanol/water:	No data available.

Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
VOC content:	No data available.

Section 10. Stability and reactivity

Reactivity/Incompatible materials:	Oxidizing agents. Acids. Bases. Sodium hypochlorite. Peroxides. This product slowly corrodes copper, aluminum, zinc and galvanized surfaces. None if used properly.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions:	None under normal processing.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Ammonia. Phenolics. Hydrogen sulfide. Nitric acid. Toxic fumes. Irritating vapors.

Section 11. Toxicological information

Oral toxicity:	Acute toxicity estimate (ATE) : 837.09 mg/kg Method: Calculation method
Inhalative toxicity:	Acute toxicity estimate (ATE) : > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Dermal toxicity:	Acute toxicity estimate (ATE) : > 2,000 mg/kg Method: Calculation method

Symptoms of Overexposure**:** None known.

Acute oral toxicity:

2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	Value type	LD50
	Value	> 50 - 300 mg/kg
	Species	rat
	Method	OECD Guideline 423 (Acute Oral toxicity)
Phenol, 4,4′-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, reaction products with 3,3′-[oxybis(2,1-ethanediyloxy)] 68585-28-4	Value type	Acute toxicity estimate (ATE)
	Value	500 mg/kg
	Species	
	Method	Expert judgement
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	Value type	LD50
	Value	1,669 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Value type	LD50
	Value	3,160 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
Benzyldimethylamine 103-83-3	Value type	LD50
	Value	353 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)

Acute inhalative toxicity:

2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	Value type	LC50
	Value	1.34 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified
Benzyldimethylamine 103-83-3	Value type	LC50
	Value	2.052 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified

Acute dermal toxicity:

2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	Value type	LD50
	Value	1,310 mg/kg
	Species	rat
	Method	not specified
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Value type	Acute toxicity estimate (ATE)
	Value	2,500 mg/kg
	Species	
	Method	Expert judgement
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Value type	LD50
	Value	> 2,150 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Benzyldimethylamine 103-83-3	Value type	LD50
	Value	1,477 mg/kg
	Species	rabbit
	Method	not specified

Skin corrosion/irritation:

3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Result	Sub-Category 1B (corrosive)
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Respiratory or skin sensitization:

2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	Result	not sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Result	negative
	Type of study / Route of administration	in vitro mammalian cell micronucleus test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)

Repeated dose toxicity:

3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Result	NOAEL=< 100 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	59 daysdaily
	Species	rat
	Method	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: H411 Toxic to aquatic life with long lasting effects.

Toxicity:

2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	Value type	LC50
	Value	5.7 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Danio rerio
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	Value type	EC50
	Value	0.76 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	Value type	EC50
	Value	3.11 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EC10
	Value	0.51 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Pseudokirchneriella subcapitata

	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	Value type	EC50
	Value	772.1 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge of a predominantly domestic sewage
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	Value type	LC50
	Value	> 100 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Danio rerio
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	Value type	EC50
	Value	9.22 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	Value type	EC50
	Value	21 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EC10
	Value	5.7 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Value type	LC50
	Value	> 215 - 464 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Leuciscus idus
	Method	DIN 38412-15
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Value type	EC50
	Value	218 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	EU Method C.2 (Acute Toxicity for Daphnia)
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Value type	EC50
	Value	666 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	DIN 38412-09
	Value type	NOEC
	Value	15.6 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	DIN 38412-09
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Value type	EC10
	Value	152.5 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	17 h
	Species	Pseudomonas putida
	Method	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
Benzyldimethylamine 103-83-3	Value type	LC50
	Value	37.8 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Pimephales promelas
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)

Benzyldimethylamine 103-83-3	Value type	EC50
	Value	> 100 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	EU Method C.2 (Acute Toxicity for Daphnia)
Benzyldimethylamine 103-83-3	Value type	EC50
	Value	1.34 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)
	Method	EU Method C.3 (Algal Inhibition test)
	Value type	NOEC
	Value	0.24 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)
	Method	EU Method C.3 (Algal Inhibition test)
Benzyldimethylamine 103-83-3	Value type	EC10
	Value	534 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	17 h
	Species	Pseudomonas putida
	Method	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)

Persistence and degradability:

2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	< 10 %
	Method	OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	Result	readily biodegradable
	Route of application	
	Degradability	100 %
	Method	OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Result	not inherently biodegradable
	Route of application	aerobic
	Degradability	< 20 %
	Method	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	0 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Benzyldimethylamine 103-83-3	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	0 - 2 %
	Method	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))

Bioaccumulative potential / Mobility in soil:

2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	LogPow	1.66
	Temperature	55 °C
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	LogPow	-0.56
	Temperature	25 °C
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	LogPow	-1.25
	Temperature	25 °C
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Benzyldimethylamine 103-83-3	Bioconcentration factor (BCF)	> 2.1 - 22
	Exposure time	42 d

	Species	Cyprinus carpio
	Temperature	
	Method	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)
Benzyldimethylamine 103-83-3	LogPow	1.98
	Temperature	
	Method	EU Method A.8 (Partition Coefficient)

Section 13. Disposal considerations

Product

Method of disposal: Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages: Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:

Class:	8
Packing group:	II
Classification code:	C7
Hazard ident. number:	80
UN no.:	2735
Label:	8
Technical name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Diethylene glycol di-(3-aminopropyl) ether,N,N'-Dimethyldipropyltriamine)

Railroad transport RID:

Class:	8
Packing group:	II
Classification code:	C7
Hazard ident. number:	80
UN no.:	2735
Label:	8
Technical name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Diethylene glycol di-(3-aminopropyl) ether,N,N'-Dimethyldipropyltriamine)

Inland water transport ADN:

Class:	8
Packing group:	II
Classification code:	C7
Hazard ident. number:	80
UN no.:	2735
Label:	8
Technical name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Diethylene glycol di-(3-aminopropyl) ether,N,N'-Dimethyldipropyltriamine)

Marine transport IMDG:

Class:	8
Packing group:	II
UN no.:	2735
Label:	8
EmS:	F-A ,S-B
Seawater pollutant:	Marine pollutant
Proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Diethylene glycol di-(3-aminopropyl) ether,N,N'-Dimethyldipropyltriamine,2,2'-[1,2-Ethanediylbis(oxy)]bis(ethanethiol))

Air transport IATA:

Class:	8
Packing group:	II
Packaging instructions (passenger):	851
Packaging instructions (cargo):	855
UN no.:	2735
Label:	8
Proper shipping name:	Amines, liquid, corrosive, n.o.s. (Diethylene glycol di-(3-aminopropyl) ether,N,N'-Dimethyldipropyltriamine)

Section 15. Regulatory information

Regulatory Information: This Safety Data Sheet has been generated based on

LAW ON CHEMICALS No. 69/2025/QH15, issued on June 14, 2025;

Decree No. 24/2026/NĐ-CP, issued on January 17, 2026, ON THE LISTS OF CHEMICALS GOVERNED BY THE LAW ON CHEMICALS;

Decree No. 25/2026/NĐ-CP, issued on January 17, 2026, DETAILED REGULATIONS AND MEASURES FOR ORGANIZING AND GUIDING THE IMPLEMENTATION OF CERTAIN ARTICLES OF THE LAW ON CHEMICALS CONCERNING THE DEVELOPMENT OF THE CHEMICAL INDUSTRY AND CHEMICAL SAFETY AND SECURITY;

Decree No. 26/2026/NĐ-CP, issued on January 17, 2026, DETAILED REGULATIONS AND GUIDELINES FOR IMPLEMENTING CERTAIN ARTICLES OF THE LAW ON CHEMICALS REGARDING THE MANAGEMENT OF CHEMICAL ACTIVITIES AND HAZARDOUS CHEMICALS IN PRODUCTS AND GOODS;

Circular No. 01/2026/TT-BCT, issued on January 17, 2026, DETAILED REGULATIONS AND GUIDELINES FOR IMPLEMENTING CERTAIN ARTICLES OF THE LAW ON CHEMICALS AND GOVERNMENT DECREE NO. 26/2026/ND-CP DETAILING AND GUIDING THE IMPLEMENTATION OF CERTAIN ARTICLES OF THE LAW ON CHEMICALS REGARDING THE MANAGEMENT OF CHEMICAL ACTIVITIES AND HAZARDOUS CHEMICALS IN PRODUCTS AND GOODS;

Circular No. 02/2026/TT-BCT, issued on January 17, 2026, REGULATIONS ON SOME IMPLEMENTATION MEASURES OF THE LAW ON CHEMICALS AND GOVERNMENT DECREE NO. 25/2026/ND-CP DETAILING AND PROVIDING MEASURES FOR ORGANIZING AND GUIDING THE IMPLEMENTATION OF SOME ARTICLES OF THE LAW ON CHEMICALS CONCERNING THE DEVELOPMENT OF THE CHEMICAL INDUSTRY AND CHEMICAL SAFETY AND SECURITY;

Decree No. 161/2024/ND-CP, issued on December 18, 2024, ON LIST OF DANGEROUS GOODS, TRANSPORT OF DANGEROUS GOODS AND PROCEDURES FOR ISSUANCE OF LICENSES OR CERTIFICATES OF COMPLETION OF TRAINING PROGRAMS FOR DRIVERS OR ESCORTS TRANSPORTING DANGEROUS GOODS BY ROAD;

Decree No. 34/2024/NĐ-CP, issued on March 31, 2024, ON LIST OF DANGEROUS GOODS, TRANSPORT OF DANGEROUS GOODS BY INLAND WATERCRAFT;

Decree No. 33/2024/NĐ-CP, issued on March 27, 2024, IMPLEMENTING THE CONVENTION ON THE PROHIBITION OF THE DEVELOPMENT, PRODUCTION, STOCKPILING AND USE OF CHEMICAL WEAPONS AND ON THEIR;

Decree No. 37/2026/NĐ-CP, issued on January 23, 2026, ELABORATING CERTAIN ARTICLES AND MEASURES FOR ORGANIZING AND GUIDING THE IMPLEMENTATION OF THE LAW ON PRODUCT AND GOODS QUALITY.

If other regulatory information applies that is not already provided or updated elsewhere in this Safety Data Sheet, then it is described in this subsection.

Global inventory status:

Regulatory list	Notification
TSCA	yes

Section 16. Other information

Disclaimer:

This Safety Data Sheet has been generated based on Law On Chemicals No. 69/2025/QH15; Decree No. 24/2026/NĐ-CP; Decree No. 25/2026/NĐ-CP; Decree No. 26/2026/NĐ-CP; Circular No. 01/2026/TT-BCT; Circular No. 02/2026/TT-BCT; Decree No. 161/2024/ND-CP; Decree No. 34/2024/NĐ-CP; Decree No. 33/2024/NĐ-CP, and Decree No. 37/2026/NĐ-CP.
No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.
This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.
Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).