



Safety Data Sheet according to Singapore Standard SS 586.

Page 1 of 16

LOCTITE ECCOBOND FP4802 known as FP4802 30CC
SEMCO 50g -40CD

SDS No. : 551958

V001.4

Revision: 27.02.2025

printing date: 25.03.2026

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE ECCOBOND FP4802 known as FP4802 30CC SEMCO 50g -40CD

Other means of identification: LOCTITE ECCOBOND FP4802 30CCSM

Product code: IDH1049155

Recommended use of the chemical and restrictions on use

Intended use: 1-c- epoxide adhesive

Manufacturer/Importer/Distributor Representative Company

Henkel Singapore Pte Ltd

Science Park Drive 1B

Units 09-31 to 09-35

119315 Singapore

Singapore

Phone: +65 (6266) 0100

Fax-no.: +65 (6266) 1161

E-mail address of person responsible for Safety Data Sheet: ap-ua-psra.sea@henkel.com

Emergency Telephone for Chemical Accidents: FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +65 6424 7016

Section 2. Hazards identification

GHS Classification:

<u>Hazard Class</u>	<u>Hazard Category</u>
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitizer	Category 1
Toxic to reproduction	Category 1B
Chronic hazards to the aquatic environment	Category 3

GHS label elements:

Hazard pictogram:



Signal word:

Danger

Hazard statement:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H360 May damage fertility or the unborn child.
H412 Harmful to aquatic life with long lasting effects.

Precaution:

Prevention:

P201 Obtain special instructions before use.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition / information on ingredients
--

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Silica, vitreous 60676-86-0	30- 60 %	
Formaldehyde, polymer reaction products with 1-chloro-2,3-epoxypropane and phenol 9003-36-5	10- 30 %	Skin irritation 2 H315 Serious eye irritation 2 H319 Skin Sensitization 1 H317 Chronic hazards to the aquatic environment 2 H411
Si-oxide amorphous (fumed) 7631-86-9	1- 10 %	
Quartz (SiO ₂), <1% respirable 14808-60-7	1- 10 %	
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	0.1- 1 %	Acute toxicity 4; Oral H302 Acute toxicity 4; Inhalation H332 Acute toxicity 4; Dermal H312 Skin irritation 2 H315 Serious eye damage/eye irritation 1 H318 Skin Sensitization 1 H317 Reproductive toxicant. 1B H360
3-Trimethoxysilylpropane-1-thiol 4420-74-0	0.1- 1 %	Acute toxicity 4; Oral H302 Skin Sensitization 1B H317 Chronic hazards to the aquatic environment 2 H411
Triphenylphosphine 603-35-0	0.1- 1 %	Acute toxicity 4; Oral H302 Serious eye damage/eye irritation 1 H318 Skin Sensitization 1B H317 Target Organ Systemic Toxicant - Single exposure 3 H335 Target Organ Systemic Toxicant - Repeated exposure 1 H372

Section 4. First aid measures

Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.
Skin contact:	Rinse with running water and soap. Obtain medical attention if irritation persists.
Eye contact:	Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion: Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

Indication of immediate medical attention and special treatment needed: See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media: water, carbon dioxide, foam, powder

Improper extinguishing media: High pressure waterjet

Specific hazards arising from the chemical: In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.
In case of fire, keep containers cool with water spray.

Special protection equipment and precautions for firefighters: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional fire fighting advice: In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions: Avoid contact with skin and eyes.
Wear protective equipment.
Ensure adequate ventilation.

Environmental precautions: Do not empty into drains / surface water / ground water.

Clean-up methods: For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Section 7. Handling and storage

Handling: Avoid skin and eye contact.
See advice in section 8

Storage: Ensure good ventilation/extraction. Keep container tightly sealed.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

SILICA-AMORPHOUS: SILICA, FUSED, RESPIRABLE DUST 60676-86-0	Value type	Time Weighted Average (TWA):
	mg/m³	0.1
	Remarks	SG OEL
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles 60676-86-0	Value type	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	ACGIH
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles 60676-86-0	Value type	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	ACGIH
NUISANCE PARTICULATES 7631-86-9	Value type	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	SG OEL
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles 7631-86-9	Value type	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	ACGIH
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles 7631-86-9	Value type	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	ACGIH
Si-oxide amorphous (fumed) 7631-86-9	Value type	Time Weighted Average (TWA):
	mg/m³	6
SILICA-CRYSTALLINE: QUARTZ, RESPIRABLE DUST 14808-60-7	Value type	Time Weighted Average (TWA):
	mg/m³	0.1
	Remarks	SG OEL
Silica, crystalline- α -Quartz, respirable fraction 14808-60-7	Value type	Time Weighted Average (TWA):
	mg/m³	0.025
	Remarks	ACGIH

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; $\geq$ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; $\geq$ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the

	gloves should be replaced.
Eye protection:	Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.
Body protection:	Wear suitable protective clothing. Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.
Engineering controls:	Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.
General protection and hygiene measures:	The workplace should be equipped with an emergency shower and eye-rinsing facility.
Hygienic measures:	Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working. Take off contaminated clothing and wash before reuse.

Section 9. Physical and chemical properties

Appearance:	Black paste
Odor:	characteristic
Odor threshold (CA):	No data available.
pH:	Not applicable, Product is non-soluble (in water).
Melting point / freezing point:	Not applicable, Product is a liquid
Specific gravity:	1.7
Boiling point:	No data available.
Flash point:	> 93 °C (> 199.4 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure:	Not available.
Vapor density:	Not available.
Density:	1.7 g/cm ³
Solubility:	No data available.
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
VOC content: (2010/75/EC)	< 3 %

Section 10. Stability and reactivity

Reactivity/Incompatible materials:	Reaction with strong acids. Reacts with strong oxidants.
Conditions to avoid:	Stable under recommended storage conditions.
Hazardous decomposition products:	carbon oxides.

Section 11. Toxicological information

Oral toxicity: Acute toxicity estimate (ATE) : > 2,000 mg/kg
Method: Calculation method

Inhalative toxicity: Acute toxicity estimate (ATE) : > 20 mg/l
Exposure time: 4 h
Test atmosphere: Vapor.
Method: Calculation method

Dermal toxicity: Acute toxicity estimate (ATE) : > 2,000 mg/kg
Method: Calculation method

Symptoms of Overexposure: EYE: Irritation, conjunctivitis.
SKIN: Redness, inflammation.
SKIN: Rash, Urticaria.
May cause irritation to the digestive tract.
May cause irritation to respiratory system.

Acute oral toxicity:

Silica, vitreous 60676-86-0	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	not specified
Formaldehyde, polymer reaction products with 1-chloro-2,3-epoxypropane and phenol 9003-36-5	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Si-oxide amorphous (fumed) 7631-86-9	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
Quartz (SiO ₂), <1% respirable 14808-60-7	Value type	LD50
	Value	> 5,050 mg/kg
	Species	rat
	Method	not specified
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	Value type	LD50
	Value	1,118 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
3-Trimethoxysilylpropane-1-thiol 4420-74-0	Value type	LD50
	Value	741 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Triphenylphosphine 603-35-0	Value type	LD50
	Value	700 mg/kg
	Species	rat
	Method	BASF Test

Acute inhalative toxicity:

Si-oxide amorphous (fumed) 7631-86-9	Value type	LC50
	Value	> 5.01 mg/l
	Exposure time	4 h
	Species	rat
	Method	OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class (ATC) Method)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	Value type	Acute toxicity estimate (ATE)
	Value	11.01 mg/l
	Exposure time	4 h
	Species	
	Method	Expert judgement
Triphenylphosphine 603-35-0	Value type	LC50
	Value	12.5 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified

Acute dermal toxicity:

Silica, vitreous 60676-86-0	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rabbit
	Method	not specified
Formaldehyde, polymer reaction products with 1-chloro-2,3-epoxypropane and phenol 9003-36-5	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Si-oxide amorphous (fumed) 7631-86-9	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rabbit
	Method	not specified
Quartz (SiO ₂), <1% respirable 14808-60-7	Value type	LD50
	Value	> 2,000 mg/kg
	Species	not specified
	Method	not specified
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	Value type	LD50
	Value	1,130 mg/kg
	Species	rabbit
	Method	not specified
3-Trimethoxysilylpropane-1-thiol 4420-74-0	Value type	LD50
	Value	2,172 mg/kg
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Triphenylphosphine 603-35-0	Value type	LD50
	Value	> 4,000 mg/kg
	Species	rabbit
	Method	BASF Test

Skin corrosion/irritation:

Si-oxide amorphous (fumed) 7631-86-9	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Triphenylphosphine 603-35-0	Result	not irritating
	Exposure time	20 h
	Species	rabbit
	Method	BASF Test

Serious eye damage/irritation:

Si-oxide amorphous (fumed) 7631-86-9	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	Result	Category 1 (irreversible effects on the eye)
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Triphenylphosphine 603-35-0	Result	Category I
	Exposure time	24 h
	Species	rabbit
	Method	BASF Test

Respiratory or skin sensitization:

1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	Result	sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)
3-Trimethoxysilylpropane-1-thiol 4420-74-0	Result	Sub-Category 1B (sensitising)
	Test type	Buehler test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)
Triphenylphosphine 603-35-0	Result	Sub-Category 1B (sensitising)
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	EU Method B.6 (Skin Sensitisation)

Germ cell mutagenicity:

Si-oxide amorphous (fumed) 7631-86-9	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Si-oxide amorphous (fumed) 7631-86-9	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Si-oxide amorphous (fumed) 7631-86-9	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Si-oxide amorphous (fumed) 7631-86-9	Result	negative
	Type of study / Route of administration	inhalation
	Metabolic activation / Exposure time	
	Species	rat
	Method	not specified
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	Result	positive
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	Result	positive
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	Result	positive
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Triphenylphosphine 603-35-0	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	not specified

Repeated dose toxicity:

Si-oxide amorphous (fumed) 7631-86-9	Result	NOAEL=> 4,000 - 4,500 mg/kg
	Route of application	oral: feed
	Exposure time / Frequency of treatment	13 weeksdaily
	Species	rat
	Method	equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Si-oxide amorphous (fumed) 7631-86-9	Result	NOAEL=1.3 mg/m3
	Route of application	inhalation
	Exposure time / Frequency of treatment	13 w6 h/d, 5 d/w
	Species	rat
	Method	equivalent or similar to OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	Result	NOAEL=200 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	28 ddaily
	Species	rat
	Method	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Triphenylphosphine 603-35-0	Result	NOAEL=6 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	91 days7 days/week
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Triphenylphosphine 603-35-0	Result	NOAEL=1 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	28 days2-5 d/week (totally 20 doses)
	Species	dog
	Method	not specified
Triphenylphosphine 603-35-0	Result	NOAEL=0.01 mg/l
	Route of application	inhalation: dust
	Exposure time / Frequency of treatment	35 days3-5 d/week (20 exposures)
	Species	dog
	Method	not specified

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: H412 Harmful to aquatic life with long lasting effects.

Toxicity:

Silica, vitreous 60676-86-0	Value type	LC50
	Value	5 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Brachydanio rerio (new name: Danio rerio)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Silica, vitreous 60676-86-0	Value type	EC50
	Value	7,600 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Ceriodaphnia dubia
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Silica, vitreous 60676-86-0	Value type	EC50
	Value	440 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Formaldehyde, polymer reaction products with 1-chloro-2,3-epoxypropane and phenol 9003-36-5	Value type	EC50
	Value	1.9 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	24 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Formaldehyde, polymer reaction products with 1-chloro-2,3-epoxypropane and phenol 9003-36-5	Value type	EC50
	Value	1.8 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Si-oxide amorphous (fumed) 7631-86-9	Value type	LC50
	Value	> 10,000 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Brachydanio rerio (new name: Danio rerio)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Si-oxide amorphous (fumed) 7631-86-9	Value type	EL50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	24 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Si-oxide amorphous (fumed) 7631-86-9	Value type	NOELR
	Value	10,000 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EL50
	Value	> 10,000 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Si-oxide amorphous (fumed) 7631-86-9	Value type	EC0
	Value	10,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	Pseudomonas putida
	Method	DIN 38412, part 27 (Bacterial oxygen consumption test)
Quartz (SiO ₂), <1% respirable 14808-60-7	Value type	LC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	not specified
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Quartz (SiO ₂), <1% respirable 14808-60-7	Value type	EC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Quartz (SiO ₂), <1% respirable 14808-60-7	Value type	EC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	not specified
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Quartz (SiO ₂), <1% respirable 14808-60-7	Value type	EC0
	Value	> 1,000 mg/l

	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	not specified
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	Value type	LC50
	Value	19.8 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Danio rerio
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
	Value type	EC10
	Value	1.11 mg/l
	Acute Toxicity Study	Fish
	Exposure time	35 d
	Species	Danio rerio
	Method	OECD Guideline 210 (fish early life stage toxicity test)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	Value type	EC50
	Value	75 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	24 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	Value type	EC50
	Value	> 160 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOELR
	Value	40 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	Value type	IC50
	Value	> 100 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
3-Trimethoxysilylpropane-1-thiol 4420-74-0	Value type	LC50
	Value	439 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Brachydanio rerio (new name: Danio rerio)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
3-Trimethoxysilylpropane-1-thiol 4420-74-0	Value type	EC50
	Value	6.7 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
3-Trimethoxysilylpropane-1-thiol 4420-74-0	Value type	EC50
	Value	267 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	40 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
3-Trimethoxysilylpropane-1-thiol 4420-74-0	Value type	EC 50
	Value	440 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h

Triphenylphosphine 603-35-0	Species	
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
	Value type	LC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Leuciscus idus
Triphenylphosphine 603-35-0	Method	DIN 38412-15
	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Triphenylphosphine 603-35-0	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Triphenylphosphine 603-35-0	Value type	EC10
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	Pseudomonas putida
	Method	DIN 38412, part 27 (Bacterial oxygen consumption test)

Persistence and degradability:

Formaldehyde, polymer reaction products with 1-chloro-2,3-epoxypropane and phenol 9003-36-5	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	0 %
	Method	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)
1,4-bis(2,3-epoxypropoxy)butane 2425-79-8	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	38 %
	Method	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
	Result	inherently biodegradable
	Route of application	aerobic
	Degradability	98 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
3-Trimethoxysilylpropane-1-thiol 4420-74-0	Result	
	Route of application	aerobic
	Degradability	51 %
	Method	OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)
Triphenylphosphine 603-35-0	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	< 20 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

Bioaccumulative potential / Mobility in soil:

Formaldehyde, polymer reaction products with 1-chloro-2,3-epoxypropane and phenol 9003-36-5	LogPow	> 2.7 - 3.6
	Temperature	
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

Si-oxide amorphous (fumed) 7631-86-9	LogPow	0.53
	Temperature	25 °C
	Method	QSAR (Quantitative Structure Activity Relationship)
1,4-bis(2,3 epoxypropoxy)butane 2425-79-8	LogPow	-0.269
	Temperature	25 °C
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Triphenylphosphine 603-35-0	LogPow	5.69
	Temperature	
	Method	OECD Guideline 123 (Partition Coefficient (1-Octanol / Water), Slow-Stirring Method)

Section 13. Disposal considerations

Product

Method of disposal: Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages: Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:
Not dangerous goods

Railroad transport RID:
Not dangerous goods

Inland water transport ADN:
Not dangerous goods

Marine transport IMDG:
Not dangerous goods

Air transport IATA:
Not dangerous goods

Section 15. Regulatory information

Regulatory Information: Workplace Safety And Health Act (Chapter 354A, Section 40B) Workplace Safety And Health (Approved Codes of Practice) Notification 2020.
Workplace Safety And Health Act (Chapter 354A, Section 65) Workplace Safety And Health (General Provisions) (Amendment No.2) Regulations 2024

Global inventory status:

Regulatory list	Notification
TCSI	yes
ISHL (JP)	yes
IECSC	yes

Section 16. Other information

Disclaimer:

This Safety Data Sheet has been generated based on Workplace Safety And Health Act (Chapter 354A, Section 40B) Workplace Safety And Health (Approved Codes of Practice) Notification 2020 and Workplace Safety And Health Act (Chapter 354A, Section 65) Workplace Safety And Health (General Provisions) (Amendment No.2) Regulations 2024 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance. This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).