



Safety Data Sheet according to Singapore Standard SS 586.

Page 1 of 14

LOCTITE ECI 7004LR BO1KG E&C

SDS No. : 556736

V001.2

Revision: 04.03.2025

printing date: 25.03.2026

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE ECI 7004LR BO1KG E&C

Other means of identification: LOCTITE ECI 7004LR BO1KG E&C

Product code: IDH2076923

Recommended use of the chemical and restrictions on use

Intended use: Coating

Identification of manufacturer, importer or distributor

Importer: Henkel Singapore Pte Ltd 401 Commonwealth Drive, #03-01/02, Haw Par Technocentre, Singapore. 149598

Phone : +65 62660100 Fax : +65 62661161

E-mail address of person responsible for Safety Data Sheet: ap-ua-psra.sea@henkel.com

Emergency Telephone for Chemical Accidents: FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +65 6424 7016

Section 2. Hazards identification

GHS Classification:

Substance or mixture is not classified as hazardous according to Globally Harmonized System(GHS).

GHS label elements:

Substance or mixture is not classified as hazardous according to Globally Harmonized System(GHS).

Section 3. Composition / information on ingredients

Substance or Mixture:

Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
2-Butoxyethyl acetate 112-07-2	60- 100 %	Acute toxicity 4; Oral H302 Acute toxicity 4; Dermal H312
Carbon black 1333-86-4	10- 30 %	
cellulose nitrate 9004-70-0	10- 30 %	Explosive. 1.1 H201
Propan-2-ol 67-63-0	1- 10 %	Flammable liquids 2 H225 Serious eye irritation 2 H319 Target Organ Systemic Toxicant - Single exposure 3 H336
Graphite 7782-42-5	1- 10 %	

Section 4. First aid measures

Inhalation:	Move to fresh air, consult doctor if complaint persists.
Skin contact:	Rinse with running water and soap. In case of adverse health effects seek medical advice.
Eye contact:	Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.
Ingestion:	Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.
Indication of immediate medical attention and special treatment needed:	See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media:	Carbon dioxide, foam, powder Fine water spray
Improper extinguishing media:	Water jet (solvent-containing product).
Specific hazards arising from the chemical:	Formation of toxic gases is possible during heating or in fires.
Special protection equipment and precautions for firefighters:	Wear protective equipment. Wear self-contained breathing apparatus.
Additional fire fighting advice:	Cool endangered containers with water spray jet.

Section 6. Accidental release measures

Personal precautions:	Avoid skin and eye contact. Danger of slipping on spilled product.
------------------------------	---

Environmental precautions:	Do not empty into drains / surface water / ground water.
Clean-up methods:	Take up with liquid-absorbing material (sand). Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling:	Avoid skin and eye contact. Ensure that workrooms are adequately ventilated. See advice in section 8 Keep away from sources of ignition - no smoking. Take measures to prevent the build-up of electrostatic charges.
Storage:	Ensure good ventilation/extraction. Temperatures between + 5 °C and + 30 °C. Protect from direct sunlight. Keep container tightly sealed.

Section 8. Exposure controls / personal protection**Components with specific control parameters for workplace:**

2-BUTOXYETHYL ACETATE (EGBEA) 112-07-2	Value type	Time Weighted Average (TWA):
	ppm	20
	Remarks	ACGIH
CARBON BLACK, INHALABLE FRACTION 1333-86-4	Value type	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	ACGIH
CARBON BLACK 1333-86-4	Value type	Time Weighted Average (TWA):
	mg/m³	3.5
	Remarks	SG OEL
2-PROPANOL 67-63-0	Value type	Time Weighted Average (TWA):
	ppm	200
	Remarks	ACGIH
ISOPROPYL ALCOHOL 67-63-0	Value type	Time Weighted Average (TWA):
	ppm	400
	mg/m³	983
	Remarks	SG OEL
2-PROPANOL 67-63-0	Value type	Short Term Exposure Limit (STEL):
	ppm	400
	Remarks	ACGIH
ISOPROPYL ALCOHOL 67-63-0	Value type	Short Term Exposure Limit (STEL):
	ppm	500
	mg/m³	1,230
	Remarks	SG OEL
GRAPHITE (ALL FORMS EXCEPT GRAPHITE FIBERS), RESPIRABLE FRACTION 7782-42-5	Value type	Time Weighted Average (TWA):
	mg/m³	2
	Remarks	ACGIH
Graphite, respirable dust 7782-42-5	Value type	Time Weighted Average (TWA):
	mg/m³	2
	Remarks	SG OEL

Respiratory protection:

In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).
This recommendation should be matched to local conditions.

Hand protection:

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; $\geq$ 0.7 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; $\geq$ 0.7 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Goggles which can be tightly sealed.
Protective eye equipment should conform to EN166.

Body protection:	Suitable protective clothing Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.
Engineering controls:	Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.
General protection and hygiene measures:	The workplace should be equipped with an emergency shower and eye-rinsing facility.
Hygienic measures:	Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working. Take off contaminated clothing and wash before reuse.

Section 9. Physical and chemical properties

Appearance:	Black liquid
Odor:	Solvent
Odor threshold (CA):	No data available.
pH:	Not applicable, Product is non-soluble (in water).
Melting point / freezing point:	Not applicable, Product is a liquid
Specific gravity:	No data available.
Boiling point:	192 °C (377.6 °F)
Flash point:	78 °C (172.4 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	0.9 %(V)
Upper explosive limit:	8.5 %(V)
Vapor pressure:	< 1 mbar
(; 50 °C (122 °F); 20 °C (68 °F))	< 1 hPa
Vapor density:	> 1
Density:	1.1 g/cm ³
Solubility:	Insoluble
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	15,000 - 35,000 mPa.s (Brookfield; Instrument: RVT; 20 °C (68 °F); speed of rotation: 20 min-1; Method: no method / method unknown)
VOC content:	No data available.

Section 10. Stability and reactivity

Reactivity/Incompatible materials:	Reaction with strong oxidants.
Chemical stability:	Stable under recommended storage conditions.
Conditions to avoid:	No decomposition if used according to specifications.
Hazardous decomposition products:	In case of fire toxic gases can be released.

Section 11. Toxicological information

Oral toxicity: Acute toxicity estimate (ATE) : > 2,000 mg/kg
Method: Calculation method

Dermal toxicity: Acute toxicity estimate (ATE) : > 2,000 mg/kg
Method: Calculation method

Health Effects:

Skin: Harmful in contact with skin.
Inhalation: Harmful if inhaled.
Symptoms of Overexposure: SKIN: Redness, inflammation.
RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

Acute oral toxicity:

2-Butoxyethyl acetate 112-07-2	Value type	LD50
	Value	1,880 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
Carbon black 1333-86-4	Value type	LD50
	Value	> 8,000 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
cellulose nitrate 9004-70-0	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	not specified
Propan-2-ol 67-63-0	Value type	LD50
	Value	5,840 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Graphite 7782-42-5	Value type	Acute toxicity estimate (ATE)
	Value	> 5,000 mg/kg
	Species	
	Method	Expert judgement

Acute inhalative toxicity:

Graphite 7782-42-5	Value type	LC50
	Value	> 2 mg/l
	Exposure time	4 h
	Species	rat
	Method	OECD Guideline 403 (Acute Inhalation Toxicity)

Acute dermal toxicity:

2-Butoxyethyl acetate 112-07-2	Value type	LD50
	Value	1,500 mg/kg
	Species	rabbit
	Method	not specified
Carbon black 1333-86-4	Value type	LD50
	Value	> 15,400 mg/kg
	Species	rabbit
	Method	not specified
Propan-2-ol 67-63-0	Value type	LD50
	Value	12,870 mg/kg
	Species	rabbit
	Method	OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

2-Butoxyethyl acetate 112-07-2	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	BASF Test
Carbon black 1333-86-4	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Propan-2-ol 67-63-0	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Graphite 7782-42-5	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

2-Butoxyethyl acetate 112-07-2	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	BASF Test
Carbon black 1333-86-4	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Propan-2-ol 67-63-0	Result	Category 2A (irritating to eyes)
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Graphite 7782-42-5	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Carbon black 1333-86-4	Result	not sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Propan-2-ol 67-63-0	Result	not sensitising
	Test type	Buehler test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)
Graphite 7782-42-5	Result	not sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

Carbon black 1333-86-4	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Carbon black 1333-86-4	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Carbon black 1333-86-4	Result	negative
	Type of study / Route of administration	sister chromatid exchange assay in mammalian cells
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells)
Carbon black 1333-86-4	Result	negative
	Type of study / Route of administration	in vitro mammalian cell micronucleus test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
Carbon black 1333-86-4	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 490 (In Vitro Mammalian Cell Gene Mutation Tests Using the Thymidine Kinase Gene)
Carbon black 1333-86-4	Result	negative
	Type of study / Route of administration	inhalation
	Metabolic activation / Exposure time	
	Species	rat
	Method	OECD Guideline 489 (In Vivo Mammalian Alkaline Comet Assay)
Propan-2-ol 67-63-0	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propan-2-ol 67-63-0	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Propan-2-ol 67-63-0	Result	negative
	Type of study / Route of administration	intraperitoneal
	Metabolic activation / Exposure time	
	Species	mouse
	Method	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Graphite 7782-42-5	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Graphite 7782-42-5	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Graphite 7782-42-5	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Repeated dose toxicity:

Carbon black 1333-86-4	Result	NOAEL=> 1,000 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	90 ddaily
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Carbon black 1333-86-4	Result	NOAEL=1 mg/m3
	Route of application	inhalation
	Exposure time / Frequency of treatment	13 w6 h/d, 5 d/w
	Species	rat
	Method	not specified
Propan-2-ol 67-63-0	Result	
	Route of application	inhalation: vapour
	Exposure time / Frequency of treatment	104 w6 h/d, 5 d/w
	Species	rat
	Method	OECD Guideline 451 (Carcinogenicity Studies)
Graphite 7782-42-5	Result	NOAEL=ca. 813 mg/kg
	Route of application	oral: feed
	Exposure time / Frequency of treatment	daily
	Species	rat
	Method	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Section 12. Ecological information**General ecological information:**

Do not empty into drains / surface water / ground water.

Toxicity:

2-Butoxyethyl acetate 112-07-2	Value type	LC50
	Value	80 mg/l
	Acute Toxicity Study	Fish
	Exposure time	48 h
	Species	Leuciscus idus
	Method	DIN 38412-15
2-Butoxyethyl acetate 112-07-2	Value type	EC50
	Value	37 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	DIN 38412, part 11
2-Butoxyethyl acetate 112-07-2	Value type	EC10
	Value	> 500 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	DIN 38412-09
	Value type	EC50
	Value	> 500 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	DIN 38412-09
2-Butoxyethyl acetate 112-07-2	Value type	EC10
	Value	720 mg/l
	Acute Toxicity Study	Bacteria

	Exposure time	17 h
	Species	
	Method	not specified
Carbon black 1333-86-4	Value type	LC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Brachydanio rerio (new name: Danio rerio)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Carbon black 1333-86-4	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Daphnia
	Exposure time	24 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Carbon black 1333-86-4	Value type	NOEC
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Carbon black 1333-86-4	Value type	EC0
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge, domestic
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
cellulose nitrate 9004-70-0	Value type	LC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
cellulose nitrate 9004-70-0	Value type	EC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
cellulose nitrate 9004-70-0	Value type	EC50
	Value	> 90,000 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus sp.
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
cellulose nitrate 9004-70-0	Value type	EC0
	Value	1,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	not specified
	Method	not specified
Propan-2-ol 67-63-0	Value type	LC50
	Value	> 9,640 - 10,000 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Pimephales promelas
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Propan-2-ol 67-63-0	Value type	EC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)

	Value type	NOEC
	Value	1,000 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	Value type	EC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Graphite 7782-42-5	Value type	LC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Danio rerio
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Graphite 7782-42-5	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Graphite 7782-42-5	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Graphite 7782-42-5	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge of a predominantly domestic sewage
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

Persistence and degradability:

2-Butoxyethyl acetate 112-07-2	Result	readily biodegradable
	Route of application	aerobic
	Degradability	76 %
	Method	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)
cellulose nitrate 9004-70-0	Result	readily biodegradable
	Route of application	aerobic
	Degradability	> 60 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Propan-2-ol 67-63-0	Result	readily biodegradable
	Route of application	aerobic
	Degradability	70 - 84 %
	Method	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)

Bioaccumulative potential / Mobility in soil:

2-Butoxyethyl acetate 112-07-2	LogPow	1.51
	Temperature	
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Propan-2-ol 67-63-0	LogPow	0.05
	Temperature	

	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
--	--------	--

Section 13. Disposal considerations

Product

Method of disposal: Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages: Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:
Not dangerous goods

Railroad transport RID:
Not dangerous goods

Inland water transport ADN:
Not dangerous goods

Marine transport IMDG:
Not dangerous goods

Air transport IATA:
Not dangerous goods

Section 15. Regulatory information

Regulatory Information: Workplace Safety And Health Act (Chapter 354A, Section 40B) Workplace Safety And Health (Approved Codes of Practice) Notification 2020.
Workplace Safety And Health Act (Chapter 354A, Section 65) Workplace Safety And Health (General Provisions) (Amendment No.2) Regulations 2024

Global inventory status:

Regulatory list	Notification
TSCA	yes
DSL	yes
KECI (KR)	yes
ENCS (JP)	yes
ISHL (JP)	yes
IECSC	yes
AIIC	yes
TCSI	yes
PICCS (PH)	yes
EINECS	yes

Section 16. Other information

Disclaimer:

This Safety Data Sheet has been generated based on Workplace Safety And Health Act (Chapter 354A, Section 40B) Workplace Safety And Health (Approved Codes of Practice) Notification 2020 and Workplace Safety And Health Act (Chapter 354A, Section 65) Workplace Safety And Health (General Provisions) (Amendment No.2) Regulations 2024 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance. This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).