Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE HY 4080 B

Other means of identification: LOCTITE HY 4080 GY 50G KIT PT B
Product code: IDH2319834
Recommended use of the chemical and restrictions on use

Intended use: Adhesive
Manufacturer/Importer/Distributor Representative Company

Henkel Adhesive Tech. Vietnam Co., Ltd,
No. 7, Road 9A Bien Hoa II Industrial Zone,
Bien Hoa City,
810000 Dong Nai Province

Vietnam

Phone: +84 (28) 7100 6301
Fax-no.: +84 (28) 7100 6300

E-mail address of person responsible for Safety Data Sheet: ap-ua-psra.sea@henkel.com

Emergency Telephone for Chemical Accidents: FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +84 28 71006388

Section 2. Hazards identification

GHS Classification:

Hazard Class	Hazard Category	Target organ
Skin corrosion/irritation	Category 2	
Serious eye damage/eye irritation	Category 2A	
Skin sensitizer	Category 1	
Specific target organ toxicity - single exposure	Category 3	respiratory tract irritation
Chronic hazards to the aquatic environment	Category 3	

GHS label elements:

Hazard pictogram:



Signal word: Warning

Hazard statement:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H412 Harmful to aquatic life with long lasting effects.

Precaution:

Prevention:	P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash hands thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection.
Response:	P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.
Storage:	P403+P233 Store in a well-ventilated place. Keep container tightly closed.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	10- 30 %	Serious eye damage/eye irritation 2B H320 Skin Sensitization 1 H317
2-Hydroxyethyl acrylate, polymer with α-Epichlorohydrin, phthalic anhydride, 4,4'-Bisphenol A and ε-Caprolactone 153128-88-2	10- 30 %	Skin corrosion/irritation 2 H315 Serious eye damage/eye irritation 2A H319 Skin Sensitization 1 H317
exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	1- 10 %	Acute toxicity 5; Oral H303 Skin corrosion/irritation 3 H316 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 3 H412
Copper perchlorate hexahydrate 10294-46-9	0.1- 1 %	Oxidizing solids 2 H272 Skin corrosion/irritation 2 H315 Serious eye damage/eye irritation 2A H319 Target Organ Systemic Toxicant - Single exposure 3 H335 Acute hazards to the aquatic environment 1 H400 Chronic hazards to the aquatic environment 1 H410
2-Hydroxyethyl acrylate 818-61-1	0.1- 1 %	Acute toxicity 4; Oral H302 Acute toxicity 3; Dermal H311 Skin corrosion/irritation 1B H314 Skin Sensitization 1 H317 Acute hazards to the aquatic environment 1 H400 Chronic hazards to the aquatic environment 3 H412

Section 4. First aid measures

Inhalation: Move to fresh air, consult doctor if complaint persists.

Skin contact: Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact: Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion: Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

Indication of immediate medical attention and special treatment needed: See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media: water, carbon dioxide, foam, powder

Improper extinguishing media: High pressure waterjet

Specific hazards arising from the chemical: In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.
In case of fire, keep containers cool with water spray.

Special protection equipment and precautions for firefighters: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Section 6. Accidental release measures

Personal precautions: Avoid skin and eye contact.
Wear protective equipment.
Ensure adequate ventilation.
Remove sources of ignition.
See advice in section 8

Environmental precautions: Do not empty into drains / surface water / ground water.

Clean-up methods: For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.
Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling: Avoid skin and eye contact.
See advice in section 8

Storage: Ensure good ventilation/extraction.Keep container tightly sealed.
Refer to Technical Data Sheet.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

Siloxanes and Silicones, di-Me, reaction products with silica 67762-90-7	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
Siloxanes and Silicones, di-Me, reaction products with silica 67762-90-7	**Value type**	Time Weighted Average (TWA):
	mg/m³	3
COPPER COMPOUNDS (FUME) 10294-46-9	**Value type**	Time Weighted Average (TWA):
	mg/m³	0.1
	Remarks	VN OEL
Copper, fume as Cu 10294-46-9	**Value type**	Time Weighted Average (TWA):
	mg/m³	0.2
	Remarks	ACGIH
Copper, dusts and mists, as Cu 10294-46-9	**Value type**	Time Weighted Average (TWA):
	mg/m³	1
	Remarks	ACGIH
COPPER COMPOUNDS (DUST) 10294-46-9	**Value type**	Time Weighted Average (TWA):
	mg/m³	0.5
	Remarks	VN OEL

Respiratory protection:
Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:
Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.
Protective eye equipment should conform to EN166.

Body protection:
Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls:
Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

General protection and hygiene measures:
The workplace should be equipped with an emergency shower and eye-rinsing facility.

Hygienic measures:
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Take off contaminated clothing and wash before reuse.

Section 9. Physical and chemical properties

Appearance:	White paste
Odor:	Acrylic
Odor threshold (CA):	No data available.
pH:	Not applicable, Product is non-soluble (in water).
Melting point / freezing point:	Not applicable, Product is a liquid
Specific gravity:	No data available.
Boiling point:	> 149 °C (> 300.2 °F)
Flash point:	> 100 °C (> 212 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure:	< 700 mbar
Vapor density:	> 1
Density:	1.08 g/cm3
Solubility:	Not soluble (20 °C)
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	250,000 - 450,000 mPa.s (Cone and plate; 25 °C (77 °F); Shear gradient: 2 s-1; Method: ;; LCT STM 740; cone & plate viscosity)
VOC content: (2010/75/EC)	< 3 %

Section 10. Stability and reactivity

Reactivity/Incompatible materials:	Strong oxidizing agents. Strong bases. Acids. Reducing agents.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions:	Rapid polymerization may generate excessive heat and pressure.
Conditions to avoid:	Stable under normal conditions of storage and use.
Hazardous decomposition products:	carbon oxides. Hydrocarbons nitrogen oxides Rapid polymerisation may generate excessive heat and pressure.

Section 11. Toxicological information

Dermal toxicity:	Acute toxicity estimate (ATE) : > 2,000 mg/kg Method: Calculation method

Symptoms of Overexposure**:** SKIN: Redness, inflammation.
SKIN: Rash, Urticaria.
EYE: Irritation, conjunctivitis.

Acute oral toxicity:

Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	Value type	LD50
	Value	3,160 mg/kg
	Species	rat
	Method	not specified
2-Hydroxyethyl acrylate 818-61-1	Value type	LD50
	Value	540 mg/kg
	Species	rat
	Method	not specified

Acute dermal toxicity:

Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rabbit
	Method	not specified
exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	Value type	LD50
	Value	> 3,000 mg/kg
	Species	rabbit
	Method	not specified

Skin corrosion/irritation:

Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Result	not irritating
	Exposure time	24 h
	Species	rabbit
	Method	Draize Test
exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	Result	mildly irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Result	Category 2B (mildly irritating to eyes)
	Exposure time	
	Species	rabbit
	Method	Draize Test
exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	FDA Guideline
exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	Result	slightly irritating
	Exposure time	
	Species	rabbit
	Method	Draize Test

Respiratory or skin sensitization:

Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Result	sensitising
	Test type	
	Species	human
	Method	not specified
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Result	sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	not specified
exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	Result	not sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)
2-Hydroxyethyl acrylate 818-61-1	Result	sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	not specified

Germ cell mutagenicity:

Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Result	positive
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	Chromosome Aberration Test
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	Drosophila melanogaster
	Method	not specified
exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	Result	negative
	Type of study / Route of administration	
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2-Hydroxyethyl acrylate 818-61-1	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	not specified
2-Hydroxyethyl acrylate 818-61-1	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Repeated dose toxicity:

Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Result	NOAEL=300 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	49 ddaily
	Species	rat
	Method	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Result	NOAEL=0.352 mg/l
	Route of application	inhalation
	Exposure time / Frequency of treatment	90 d6 h/d, 5 d/w
	Species	rat
	Method	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: H412 Harmful to aquatic life with long lasting effects.

Toxicity:

Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Value type	LC50
	Value	493 mg/l
	Acute Toxicity Study	Fish
	Exposure time	48 h
	Species	Leuciscus idus melanotus
	Method	DIN 38412-15
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Value type	EC50
	Value	> 143 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Value type	EC50
	Value	> 97.2 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	> 97.2 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Value type	EC10
	Value	1,140 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	16 h
	Species	
	Method	not specified
exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	Value type	LC50
	Value	1.79 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Danio rerio
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)

exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	Value type	EC50
	Value	> 2.57 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	Value type	EC50
	Value	2.66 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	0.254 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Copper perchlorate hexahydrate 10294-46-9	Value type	LC50
	Value	0.48 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Brachydanio rerio (new name: Danio rerio)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-Hydroxyethyl acrylate 818-61-1	Value type	LC50
	Value	4.8 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Pimephales promelas
	Method	other guideline:
2-Hydroxyethyl acrylate 818-61-1	Value type	EC50
	Value	9.3 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-Hydroxyethyl acrylate 818-61-1	Value type	EC50
	Value	6 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	1 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Hydroxyethyl acrylate 818-61-1	Value type	EC10
	Value	> 100 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	72 h
	Species	activated sludge, domestic
	Method	other guideline:

Persistence and degradability:

Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Result	readily biodegradable
	Route of application	aerobic
	Degradability	94.2 %
	Method	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	Result	readily biodegradable
	Route of application	aerobic
	Degradability	70 %
	Method	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)
2-Hydroxyethyl acrylate 818-61-1	Result	readily biodegradable
	Route of application	aerobic

	Degradability	> 79 - 80 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

Bioaccumulative potential / Mobility in soil:

Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	LogPow	0.97
	Temperature	20 °C
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	Bioconcentration factor (BCF)	37
	Exposure time	56 day
	Species	Danio rerio
	Temperature	24 °C
	Method	OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test)
exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	LogPow	5.09
	Temperature	
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
2-Hydroxyethyl acrylate 818-61-1	LogPow	-0.17
	Temperature	25 °C
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

Section 13. Disposal considerations

Product

Method of disposal: Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages: Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:
Not dangerous goods

Railroad transport RID:
Not dangerous goods

Inland water transport ADN:
Not dangerous goods

Marine transport IMDG:
Not dangerous goods

Air transport IATA:
Not dangerous goods

Section 15. Regulatory information

Regulatory Information: This Safety Data Sheet has been generated based on

LAW ON CHEMICALS No. 69/2025/QH15, issued on June 14, 2025;

Decree No. 24/2026/NĐ-CP, issued on January 17, 2026, ON THE LISTS OF CHEMICALS GOVERNED BY THE LAW ON CHEMICALS;

Decree No. 25/2026/NĐ-CP, issued on January 17, 2026, DETAILED REGULATIONS AND MEASURES FOR ORGANIZING AND GUIDING THE IMPLEMENTATION OF CERTAIN ARTICLES OF THE LAW ON CHEMICALS CONCERNING THE DEVELOPMENT OF THE CHEMICAL INDUSTRY AND CHEMICAL SAFETY AND SECURITY;

Decree No. 26/2026/NĐ-CP, issued on January 17, 2026, DETAILED REGULATIONS AND GUIDELINES FOR IMPLEMENTING CERTAIN ARTICLES OF THE LAW ON CHEMICALS REGARDING THE MANAGEMENT OF CHEMICAL ACTIVITIES AND HAZARDOUS CHEMICALS IN PRODUCTS AND GOODS;

Circular No. 01/2026/TT-BCT, issued on January 17, 2026, DETAILED REGULATIONS AND GUIDELINES FOR IMPLEMENTING CERTAIN ARTICLES OF THE LAW ON CHEMICALS AND GOVERNMENT DECREE NO. 26/2026/ND-CP DETAILING AND GUIDING THE IMPLEMENTATION OF CERTAIN ARTICLES OF THE LAW ON CHEMICALS REGARDING THE MANAGEMENT OF CHEMICAL ACTIVITIES AND HAZARDOUS CHEMICALS IN PRODUCTS AND GOODS;

Circular No. 02/2026/TT-BCT, issued on January 17, 2026, REGULATIONS ON SOME IMPLEMENTATION MEASURES OF THE LAW ON CHEMICALS AND GOVERNMENT DECREE NO. 25/2026/ND-CP DETAILING AND PROVIDING MEASURES FOR ORGANIZING AND GUIDING THE IMPLEMENTATION OF SOME ARTICLES OF THE LAW ON CHEMICALS CONCERNING THE DEVELOPMENT OF THE CHEMICAL INDUSTRY AND CHEMICAL SAFETY AND SECURITY;

Decree No. 161/2024/ND-CP, issued on December 18, 2024, ON LIST OF DANGEROUS GOODS, TRANSPORT OF DANGEROUS GOODS AND PROCEDURES FOR ISSUANCE OF LICENSES OR CERTIFICATES OF COMPLETION OF TRAINING PROGRAMS FOR DRIVERS OR ESCORTS TRANSPORTING DANGEROUS GOODS BY ROAD;

Decree No. 34/2024/NĐ-CP, issued on March 31, 2024, ON LIST OF DANGEROUS GOODS, TRANSPORT OF DANGEROUS GOODS BY INLAND WATERCRAFT;

Decree No. 33/2024/NĐ-CP, issued on March 27, 2024, IMPLEMENTING THE CONVENTION ON THE PROHIBITION OF THE DEVELOPMENT, PRODUCTION, STOCKPILING AND USE OF CHEMICAL WEAPONS AND ON THEIR;

Decree No. 37/2026/NĐ-CP, issued on January 23, 2026, ELABORATING CERTAIN ARTICLES AND MEASURES FOR ORGANIZING AND GUIDING THE IMPLEMENTATION OF THE LAW ON PRODUCT AND GOODS QUALITY.

If other regulatory information applies that is not already provided or updated elsewhere in this Safety Data Sheet, then it is described in this subsection.

Global inventory status:

Regulatory list	Notification
TSCA	yes
NZIOC	yes

Section 16. Other information

Disclaimer:

This Safety Data Sheet has been generated based on Law On Chemicals No. 69/2025/QH15; Decree No. 24/2026/NĐ-CP; Decree No. 25/2026/NĐ-CP; Decree No. 26/2026/NĐ-CP; Circular No. 01/2026/TT-BCT; Circular No. 02/2026/TT-BCT; Decree No. 161/2024/ND-CP; Decree No. 34/2024/NĐ-CP; Decree No. 33/2024/NĐ-CP, and Decree No. 37/2026/NĐ-CP.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).