Safety Data Sheet according to Singapore Standard SS 586.

LOCTITE LB 8009 HEAVY DUTY ANTI-SEIZE known as Heavy Duty Anti-Seize

SDS No. : 798766
V001.1
Revision: 12.01.2025
printing date: 24.03.2026

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE LB 8009 HEAVY DUTY ANTI-SEIZE known as Heavy Duty Anti-Seize

Other means of identification: LOCTITE LB 8009 BO9OZEN
Product code: IDH234347
Recommended use of the chemical and restrictions on use

Intended use: Antiseize
Manufacturer/Importer/Distributor Representative Company

Henkel Singapore Pte Ltd
Science Park Drive 1B
Units 09-31 to 09-35
119315 Singapore

Singapore

Phone: +65 (6266) 0100
Fax-no.: +65 (6266) 1161

E-mail address of person responsible for Safety Data Sheet: ap-ua-psra.sea@henkel.com

Emergency Telephone for Chemical Accidents: FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +65 6424 7016

Section 2. Hazards identification

GHS Classification:

Hazard Class	Hazard Category
Serious eye damage/eye irritation	Category 1

GHS label elements:

Hazard pictogram:



Signal word: Danger

Hazard statement: H318 Causes serious eye damage.

Precaution:

Prevention: P280 Wear eye protection/face protection.

Response: P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Calcium fluoride 7789-75-5	10- 30 %	
Paraffin oils (petroleum), catalytic dewaxed heavy 64742-70-7	10- 30 %	
Graphite 7782-42-5	10- 30 %	
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	10- 30 %	
Calcium distearate 1592-23-0	1- 10 %	
Distillates (petroleum), solvent-refined heavy paraffinic; <3% DMSO 64741-88-4	1- 10 %	
Calcium dodecylbenzene sulfonate 26264-06-2	1- 10 %	Acute toxicity 4; Oral H302 Skin irritation 2 H315 Serious eye damage/eye irritation 1 H318
Calcium carbonate 471-34-1	1- 10 %	
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	0.1- 1 %	Reproductive toxicant. 2 H361 Target Organ Systemic Toxicant - Repeated exposure 2 H373

Section 4. First aid measures

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact: Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion: Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

Section 5. Fire fighting measures

Suitable extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Improper extinguishing media: High pressure waterjet

Specific hazards arising from the chemical:	In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.
Special protection equipment and precautions for firefighters:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Additional fire fighting advice:	In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions:	Avoid contact with skin and eyes. Wear protective equipment. Ensure adequate ventilation. See advice in section 8
Environmental precautions:	Do not empty into drains / surface water / ground water.
Clean-up methods:	For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal. Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling:	Avoid skin and eye contact. Use only in well-ventilated areas. See advice in section 8
Storage:	Refer to Technical Data Sheet.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

FLUORIDES, AS F 7789-75-5	**Value type**	Time Weighted Average (TWA):
	mg/m³	2.5
	Remarks	ACGIH
FLUORIDES, AS F 7789-75-5	**Value type**	Time Weighted Average (TWA):
	mg/m³	2.5
	Remarks	SG OEL
MINERAL OIL, EXCLUDING METAL WORKING FLUIDS, PURE, HIGHLY AND SEVERELY REFINED, INHALABLE FRACTION 64742-70-7	**Value type**	Time Weighted Average (TWA):
	mg/m³	5
	Remarks	ACGIH
OIL MIST, MINERAL 64742-70-7	**Value type**	Time Weighted Average (TWA):
	mg/m³	5
	Remarks	SG OEL
OIL MIST, MINERAL 64742-70-7	**Value type**	Short Term Exposure Limit (STEL):
	mg/m³	10
	Remarks	SG OEL
GRAPHITE (ALL FORMS EXCEPT GRAPHITE FIBERS), RESPIRABLE FRACTION 7782-42-5	**Value type**	Time Weighted Average (TWA):
	mg/m³	2
	Remarks	ACGIH
Graphite, respirable dust 7782-42-5	**Value type**	Time Weighted Average (TWA):
	mg/m³	2
	Remarks	SG OEL
Mineral oil, excluding metal working fluids, pure, highly and severely refined, inhalable fraction 64742-52-5	**Value type**	Time Weighted Average (TWA):
	mg/m³	5
	Remarks	ACGIH
OIL MIST, MINERAL 64742-52-5	**Value type**	Time Weighted Average (TWA):
	mg/m³	5
	Remarks	SG OEL
OIL MIST, MINERAL 64742-52-5	**Value type**	Short Term Exposure Limit (STEL):
	mg/m³	10
	Remarks	SG OEL
STEARATES 1592-23-0	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	SG OEL
Calcium distearate 1592-23-0	**Value type**	Time Weighted Average (TWA):
	mg/m³	3
STEARATES (EXCEPT STEARATES OF TOXIC METALS), RESPIRABLE FRACTION 1592-23-0	**Value type**	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	ACGIH
STEARATES (EXCEPT STEARATES OF TOXIC METALS), INHALABLE FRACTION 1592-23-0	**Value type**	Time Weighted Average (TWA):

	mg/m³	10
	Remarks	ACGIH
Mineral oil, excluding metal working fluids, pure, highly and severely refined, inhalable fraction 64741-88-4	**Value type**	Time Weighted Average (TWA):
	mg/m³	5
	Remarks	ACGIH
OIL MIST, MINERAL 64741-88-4	**Value type**	Short Term Exposure Limit (STEL):
	mg/m³	10
	Remarks	SG OEL
Distillates (petroleum), solvent-refined heavy paraffinic; <3% DMSO 64741-88-4	**Value type**	Time weighted average.
	mg/m³	5
Distillates (petroleum), solvent-refined heavy paraffinic; <3% DMSO 64741-88-4	**Value type**	Short Term Exposure Limit (STEL).
	mg/m³	10
OIL MIST, MINERAL 64741-88-4	**Value type**	Time Weighted Average (TWA):
	mg/m³	5
	Remarks	SG OEL
NUISANCE PARTICULATES 471-34-1	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	SG OEL
Calcium carbonate 471-34-1	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles 471-34-1	**Value type**	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	ACGIH
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles 471-34-1	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	ACGIH
Calcium carbonate (Limestone, Marble) 471-34-1	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	SG OEL

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

Eye protection: Safety goggles or safety glasses with side shields.
Full face protection should be used if the potential for splashing or spraying of product exists.
Protective eye equipment should conform to EN166.

Body protection: Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls:	Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.
General protection and hygiene measures:	The workplace should be equipped with an emergency shower and eye-rinsing facility.
Hygienic measures:	Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working. Take off contaminated clothing and wash before reuse.

Section 9. Physical and chemical properties

Appearance:	Gray / Grey liquid
Odor:	mild, fatty
Odor threshold (CA):	No data available.
pH:	Product is non-soluble (in water)., Not applicable
Melting point / freezing point:	Not applicable, Product is a liquid
Specific gravity:	1.18
Boiling point:	> 100 °C (> 212 °F)
Flash point:	> 93 °C (> 199.4 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure: (; 20 °C (68 °F))	< 1 hPa
Vapor density:	> 1
Density:	1.1799 g/cm3
Solubility:	Not miscible or difficult to mix
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
VOC content:	No data available.

Section 10. Stability and reactivity

Reactivity/Incompatible materials:	Reaction with strong oxidants. Reaction with strong acids.
Chemical stability:	Stable under recommended storage conditions.
Conditions to avoid:	Stable under normal conditions of storage and use.
Hazardous decomposition products:	carbon oxides.

Section 11. Toxicological information

Oral toxicity:	Acute toxicity estimate (ATE) : > 2,000 mg/kg Method: Calculation method

Symptoms of Overexposure**:** None known.

Acute oral toxicity:

Calcium fluoride 7789-75-5	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 423 (Acute Oral toxicity)
Paraffin oils (petroleum), catalytic dewaxed heavy 64742-70-7	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	not specified
Graphite 7782-42-5	Value type	Acute toxicity estimate (ATE)
	Value	> 5,000 mg/kg
	Species	
	Method	Expert judgement
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
Calcium distearate 1592-23-0	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 423 (Acute Oral toxicity)
Distillates (petroleum), solvent-refined heavy paraffinic; <3% DMSO 64741-88-4	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
Calcium dodecylbenzene sulfonate 26264-06-2	Value type	LD50
	Value	1,300 mg/kg
	Species	rat
	Method	other guideline:
Calcium carbonate 471-34-1	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 420 (Acute Oral Toxicity)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)

Acute inhalative toxicity:

Calcium fluoride 7789-75-5	Value type	LC50
	Value	> 5.07 mg/l
	Exposure time	4 h
	Species	rat
	Method	OECD Guideline 403 (Acute Inhalation Toxicity)
Graphite 7782-42-5	Value type	LC50
	Value	> 2 mg/l
	Exposure time	4 h
	Species	rat
	Method	OECD Guideline 403 (Acute Inhalation Toxicity)
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	Value type	LC50
	Value	> 5.53 mg/l
	Exposure time	4 h
	Species	rat
	Method	OECD Guideline 403 (Acute Inhalation Toxicity)
Distillates (petroleum), solvent-refined heavy paraffinic; <3% DMSO 64741-88-4	Value type	LC50
	Value	> 5.53 mg/l
	Exposure time	4 h
	Species	rat
	Method	OECD Guideline 403 (Acute Inhalation Toxicity)
Calcium carbonate 471-34-1	Value type	LC50
	Value	> 3 mg/l
	Exposure time	4 h
	Species	rat
	Method	OECD Guideline 403 (Acute Inhalation Toxicity)

Acute dermal toxicity:

Calcium fluoride 7789-75-5	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	EPA OPP 81-2 (Acute Dermal Toxicity)
Paraffin oils (petroleum), catalytic dewaxed heavy 64742-70-7	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rabbit
	Method	not specified
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rabbit
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
Calcium distearate 1592-23-0	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
Distillates (petroleum), solvent-refined heavy paraffinic; <3% DMSO 64741-88-4	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rabbit
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
Calcium dodecylbenzene sulfonate 26264-06-2	Value type	LD50
	Value	> 4,199 mg/kg
	Species	rabbit
	Method	not specified
Calcium carbonate 471-34-1	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

Calcium fluoride 7789-75-5	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Graphite 7782-42-5	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Calcium distearate 1592-23-0	Result	not irritating
	Exposure time	24 h
	Species	rabbit
	Method	Draize Test
Calcium distearate 1592-23-0	Result	not corrosive
	Exposure time	
	Species	Human, EpiSkinTM (SM), Reconstructed Human Epidermis (RHE)
	Method	OECD Guideline 431 (In Vitro Skin Corrosion: Reconstructed Human Epidermis (RHE) Test Method)
Calcium distearate 1592-23-0	Result	not irritating
	Exposure time	
	Species	Human, EpiSkinTM (SM), Reconstructed Human Epidermis (RHE)
	Method	OECD Guideline 439 (In Vitro Skin Irritation: Reconstructed Human Epidermis (RHE) Test Method)
Distillates (petroleum), solvent-refined heavy paraffinic; <3% DMSO 64741-88-4	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Calcium dodecylbenzene sulfonate 26264-06-2	Result	irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Calcium carbonate 471-34-1	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	Result	mildly irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Calcium fluoride 7789-75-5	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Graphite 7782-42-5	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Calcium distearate 1592-23-0	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	Draize Test
Distillates (petroleum), solvent-refined heavy paraffinic; <3% DMSO 64741-88-4	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	other guideline:
Calcium dodecylbenzene sulfonate 26264-06-2	Result	Category 1 (irreversible effects on the eye)
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Calcium carbonate 471-34-1	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Calcium fluoride 7789-75-5	Result	not sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Graphite 7782-42-5	Result	not sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Calcium distearate 1592-23-0	Result	not sensitising
	Test type	Patch-Test
	Species	human
	Method	Patch Test
Calcium distearate 1592-23-0	Result	not sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Distillates (petroleum), solvent-refined heavy paraffinic; <3% DMSO 64741-88-4	Result	not sensitising
	Test type	Buehler test
	Species	guinea pig
	Method	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
Calcium carbonate 471-34-1	Result	not sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	Result	not sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Calcium fluoride 7789-75-5	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Calcium fluoride 7789-75-5	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Calcium fluoride 7789-75-5	Result	negative
	Type of study / Route of administration	
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Graphite 7782-42-5	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Graphite 7782-42-5	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Graphite 7782-42-5	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Calcium distearate 1592-23-0	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Calcium distearate 1592-23-0	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Calcium distearate 1592-23-0	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Distillates (petroleum), solvent-refined heavy paraffinic; <3% DMSO 64741-88-4	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Distillates (petroleum), solvent-refined heavy paraffinic; <3% DMSO 64741-88-4	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Distillates (petroleum), solvent-refined heavy paraffinic; <3% DMSO 64741-88-4	Result	negative
	Type of study / Route of administration	
	Metabolic activation / Exposure time	
	Species	mouse
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Calcium carbonate 471-34-1	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Calcium carbonate 471-34-1	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)

Calcium carbonate 471-34-1	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Repeated dose toxicity:

Calcium fluoride 7789-75-5	Result	
	Route of application	inhalation: aerosol
	Exposure time / Frequency of treatment	28 d6 hours/day, 5 days/week
	Species	rat
	Method	OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day)
Graphite 7782-42-5	Result	NOAEL=ca. 813 mg/kg
	Route of application	oral: feed
	Exposure time / Frequency of treatment	daily
	Species	rat
	Method	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Calcium distearate 1592-23-0	Result	NOAEL=2,000 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	28 ddaily
	Species	rat
	Method	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Distillates (petroleum), solvent-refined heavy paraffinic; <3% DMSO 64741-88-4	Result	LOAEL=125 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	13 w5 days per week
	Species	rat
	Method	equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Calcium carbonate 471-34-1	Result	NOAEL=1,000 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	48 ddaily
	Species	rat
	Method	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	Result	NOAEL=25 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	M: 28 d / F: 53 ddaily
	Species	rat
	Method	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	Result	LOAEL=18 mg/kg
	Route of application	oral: feed
	Exposure time / Frequency of treatment	17 weeks
	Species	rat
	Method	OECD Guideline 443 (Extended One-Generation Reproductive Toxicity Study)

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity:

Toxicity:

Calcium fluoride 7789-75-5	Value type	LC50
	Value	104.7 mg/l

	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	other guideline:
	Value type	NOEC
	Value	7.43 mg/l
	Acute Toxicity Study	Fish
	Exposure time	21 d
	Species	Oncorhynchus mykiss
	Method	other guideline:
Calcium fluoride 7789-75-5	Value type	EC50
	Value	199 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	other guideline:
Calcium fluoride 7789-75-5	Value type	EC10
	Value	280 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	DIN 38412-09
	Value type	EC50
	Value	850 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	DIN 38412-09
Calcium fluoride 7789-75-5	Value type	EC0
	Value	231 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	16 h
	Species	
	Method	not specified
Paraffin oils (petroleum), catalytic dewaxed heavy 64742-70-7	Value type	LL50
	Value	> 100 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Pimephales promelas
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Paraffin oils (petroleum), catalytic dewaxed heavy 64742-70-7	Value type	EL50
	Value	> 10,000 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Paraffin oils (petroleum), catalytic dewaxed heavy 64742-70-7	Value type	NOELR
	Value	100 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Graphite 7782-42-5	Value type	LC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Danio rerio
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Graphite 7782-42-5	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Graphite 7782-42-5	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)

	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Graphite 7782-42-5	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge of a predominantly domestic sewage
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	Value type	LC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	Value type	EC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	Value type	NOELR
	Value	100 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Calcium distearate 1592-23-0	Value type	LL50
	Value	> 100 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Calcium distearate 1592-23-0	Value type	EL50
	Value	> 100 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Calcium distearate 1592-23-0	Value type	EL50
	Value	> 160 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOELR
	Value	160 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Calcium distearate 1592-23-0	Value type	EC0
	Value	> 1,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	Pseudomonas putida
	Method	DIN 38412, part 27 (Bacterial oxygen consumption test)
Distillates (petroleum), solvent-refined heavy paraffinic; <3% DMSO 64741-88-4	Value type	LC50
	Value	> 5,000 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Distillates (petroleum), solvent-refined heavy paraffinic; <3%	Value type	EC50
	Value	> 1,000 mg/l

DMSO 64741-88-4	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Distillates (petroleum), solvent-refined heavy paraffinic; <3% DMSO 64741-88-4	Value type	NOEC
	Value	500 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EC50
	Value	> 500 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Calcium dodecylbenzene sulfonate 26264-06-2	Value type	LC50
	Value	4.6 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Pimephales promelas
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
	Value type	NOEC
	Value	0.9 mg/l
	Acute Toxicity Study	Fish
	Exposure time	28 d
	Species	Pimephales promelas
	Method	other guideline:
Calcium dodecylbenzene sulfonate 26264-06-2	Value type	EC50
	Value	5.88 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	other guideline:
Calcium dodecylbenzene sulfonate 26264-06-2	Value type	EC50
	Value	29 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)
	Method	other guideline:
	Value type	NOEC
	Value	0.5 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)
	Method	other guideline:
Calcium carbonate 471-34-1	Value type	LC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Calcium carbonate 471-34-1	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Calcium carbonate 471-34-1	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	14 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus

	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Calcium carbonate 471-34-1	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge of a predominantly domestic sewage
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	Value type	LC50
	Value	> 100 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Brachydanio rerio (new name: Danio rerio)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	Value type	EC50
	Value	51 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	Value type	EC50
	Value	> 100 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	10 - 100 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	Value type	IC50
	Value	> 100 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge, domestic
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

Persistence and degradability:

Paraffin oils (petroleum), catalytic dewaxed heavy 64742-70-7	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	31 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	6 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Calcium distearate 1592-23-0	Result	readily biodegradable
	Route of application	aerobic
	Degradability	91 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Distillates (petroleum), solvent-refined heavy paraffinic; <3% DMSO 64741-88-4	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	6 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Calcium dodecylbenzene sulfonate 26264-06-2	Result	readily biodegradable
	Route of application	aerobic
	Degradability	> 75 %
	Method	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	0 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

Bioaccumulative potential / Mobility in soil:

Calcium distearate 1592-23-0	LogPow	3.82
	Temperature	25 °C
	Method	QSAR (Quantitative Structure Activity Relationship)
Calcium dodecylbenzene sulfonate 26264-06-2	LogPow	4.77
	Temperature	
	Method	QSAR (Quantitative Structure Activity Relationship)
Calcium carbonate 471-34-1	LogPow	-2.12
	Temperature	
	Method	QSAR (Quantitative Structure Activity Relationship)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	Bioconcentration factor (BCF)	> 411 - 1,730
	Exposure time	42 d
	Species	Cyprinus carpio
	Temperature	24 °C
	Method	other guideline:
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	LogPow	> 5
	Temperature	25 °C
	Method	QSAR (Quantitative Structure Activity Relationship)

Section 13. Disposal considerations

Product

Method of disposal: Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages: Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:
Not dangerous goods

Railroad transport RID:
Not dangerous goods

Inland water transport ADN:
Not dangerous goods

Marine transport IMDG:
Not dangerous goods

Air transport IATA:
Not dangerous goods

Section 15. Regulatory information

Regulatory Information: Workplace Safety And Health Act (Chapter 354A, Section 40B) Workplace Safety And Health (Approved Codes of Practice) Notification 2020.
Workplace Safety And Health Act (Chapter 354A, Section 65) Workplace Safety And Health (General Provisions) (Amendment No.2) Regulations 2024

Global inventory status:

Regulatory list	Notification
TSCA	yes
DSL	yes
KECI (KR)	yes
IECSC	yes
AIIC	yes
TCSI	yes
PICCS (PH)	yes
EINECS	yes

Section 16. Other information

Disclaimer: This Safety Data Sheet has been generated based on Workplace Safety And Health Act (Chapter 354A, Section 40B) Workplace Safety And Health (Approved Codes of Practice) Notification 2020 and Workplace Safety And Health Act (Chapter 354A, Section 65) Workplace Safety And Health (General Provisions) (Amendment No.2) Regulations 2024 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.
Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).