Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No. : 586979
V004.0

LOCTITE PC 7383 Part B

Revision: 17.11.2025
printing date: 17.11.2025
Replaces version from: 18.12.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE PC 7383 Part B
UFI: 84NA-9X08-120D-EH91

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Polyurethane hardener

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA
Henkelstr. 67
40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com
For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Acute toxicity	Category 4
H332 Harmful if inhaled.	
Route of Exposure: Inhalation	
Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Respiratory sensitizer	Category 1
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Carcinogenicity	Category 2
H351 Suspected of causing cancer.	
Specific target organ toxicity - single exposure	Category 3
H335 May cause respiratory irritation.	
Target organ: respiratory tract irritation	
Specific target organ toxicity - repeated exposure	Category 2
H373 May cause damage to organs through prolonged or repeated exposure.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

Diphenylmethane diisocyanate, isomers and homologues

Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate

4-isocyanatosulphonyltoluene

p-Toluene sulfonyl chloride

Signal word:

Danger

Hazard statement:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.

Supplemental information

As from 24 August 2023 adequate training is required before industrial or professional use.
Further information: https://www.feica.eu/PUinfo

Precautionary statement: Prevention

P261 Avoid breathing vapors.
P280 Wear protective gloves/protective clothing.

Precautionary statement: Response

P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration ≥ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration ≥ the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS No. EC No REACH-Reg. No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	50- < 100 %	Carc. 2, H351 Acute Tox. 4, Inhalation, H332 STOT RE 2, H373 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317	Eye Irrit. 2; H319; C >= 5 % Skin Irrit. 2; H315; C >= 5 % Resp. Sens. 1; H334; C >= 0,1 % STOT SE 3; H335; C >= 5 % ===== inhalation:ATE = 1,5 mg/l;dust/mist	
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate 01-2119457015-45	10- < 20 %	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 4, Inhalation, H332 Resp. Sens. 1, H334 STOT SE 3, H335 Carc. 2, H351 STOT RE 2, H373	Eye Irrit. 2; H319; C >= 5 % Skin Irrit. 2; H315; C >= 5 % Resp. Sens. 1; H334; C >= 0,1 % STOT SE 3; H335; C >= 5 % ===== inhalation:ATE = 1,5 mg/l;dust/mist	
4,4'- methylenediphenyl diisocyanate 101-68-8 202-966-0 01-2119457014-47	5- < 10 %	Carc. 2, H351 Acute Tox. 4, Inhalation, H332 STOT RE 2, H373 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317	Eye Irrit. 2; H319; C >= 5 % Skin Irrit. 2; H315; C >= 5 % Resp. Sens. 1; H334; C >= 0,1 % STOT SE 3; H335; C >= 5 % ===== inhalation:ATE = 1,5 mg/l;dust/mist	
4-isocyanatosulphonyltoluene 4083-64-1 223-810-8 01-2119980050-47	1- < 5 %	Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334	Eye Irrit. 2; H319; C >= 5 % STOT SE 3; H335; C >= 5 % Skin Irrit. 2; H315; C >= 5 %	
p-Toluene sulfonyl chloride 98-59-9 202-684-8	0,01- < 0,1 %	Met. Corr. 1, H290 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317		

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.
For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:
Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact:
Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:
Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed
SKIN: Rash, Urticaria.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

4.3. Indication of any immediate medical attention and special treatment needed
See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media
Suitable extinguishing media:
Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:
High pressure waterjet

5.2. Special hazards arising from the substance or mixture
In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters
Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:
In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Avoid contact with skin and eyes.
Wear protective equipment.
Ensure adequate ventilation.
Keep away from sources of ignition.

6.2. Environmental precautions
Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up
Dispose of contaminated material as waste according to Section 13.
For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections
See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Avoid skin and eye contact.
See advice in section 8
Do not inhale vapors and fumes.

Hygiene measures:
Wash hands before work breaks and after finishing work.
Good industrial hygiene practices should be observed.
Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities
Ensure good ventilation/extraction.
Keep container tightly sealed.
Refer to Technical Data Sheet.

7.3. Specific end use(s)
Polyurethane hardener

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m³	Value type	Short term exposure limit category / Remarks	Regulatory list
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9			STEL (Short Term Exposure Limit) factor:	1 Substance listed with both Peak factor and STEL factor. The Peak factor is supplied with the AGW values.	TRGS 900
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9			Skin designation:	Can be absorbed through the skin.	TRGS 900
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9		0,05	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [Diisocyanates]			Hazard Designation:		EU_OEL
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [Diisocyanates]			Hazard Designation:		EU_OEL
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [Diisocyanates]			Short Term Exposure Limit (STEL):	Effective date: 9 April 2026	EU_OEL
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [Diisocyanates]			Hazard Designation:		EU_OEL
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [Diisocyanates]			Time Weighted Average (TWA):	Effective date: 9 April 2026	EU_OEL
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [Diisocyanates]			Time Weighted Average (TWA):	Effective date: 1 January 2029	EU_OEL
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [Diisocyanates]			Short Term Exposure Limit (STEL):	Effective date: 1 January 2029	EU_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8			Skin designation:	Can be absorbed through the skin.	TRGS 900
4,4'-Methylenediphenyl diisocyanate 101-68-8			STEL (Short Term Exposure Limit) factor:	1 Substance listed with both Peak factor and STEL factor. The Peak factor is supplied with the AGW values.	TRGS 900
4,4'-Methylenediphenyl diisocyanate 101-68-8		0,05	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900

4,4'-Methylenediphenyl diisocyanate 101-68-8			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
4,4'-Methylenediphenyl diisocyanate 101-68-8 [Diisocyanates]			Hazard Designation:		EU_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [Diisocyanates]			Hazard Designation:		EU_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [Diisocyanates]			Time Weighted Average (TWA):	Effective date: 1 January 2029	EU_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [Diisocyanates]			Time Weighted Average (TWA):	Effective date: 9 April 2026	EU_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [Diisocyanates]			Hazard Designation:		EU_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [Diisocyanates]			Short Term Exposure Limit (STEL):	Effective date: 1 January 2029	EU_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [Diisocyanates]			Short Term Exposure Limit (STEL):	Effective date: 9 April 2026	EU_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	aqua (freshwater)		0,0037 mg/l				
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	aqua (marine water)		0,00037 mg/l				
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	Freshwater - intermittent		0,037 mg/l				
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	Soil				2,33 mg/kg		
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	sediment (freshwater)				11,7 mg/kg		
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	sediment (marine water)				1,17 mg/kg		
4,4'- methylenediphenyl diisocyanate 101-68-8	aqua (freshwater)		0,0037 mg/l				
4,4'- methylenediphenyl diisocyanate 101-68-8	aqua (intermittent releases)		0,037 mg/l				
4,4'- methylenediphenyl diisocyanate 101-68-8	aqua (marine water)		0,00037 mg/l				
4,4'- methylenediphenyl diisocyanate 101-68-8	sediment (freshwater)				11,7 mg/kg		
4,4'- methylenediphenyl diisocyanate 101-68-8	sediment (freshwater)				1,17 mg/kg		
4,4'- methylenediphenyl diisocyanate 101-68-8	Soil				2,33 mg/kg		
4,4'- methylenediphenyl diisocyanate 101-68-8	Predator						no potential for bioaccumulation
p-Toluenesulphonyl isocyanate 4083-64-1	aqua (freshwater)		0,03 mg/l				
p-Toluenesulphonyl isocyanate 4083-64-1	aqua (marine water)		0,003 mg/l				
p-Toluenesulphonyl isocyanate 4083-64-1	sewage treatment plant (STP)		0,4 mg/l				
p-Toluenesulphonyl isocyanate 4083-64-1	sediment (freshwater)				0,172 mg/kg		
p-Toluenesulphonyl isocyanate 4083-64-1	sediment (marine water)				0,017 mg/kg		
p-Toluenesulphonyl isocyanate 4083-64-1	Soil				0,017 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	Workers	inhalation	Acute/short term exposure - local effects		0,1 mg/m3	
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	Workers	inhalation	Long term exposure - local effects		0,05 mg/m3	
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	General population	inhalation	Acute/short term exposure - local effects		0,05 mg/m3	
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	General population	inhalation	Long term exposure - local effects		0,025 mg/m3	
4,4'- methylenediphenyl diisocyanate 101-68-8	Workers	inhalation	Long term exposure - local effects		0,05 mg/m3	no potential for bioaccumulation
4,4'- methylenediphenyl diisocyanate 101-68-8	Workers	inhalation	Acute/short term exposure - local effects		0,1 mg/m3	no potential for bioaccumulation
4,4'- methylenediphenyl diisocyanate 101-68-8	General population	inhalation	Long term exposure - local effects		0,025 mg/m3	no potential for bioaccumulation
4,4'- methylenediphenyl diisocyanate 101-68-8	General population	inhalation	Acute/short term exposure - local effects		0,05 mg/m3	no potential for bioaccumulation
p-Toluenesulphonyl isocyanate 4083-64-1	Workers	inhalation	Long term exposure - systemic effects		3,24 mg/m3	
p-Toluenesulphonyl isocyanate 4083-64-1	Workers	dermal	Long term exposure - systemic effects		0,92 mg/kg	
p-Toluenesulphonyl isocyanate 4083-64-1	General population	inhalation	Long term exposure - systemic effects		0,8 mg/m3	
p-Toluenesulphonyl isocyanate 4083-64-1	General population	dermal	Long term exposure - systemic effects		0,46 mg/kg	
p-Toluenesulphonyl isocyanate 4083-64-1	General population	oral	Long term exposure - systemic effects		0,46 mg/kg	

Biological Exposure Indices:
None

8.2. Exposure controls:

Engineering controls:
Ensure good ventilation/extraction.

Respiratory protection:
Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:
Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.
Protective eye equipment should conform to EN166.

Skin protection:
Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:
The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.
Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form	liquid
Colour	Brown
Odor	Characteristic
Physical state	liquid
Melting point	Currently under determination
Initial boiling point	Currently under determination
Flammability	Currently under determination
Explosive limits	Currently under determination
Flash point	> 100 °C (> 212 °F); no method / method unknown
Auto-ignition temperature	Currently under determination
Decomposition temperature	Currently under determination
pH	6,8 - 7,3
(; Conc.: 100 %)	
Viscosity (kinematic)	Currently under determination
Solubility (qualitative)	Currently under determination
Partition coefficient: n-octanol/water	Currently under determination
Vapour pressure	Currently under determination
Density	1,23 g/cm3 no method / method unknown
()	
Relative vapour density:	Currently under determination
Particle characteristics	Currently under determination

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity
Water
Reacts with alcohols and amines.
Reaction with some curing agents may produce an exothermic reaction which in large masses could cause runaway polymerization.
Reacts with oxidants, acids and lyes

10.2. Chemical stability
Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions
See section reactivity

10.4. Conditions to avoid
Stable under normal conditions of storage and use.

10.5. Incompatible materials
See section reactivity.

10.6. Hazardous decomposition products
Hydrocarbons
carbon oxides.
nitrogen oxides
Hydrogen cyanide.
Isocyanate vapors
Rapid polymerisation may generate excessive heat and pressure.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	LD50	> 10.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	LD50	> 2.000 mg/kg	rat	other guideline:
4,4'- methylenediphenyl diisocyanate 101-68-8	LD50	> 2.000 mg/kg	rat	other guideline:
4-isocyanatosulphonyltoluene 4083-64-1	LD50	2.330 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
p-Toluene sulfonyl chloride 98-59-9	LD50	4.680 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	LD50	> 9.400 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	LD50	> 9.400 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
4,4'- methylenediphenyl diisocyanate 101-68-8	LD50	> 9.400 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
4-isocyanatosulphonyltoluene 4083-64-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	Acute toxicity estimate (ATE)	1,5 mg/l	dust/mist	4 h		Expert judgement
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	Acute toxicity estimate (ATE)	1,5 mg/l	dust/mist	4 h		Expert judgement
4,4'- methylenediphenyl diisocyanate 101-68-8	Acute toxicity estimate (ATE)	1,5 mg/l	dust/mist	4 h		Expert judgement

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
4,4'- methylenediphenyl diisocyanate 101-68-8	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
p-Toluene sulfonyl chloride 98-59-9	irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	irritating		human	Weight of evidence
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	irritating		human	Weight of evidence
4,4'- methylenediphenyl diisocyanate 101-68-8	irritating		human	Weight of evidence
p-Toluene sulfonyl chloride 98-59-9	Category I		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	sensitising	Skin sensitisation	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	sensitising	Skin sensitisation	guinea pig	OECD Guideline 406 (Skin Sensitisation)
4,4'- methylenediphenyl diisocyanate 101-68-8	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
4,4'- methylenediphenyl diisocyanate 101-68-8	sensitising	Respiratory sensitisation	guinea pig	not specified
p-Toluene sulfonyl chloride 98-59-9	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
4,4'- methylenediphenyl diisocyanate 101-68-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
4-isocyanatosulphonyltoluene 4083-64-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified
4-isocyanatosulphonyltoluene 4083-64-1	negative	in vitro mammalian chromosome aberration test	with and without		not specified

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	carcinogenic	inhalation: aerosol	2 y 6 h/d	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	carcinogenic	inhalation: aerosol	2 y 6 h/d	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
4,4'- methylenediphenyl diisocyanate 101-68-8	carcinogenic	inhalation: aerosol	2 y 6 h/d	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
4-isocyanatosulphonyltoluene 4083-64-1	NOAEL F1 300 mg/kg	one-generation study	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Assessment	Route of exposure	Target Organs	Remarks
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	May cause respiratory irritation.			
4,4'- methylenediphenyl diisocyanate 101-68-8	May cause respiratory irritation.			

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	NOAEL 0,0002 mg/l	inhalation: aerosol	2 y 6 h per d, 5 d per week	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
4,4'- methylenediphenyl diisocyanate 101-68-8	NOAEL 0,0002 mg/l	inhalation: aerosol	main: 2 y; satellite:1 y 6 h/d; 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	LC50	> 1.000 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	LC50	Toxicity > Water solubility	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	LL50	> 100 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
4-isocyanatosulphonyltoluene 4083-64-1	LC50	> 45 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
p-Toluene sulfonyl chloride 98-59-9	LC50	> 100 mg/l	96 h	Danio rerio	not specified

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	EC50	> 1.000 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	EC50	Toxicity > Water solubility	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	EC50	> 100 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)
4-isocyanatosulphonyltoluene 4083-64-1	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diphenylmethane	NOEC	10 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia

diisocyanate, isomers and homologues 9016-87-9					magna, Reproduction Test)
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	NOEC	Toxicity > Water solubility	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	NOEC	10 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	EC50	> 1.640 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	EC50	Toxicity > Water solubility	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	NOELR	Toxicity > Water solubility	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	EL50	> 100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	NOELR	100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
4-isocyanatosulphonyltoluene 4083-64-1	EC50	30 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
4-isocyanatosulphonyltoluene 4083-64-1	EC10	23 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	EC50	> 100 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	EC50	Toxicity > Water solubility	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	EC50	> 1.000 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
4-isocyanatosulphonyltoluene 4083-64-1	EC50	2.511 mg/l			OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	not inherently biodegradable	aerobic	0 %	28 d	OECD Guideline 302 C (Inherent Biodegradability: Modified MITI Test (II))
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	not readily biodegradable.	not specified	0 %	28 d	OECD 301 A - F
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	not inherently biodegradable	aerobic	0 %	28 day	OECD Guideline 302 C (Inherent Biodegradability: Modified MITI Test (II))
4,4'- methylenediphenyl diisocyanate 101-68-8	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
4-isocyanatosulphonyltoluene 4083-64-1	readily biodegradable	aerobic	83 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
p-Toluene sulfonyl chloride 98-59-9	readily biodegradable	aerobic	60 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	200			Cyprinus carpio	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	92 - 200	28 d		Cyprinus carpio	OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	92 - 200	28 d		Cyprinus carpio	OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test)

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Reaction mass of 4,4`-Methylenediphenyl diisoyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	4,51	22 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
4,4'- methylenediphenyl diisocyanate 101-68-8	4,51	22 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
4-isocyanatosulphonyltoluene 4083-64-1	0,6	30 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

12.5. Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or vPvB.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:
Do not empty into drains / surface water / ground water.
Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:
After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances
The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable

VOC content (2010/75/EC)	< 3 %

National regulations/information (Germany):

WGK:	WGK 1: slightly hazardous to water (Ordinance on facilities for handling substances that are hazardous to water (AwSV)) Classification according to AwSV, Annex 1 (5.2)
Storage class according to TRGS 510:	10

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H290 May be corrosive to metals.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.

Abbreviations and acronyms:

ADG(-Code): Australian Dangerous Goods (Code)
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
ASTM: American Society for Testing and Materials
ATE: acute toxicity estimate
AS: Australian Standard
AwSV: Ordinance on Installations for the Handling of Substances Hazardous to Water
CAS: Chemical Abstract Service
CLP: Regulation (EC) No 1272/2008
CMR: cancerogenic, mutagenic or reprotoxic
DIN: German Institute for Standardization
ECx: Effective concentration (x% effective level)
ECHA: European Chemicals Agency
EC-Nummer: Substance number in the EU-inventories EINECS/ELINCS
ECTLV: European community threshold limit value
ED:Substance identified as having endocrine disrupting properties
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
EN : European Standard
ENCS: Japanese chemical inventory
EPA: US Environmental Protection Agency
EU: European Union
EU EXPLD1: Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD2: Substance listed in Annex II, Reg (EC) No. 2019/1148
EWC: European Waste Catalogue
GHS: Globally Harmonised System for Classification and Labelling of Chemicals
GLP: Good Laboratory Practice
HSNO: Hazardous Substances and New Organisms
IARC: International Agency for Research of Cancer
IATA: International Air Transport Association
IBC-Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50: half maximal inhibitory concentration
ICAO: International Civil Aviation Organization
IMDG-Code: International Maritime Code for Dangerous Goods
IMO: International Maritime Organization
ISO: International Standardization Organisation
LC50: Median lethal concentration
LD50: Median lethal dose
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
n.o.s.: not otherwise specified
NO(A)EC: No (adverse) effect concentration
NO(A)EL: No (adverse) effect level
NZS: New Zealand Standard
OECD: Organisation for Economic Co-operation and Development
OEL: Occupational Exposure Limit
OPPT: US EPA Office of Pollution Prevention and Toxics
OPPTS: US EPA Office of Prevention, Pesticides and Toxic Substances
PBT: Persistent, bioaccumulative, toxic

(Q)SAR: (Quantitative) structure–activity relationship
REACH: Regulation (EC) No. 1907/2006
RID: Regulations concerning the International Transport of Dangerous Goods by Rail
SADT: Self Accelerating Decomposition Temperature
SDS: Safety Data Sheet
STOT: Specific Target Organ Toxicity
STOT SE: Specific Target Organ Toxicity - single exposure
STOT RE: Specific Target Organ Toxicity - repeated exposure
SUSMP: Standard for the Uniform Scheduling of Medicines and Poisons
SVHC: Substance of very high concern (REACH Candidate List)
TRGS: German Technical Rules for hazardous substances
UN: United Nations
VOC: Volatile Organic Compound
814.018 VOC Reg CH: Swiss Ordinance 814.018 on the Incentive Tax on Volatile Organic Compounds
vPvB: Very persistent, very bioaccumulative
VwVwS: Administrative Regulation on Substances Hazardous to Waters
WGK: Water hazard class

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel´s Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.