Safety Data Sheet according to Singapore Standard SS 586.

LOCTITE PC 9626 GROUT known as FIXMASTER DEEP POUR KIT AGGREGA

SDS No. : 171603
V001.2
Revision: 09.10.2025
printing date: 25.03.2026

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE PC 9626 GROUT known as FIXMASTER DEEP POUR KIT AGGREGA

Other means of identification: LOCTITE PC 9626 GROUT KT5GAEN
Product code: IDH718504
Recommended use of the chemical and restrictions on use

Intended use: Filler
Manufacturer/Importer/Distributor Representative Company

Henkel Singapore Pte Ltd
Science Park Drive 1B
Units 09-31 to 09-35
119315 Singapore

Singapore

Phone: +65 (6266) 0100
Fax-no.: +65 (6266) 1161

E-mail address of person responsible for Safety Data Sheet: ap-ua-psra.sea@henkel.com

Emergency Telephone for Chemical Accidents: FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +65 6424 7016

Section 2. Hazards identification

GHS Classification:

Substance or mixture is not classified as hazardous according to Globally Harmonized System(GHS).

GHS label elements:

Substance or mixture is not classified as hazardous according to Globally Harmonized System(GHS).

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Limestone 1317-65-3	60- 100 %	

Section 4. First aid measures

Inhalation:
Move to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention.

Skin contact:
Immediately flush skin with plenty of water (using soap, if available).
Remove contaminated clothing and footwear.
Wash clothing before reuse.
Get medical attention.

Eye contact:
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Get medical attention.

Ingestion:
DO NOT induce vomiting unless directed to do so by medical personnel.
Never give anything by mouth to an unconscious person.
Get medical attention.

Section 5. Fire fighting measures

Suitable extinguishing media:
Water spray (fog), foam, dry chemical or carbon dioxide.

Special protection equipment and precautions for firefighters:
Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions:
Avoid skin and eye contact.
Wear protective equipment.
Ensure adequate ventilation.
See advice in section 8

Environmental precautions:
Do not empty into drains / surface water / ground water.

Clean-up methods:
Remove all sources of ignition.
Wear appropriate personal protective equipment.
Sweep up spilled material. Avoid creating dust.
Store in a partly filled, closed container until disposal.
Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling:
Use only with adequate ventilation.
Avoid breathing dust.
Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling.
Keep container closed.
See advice in section 8

Storage:
Store in tightly closed containers. In a cool/well-ventilated area.
Isolate from incompatible substances.
Keep away from sources of ignition.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

CALCIUM CARBONATE (LIMESTONE, MARBLE) 1317-65-3	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	SG OEL
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles 1317-65-3	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	ACGIH
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles 1317-65-3	**Value type**	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	ACGIH
Limestone 1317-65-3	**Value type**	Time Weighted Average (TWA):
	mg/m³	10

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

Eye protection: Safety goggles or safety glasses with side shields.
Protective eye equipment should conform to EN166.

Body protection: Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls: Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

General protection and hygiene measures: The workplace should be equipped with an emergency shower and eye-rinsing facility.

Hygienic measures: Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Take off contaminated clothing and wash before reuse.

Section 9. Physical and chemical properties

Appearance: Tan, Gray / Grey
Solid, Granules
Odor: Odourless / Odorless
Odor threshold (CA): No data available.
pH: No data available.
Melting point / freezing point: No data available.
Specific gravity: 2.6 - 2.95
Boiling point: No data available.
Flash point: Product is a solid
Evaporation rate: No data available.
Flammability (solid, gas): No data available.
Lower explosive limit: No data available.
Upper explosive limit: No data available.
Vapor pressure: No data available.
Vapor density: No data available.

Density:	No data available.
Solubility:	Negligible
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
VOC content:	No data available.

Section 10. Stability and reactivity

Reactivity/Incompatible materials:	Fluorine. Acids. Ammonium salts. Mercury and hydrogen mixtures.
Conditions to avoid:	Keep away from heat, spark and flame.
Hazardous decomposition products:	Calcium oxide.

Section 11. Toxicological information

Symptoms of Overexposure**:** None known.

Acute oral toxicity:

Limestone 1317-65-3	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 420 (Acute Oral Toxicity)

Acute inhalative toxicity:

Limestone 1317-65-3	Value type	LC50
	Value	> 3 mg/l
	Exposure time	4 h
	Species	rat
	Method	OECD Guideline 403 (Acute Inhalation Toxicity)

Acute dermal toxicity:

Limestone 1317-65-3	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

Limestone 1317-65-3	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Limestone 1317-65-3	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Limestone 1317-65-3	Result	not sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

Limestone 1317-65-3	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Limestone 1317-65-3	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Limestone 1317-65-3	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Repeated dose toxicity:

Limestone 1317-65-3	Result	NOAEL=1,000 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	48 ddaily
	Species	rat
	Method	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Toxicity:

Limestone 1317-65-3	Value type	LC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	not specified
Limestone 1317-65-3	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Daphnia
	Exposure time	48 h

	Species	Daphnia magna
	Method	not specified
Limestone 1317-65-3	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	not specified
Limestone 1317-65-3	Value type	EC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge of a predominantly domestic sewage
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

Section 13. Disposal considerations

Product

Method of disposal: Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages: Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:
Not dangerous goods

Railroad transport RID:
Not dangerous goods

Inland water transport ADN:
Not dangerous goods

Marine transport IMDG:
Not dangerous goods

Air transport IATA:
Not dangerous goods

Section 15. Regulatory information

Regulatory Information: Workplace Safety And Health Act (Chapter 354A, Section 40B) Workplace Safety And Health (Approved Codes of Practice) Notification 2020.
Workplace Safety And Health Act (Chapter 354A, Section 65) Workplace Safety And Health (General Provisions) (Amendment No.2) Regulations 2024

Global inventory status:

Regulatory list	Notification
TCSI	yes
TSCA	yes
AIIC	yes
DSL	yes
ENCS (JP)	yes
ISHL (JP)	yes
KECI (KR)	yes
PICCS (PH)	yes
IECSC	yes
NZIOC	yes

Section 16. Other information

Disclaimer:

This Safety Data Sheet has been generated based on Workplace Safety And Health Act (Chapter 354A, Section 40B) Workplace Safety And Health (Approved Codes of Practice) Notification 2020 and Workplace Safety And Health Act (Chapter 354A, Section 65) Workplace Safety And Health (General Provisions) (Amendment No.2) Regulations 2024 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.
Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).