LOCTITE SF 7701 PRIMER known as LOCTITE® 7701™ PRIMER PRISM®

SDS No. : 153658
V001.11
Revision: 08.04.2026
printing date: 09.04.2026

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE SF 7701 PRIMER known as LOCTITE® 7701™ PRIMER PRISM®

Other means of identification: LOCTITE SF 7701 AE1.75FOEN
Product code: IDH88195
Recommended use of the chemical and restrictions on use

Intended use: Primer, containing solvents
Manufacturer/Importer/Distributor Representative Company

Henkel Adhesive Tech. Vietnam Co., Ltd,
No. 7, Road 9A Bien Hoa II Industrial Zone,
Bien Hoa City,
810000 Dong Nai Province

Vietnam

Phone: +84 (28) 7100 6301
Fax-no.: +84 (28) 7100 6300

E-mail address of person responsible for Safety Data Sheet: ap-ua-psra.sea@henkel.com

Emergency Telephone for Chemical Accidents: FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +84 28 71006388

Section 2. Hazards identification

GHS Classification:

Hazard Class	Hazard Category	Target organ
Flammable liquids	Category 2	
Skin corrosion/irritation	Category 2	
Specific target organ toxicity - single exposure	Category 3	Central nervous system
Aspiration hazard	Category 1	
Acute hazards to the aquatic environment	Category 1	
Chronic hazards to the aquatic environment	Category 1	

GHS label elements:

Hazard pictogram:



Signal word: Danger

Hazard statement:	H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H410 Very toxic to aquatic life with long lasting effects.

Precaution:

Prevention:	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection. P264 Wash hands thoroughly after handling. P273 Avoid release to the environment.
Response:	P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P331 Do NOT induce vomiting. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P363 Wash contaminated clothing before reuse. P370+P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction. P391 Collect spillage.
Storage:	P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
n-Heptane 142-82-5	60- 100 %	Flammable liquids 2 H225 Skin corrosion/irritation 2 H315 Target Organ Systemic Toxicant - Single exposure 3 H336 Aspiration hazard 1 H304 Acute hazards to the aquatic environment 1 H400 Chronic hazards to the aquatic environment 1 H410
Methylcyclohexane 108-87-2	0.1- 1 %	Flammable liquids 2 H225 Skin corrosion/irritation 2 H315 Target Organ Systemic Toxicant - Single exposure 3 H336 Aspiration hazard 1 H304 Acute hazards to the aquatic environment 1 H400 Chronic hazards to the aquatic environment 1 H410
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	0.1- 1 %	Corrosive to metals 1 H290 Acute toxicity 3; Oral H301 Skin corrosion/irritation 1B H314 Serious eye damage/eye irritation 1 H318 Acute hazards to the aquatic environment 3 H402

Section 4. First aid measures

Inhalation: Move to fresh air, consult doctor if complaint persists.

Skin contact: Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact: Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion: Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

Indication of immediate medical attention and special treatment needed: Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema.

Do not induce vomiting.
Seek medical attention from a specialist.

Section 5. Fire fighting measures

Suitable extinguishing media: Foam, extinguishing powder, carbon dioxide.

Improper extinguishing media:	High pressure waterjet
Combustion behaviour:	Solvent containing flammable product. In case of fire toxic gases are released.
Specific hazards arising from the chemical:	Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.
Special protection equipment and precautions for firefighters:	Wear self-contained breathing apparatus.
Hazardous combustion products:	Oxides of carbon, oxides of nitrogen, irritating organic vapors.
Additional fire fighting advice:	In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions:	Remove sources of ignition. Ensure adequate ventilation. Wear protective equipment. Avoid contact with skin and eyes. See advice in section 8
Environmental precautions:	Do not empty into drains / surface water / ground water.
Clean-up methods:	Store in a partly filled, closed container until disposal. For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal. Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling:	Keep away from sources of ignition - no smoking. Vapours should be extracted to avoid inhalation. Avoid skin and eye contact. See advice in section 8
Storage:	Store in a cool, dry place. Refer to Technical Data Sheet.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

HEPTANE (ALL ISOMERS) 142-82-5	**Value type**	Time Weighted Average (TWA):
	mg/m³	800
	Remarks	VN OEL
Heptane, straight and branched isomers 142-82-5	**Value type**	Time Weighted Average (TWA):
	ppm	200
	Remarks	ACGIH
Heptane, straight and branched isomers 142-82-5	**Value type**	Short Term Exposure Limit (STEL):
	ppm	400
	Remarks	ACGIH
HEPTANE (ALL ISOMERS) 142-82-5	**Value type**	Short-term exposure limit (STEL):
	mg/m³	1,250
	Remarks	VN OEL
HYDROCARBONS (1-10 C) 142-82-5	**Value type**	Short-term exposure limit (STEL):
	mg/m³	300
	Remarks	VN OEL
HYDROCARBONS (1-10 C) 108-87-2	**Value type**	Short-term exposure limit (STEL):
	mg/m³	300
	Remarks	VN OEL
Methylcyclohexane 108-87-2	**Value type**	Time Weighted Average (TWA):
	ppm	100
	Remarks	ACGIH

Respiratory protection:

Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.
Protective eye equipment should conform to EN166.

Body protection:

Suitable protective clothing
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls:	Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.
General protection and hygiene measures:	The workplace should be equipped with an emergency shower and eye-rinsing facility.
Hygienic measures:	Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working. Take off contaminated clothing and wash before reuse.

Section 9. Physical and chemical properties

Appearance:	liquid
Odor:	Aliphatic
Odor threshold (CA):	No data available.
pH:	Not applicable, Product is non-soluble (in water).
Melting point / freezing point:	Not applicable, Product is a liquid
Specific gravity:	0.68
Boiling point:	96 - 98 °C (204.8 - 208.4 °F)
Flash point: (Tagliabue closed cup)	-2 °C (28.4 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	1.1 %(V)
Upper explosive limit:	6.7 %(V)
Vapor pressure:	47 hPa
(; 20 °C (68 °F); 50 °C (122 °F))	188 hPa
Vapor density:	3.45 Heavier than air.
Density:	0.68 g/cm3
Solubility:	Not miscible (20 °C)
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
VOC content: (2010/75/EC)	99.7 %

Section 10. Stability and reactivity

Reactivity/Incompatible materials:	Strong oxidizing agents.
Chemical stability:	Stable under recommended storage conditions.
Conditions to avoid:	Heat, flames, sparks and other sources of ignition.
Hazardous decomposition products:	No decomposition if used according to specifications.

Section 11. Toxicological information

Oral toxicity:	Acute toxicity estimate (ATE) : > 2,000 mg/kg Method: Calculation method

Symptoms of Overexposure**:** ASPIRATION: Coughing, shortness of breath, nausea. Delayed effect: bronchopneumonia or pulmonary oedema
SKIN: Redness, inflammation.
Vapors may cause drowsiness and dizziness.
Prolonged or repeated contact may cause eye irritation.

Acute oral toxicity:

n-Heptane 142-82-5	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Methylcyclohexane 108-87-2	Value type	LD50
	Value	> 3,200 mg/kg
	Species	rat
	Method	not specified
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Value type	Acute toxicity estimate (ATE)
	Value	215 mg/kg
	Species	
	Method	Expert judgement

Acute inhalative toxicity:

n-Heptane 142-82-5	Value type	LC50
	Value	> 29.29 mg/l
	Exposure time	4 h
	Species	rat
	Method	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Methylcyclohexane 108-87-2	Value type	LC50
	Value	> 26.3 mg/l
	Exposure time	1 h
	Species	rat
	Method	not specified

Acute dermal toxicity:

n-Heptane 142-82-5	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Methylcyclohexane 108-87-2	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rabbit
	Method	OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

n-Heptane 142-82-5	Result	irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Methylcyclohexane 108-87-2	Result	not irritating
	Exposure time	24 h
	Species	rabbit
	Method	Draize Test

Serious eye damage/irritation:

n-Heptane 142-82-5	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Methylcyclohexane 108-87-2	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

n-Heptane 142-82-5	Result	not sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)
Methylcyclohexane 108-87-2	Result	not sensitising
	Test type	Buehler test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

n-Heptane 142-82-5	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
n-Heptane 142-82-5	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	not applicable
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Methylcyclohexane 108-87-2	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Methylcyclohexane 108-87-2	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Methylcyclohexane 108-87-2	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Repeated dose toxicity:

n-Heptane 142-82-5	Result	
	Route of application	inhalation: vapour
	Exposure time / Frequency of treatment	16 weeks12 hours/day, 7 days/week
	Species	rat
	Method	
Methylcyclohexane 108-87-2	Result	NOAEL=250 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	28 ddaily
	Species	rat
	Method	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: H410 Very toxic to aquatic life with long lasting effects.

Toxicity:

n-Heptane 142-82-5	Value type	LC50
	Value	> 220 - 270 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Leuciscus idus
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
n-Heptane 142-82-5	Value type	EC50
	Value	1.5 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	other guideline:
Methylcyclohexane 108-87-2	Value type	LC50
	Value	2.07 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oryzias latipes
	Method	other guideline:
Methylcyclohexane 108-87-2	Value type	EC50
	Value	0.326 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	other guideline:
Methylcyclohexane 108-87-2	Value type	EC50
	Value	0.134 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)
	Method	other guideline:
	Value type	NOEC
	Value	0.022 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)
	Method	other guideline:
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Value type	LC50
	Value	> 100 - 220 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Leuciscus idus
	Method	DIN 38412-15
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Value type	EC50
	Value	50 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Value type	EC50
	Value	> 100 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)
	Method	EU Method C.3 (Algal Inhibition test)
	Value type	NOEC
	Value	> 100 mg/l

	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)
	Method	EU Method C.3 (Algal Inhibition test)
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Value type	EC50
	Value	330 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	17 h
	Species	
	Method	not specified

Persistence and degradability:

n-Heptane 142-82-5	Result	readily biodegradable
	Route of application	aerobic
	Degradability	70 %
	Method	other guideline:
Methylcyclohexane 108-87-2	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	0 %
	Method	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Result	not inherently biodegradable
	Route of application	aerobic
	Degradability	< 20 %
	Method	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	< 20 %
	Method	OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)

Bioaccumulative potential / Mobility in soil:

n-Heptane 142-82-5	Bioconcentration factor (BCF)	552
	Exposure time	
	Species	calculation
	Temperature	
	Method	QSAR (Quantitative Structure Activity Relationship)
n-Heptane 142-82-5	LogPow	4.66
	Temperature	
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Methylcyclohexane 108-87-2	Bioconcentration factor (BCF)	> 95 - < 321
	Exposure time	56 day
	Species	Cyprinus carpio
	Temperature	25 °C
	Method	other guideline:
Methylcyclohexane 108-87-2	LogPow	3.88
	Temperature	
	Method	other guideline:
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Bioconcentration factor (BCF)	< 0.4
	Exposure time	42 day
	Species	Cyprinus carpio
	Temperature	
	Method	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)

Section 13. Disposal considerations

Product

Method of disposal: Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages: Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:

Class:	3
Packing group:	II
Classification code:	F1
Hazard ident. number:	33
UN no.:	1206
Label:	3
Technical name:	HEPTANES (solution)

Railroad transport RID:

Class:	3
Packing group:	II
Classification code:	F1
Hazard ident. number:	33
UN no.:	1206
Label:	3
Technical name:	HEPTANES (solution)

Inland water transport ADN:

Class:	3
Packing group:	II
Classification code:	F1
Hazard ident. number:	33
UN no.:	1206
Label:	3
Technical name:	HEPTANES (solution)

Marine transport IMDG:

Class:	3
Packing group:	II
UN no.:	1206
Label:	3
EmS:	F-E ,S-D
Seawater pollutant:	Marine pollutant
Proper shipping name:	HEPTANES (solution)

Air transport IATA:

Class:	3
Packing group:	II
Packaging instructions (passenger):	353
Packaging instructions (cargo):	364
UN no.:	1206
Label:	3
Proper shipping name:	Heptanes (solution)

Section 15. Regulatory information

Regulatory Information: This Safety Data Sheet has been generated based on

LAW ON CHEMICALS No. 69/2025/QH15, issued on June 14, 2025;

Decree No. 24/2026/NĐ-CP, issued on January 17, 2026, ON THE LISTS OF CHEMICALS GOVERNED BY THE LAW ON CHEMICALS;

Decree No. 25/2026/NĐ-CP, issued on January 17, 2026, DETAILED REGULATIONS AND MEASURES FOR ORGANIZING AND GUIDING THE IMPLEMENTATION OF CERTAIN ARTICLES OF THE LAW ON CHEMICALS CONCERNING THE DEVELOPMENT OF THE CHEMICAL INDUSTRY AND CHEMICAL SAFETY AND SECURITY;

Decree No. 26/2026/NĐ-CP, issued on January 17, 2026, DETAILED REGULATIONS AND GUIDELINES FOR IMPLEMENTING CERTAIN ARTICLES OF THE LAW ON CHEMICALS REGARDING THE MANAGEMENT OF CHEMICAL ACTIVITIES AND HAZARDOUS CHEMICALS IN PRODUCTS AND GOODS;

Circular No. 01/2026/TT-BCT, issued on January 17, 2026, DETAILED REGULATIONS AND GUIDELINES FOR IMPLEMENTING CERTAIN ARTICLES OF THE LAW ON CHEMICALS AND GOVERNMENT DECREE NO. 26/2026/ND-CP DETAILING AND GUIDING THE IMPLEMENTATION OF CERTAIN ARTICLES OF THE LAW ON CHEMICALS REGARDING THE MANAGEMENT OF CHEMICAL ACTIVITIES AND HAZARDOUS CHEMICALS IN PRODUCTS AND GOODS;

Circular No. 02/2026/TT-BCT, issued on January 17, 2026, REGULATIONS ON SOME IMPLEMENTATION MEASURES OF THE LAW ON CHEMICALS AND GOVERNMENT DECREE NO. 25/2026/ND-CP DETAILING AND PROVIDING MEASURES FOR ORGANIZING AND GUIDING THE IMPLEMENTATION OF SOME ARTICLES OF THE LAW ON CHEMICALS CONCERNING THE DEVELOPMENT OF THE CHEMICAL INDUSTRY AND CHEMICAL SAFETY AND SECURITY;

Decree No. 161/2024/ND-CP, issued on December 18, 2024, ON LIST OF DANGEROUS GOODS, TRANSPORT OF DANGEROUS GOODS AND PROCEDURES FOR ISSUANCE OF LICENSES OR CERTIFICATES OF COMPLETION OF TRAINING PROGRAMS FOR DRIVERS OR ESCORTS TRANSPORTING DANGEROUS GOODS BY ROAD;

Decree No. 34/2024/NĐ-CP, issued on March 31, 2024, ON LIST OF DANGEROUS GOODS, TRANSPORT OF DANGEROUS GOODS BY INLAND WATERCRAFT;

Decree No. 33/2024/NĐ-CP, issued on March 27, 2024, IMPLEMENTING THE CONVENTION ON THE PROHIBITION OF THE DEVELOPMENT, PRODUCTION, STOCKPILING AND USE OF CHEMICAL WEAPONS AND ON THEIR;

Decree No. 37/2026/NĐ-CP, issued on January 23, 2026, ELABORATING CERTAIN ARTICLES AND MEASURES FOR ORGANIZING AND GUIDING THE IMPLEMENTATION OF THE LAW ON PRODUCT AND GOODS QUALITY.

If other regulatory information applies that is not already provided or updated elsewhere in this Safety Data Sheet, then it is described in this subsection.

Global inventory status:

Regulatory list	Notification
TSCA	yes
DSL	yes
KECI (KR)	yes
IECSC	yes
TCSI	yes
PICCS (PH)	yes
EINECS	yes

Section 16. Other information

Disclaimer:

This Safety Data Sheet has been generated based on Law On Chemicals No. 69/2025/QH15; Decree No. 24/2026/NĐ-CP; Decree No. 25/2026/NĐ-CP; Decree No. 26/2026/NĐ-CP; Circular No. 01/2026/TT-BCT; Circular No. 02/2026/TT-BCT; Decree No. 161/2024/ND-CP; Decree No. 34/2024/NĐ-CP; Decree No. 33/2024/NĐ-CP, and Decree No. 37/2026/NĐ-CP.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).